Datasheet for part number CA3106F24-28SF80A176

Our Catalog Part Number: CA3106F24-28S-F80-A176
Brand: Cannon Product Category: Circular Product Line: MIL-DTL 5015 Series I Series: MIL-C-5015

Product Datasheet	
Thread	Connector with threaded coupling
Shell Style	Plug, straight
Endbell Style	Endbell for flex tube
Gender	Socket
Shell Size	24
Contact Arrangement	24-28
Number of contacts	24 contacts size 16
Contact Type	AWG Crimp
Contact Plating	Gold 0,5 µ
Contacts installed	not assembled, packed separately
Shielding	no
Contact Rating at +20 °C (68 °F) (Size 15/15S/16/16S)	22 A
Contact Resistance (Size 15/15S/16/16S)	6 mΩ
Operating Voltage	In case of voltages greater than 50V the connector must be used in accordance with DIN VDE part 410, IEC 60364-4-41.
Insulator Resistance	Acc. To VG95319, part 2, test no. 5.12 and VG95210, part 32, test conditions B, standard insulator material > 1000 MΩ
Test Voltage	1050 Vrms
Air and Creepage Paths (Min)	0,7 mm
Ambient Temperature	Standard insulator material -55°/+125°C (-67/257°F)
Safety Provisions	IP65 acc. to DIN 40 050
Salt Spray Resistance	500 hours salt spray resistant
Mating Cycles	500 min
Sep. Force per Contact (Size 15/15S/16/16S)	1,0 N
Gage	For infos on Gage please see catalog VG95234, part 1
Coupling Torque	Closing: 14 Nm max / Opening: 0,8 Nm min
Contact Retention (Size 15/15S/16/16S)	35 N
Shell Material	Aluminium alloy
Shell Plating	Olive drab chromate coating over cadmium plating
Insulator and Gromet Material	Neoprene
Contact Material	Copper alloy
Harnessing Info: Contact Cross-Section	See assembly instruction
Harnessing Info: Insulator Diameter	See assembly instruction
Wire Stripping (Size 15/15S/16/16S)	6,2 mm
General Info	*All tests in accordance with VG95319 and/or if applicable with VG95210*

Specifications and dimensions subject to change.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular DIN Connectors ***category:***

Click to view products by ITT ***manufacturer:***

Other Similar products are found below :

CTV06RQF-25-8SA-LC CTV06RQF-25-8S-LC CTV06RQW-25-8SB-LC CTV06RW-25-20P CTV06RW-25-20PA CTV06RW-25-20PB CTV06RW-25-20PE-LC CTV06RW-25-20SB CTV06RW-25-20SE CTV07RW-17-8S(506) CTVP00RW-19-32S(506) CTVP00RW-9-35S(506) M83723/71R20416 M83723/71R22196 M83723/71W2039N M83723/71W24196 M83723/71W2419N M83723/72A1404N-LC M83723/72R1203N M83723/72W20418 M83723/72W22126 M83723/72W22556 M83723/72W2419N M83723/72W2461N M83723/73R2028N M83723/73R2039N M83723/73W1412N M83723/73W2039N M83723/74R1624N M83723/74R1808N M83723/74R2212N M83723/74W1203N M83723/74W1412N M83723/74W20416 M83723/74W2041N M83723/75R10058 M83723/75W2232N M83723/76R14157 M83723/76R20256 M83723/76W1808N M83723/76W2016N M83723/76W2461N M83723/77W2016N M83723/78R22327 M83723/78W2212N M83723/78W22556 M85049/50-5F D38999/20FF11AC D38999/20FJ20BB D38999/20FJ20SC