

DATA SHEET

53010000

SKINTOP® ST-M XL / STR-M XL

valid from:

24.04.2008

The polyamide based SKINTOP® ST-M XL / STR-M XL is designed for universal use, above all for functional safety in manufacturing of machines and equipment, in measuring, controlling and automation, as well as in the electronic technology and in manufacturing of robots.



Component parts:

Gland body with lamellar design Cap nut Seal insert O- Ring seal (M 40x1.5 - M 63x1.5) polyamide based plastic (UL 94-V2) polyamide based plastic (UL 94-V2) elastomere elastomere

Technical features:

Connecting thread: M 12x1.5 - M 63x1,5 in acc. to EN 60 423, Tab. 1

Functional thread: multi-start trapezoidal thread at M 12x1.5 - M 32x1.5

single-start trapezoidal thread at M 40x1.5 - M 63x1.5

IP protection: IP 68 - 5 bar/30 min., test in acc. to EN 60 529,

with o-ring at the connecting thread (M40 – M63)

Strain relief: Kat. A in acc. to EN 50262

Temperature range: - 20° C up to + 100° C

Type: ST-M XL

STR-M XL with reducing seal insert

UV-resistance color black

Approval:









For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

elaborated by:	1		
TE-VZ: M. Steinberg	Document:	DB53010000_1EN	page 1 of 1

Nr.: 0019/0894

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cable Glands, Strain Reliefs & Cord Grips category:

Click to view products by Lapp Kabel manufacturer:

Other Similar products are found below:

120-116-1-1-20BP 120-116-1-1-32BE 120-117-40 120-123-14 120-123-16 120-125-16 120-125-16R 120-125-16Y 120-125-24Y 120-125-28 120-125-32 120-125-32R 120-125-32R 120-125-56 120-126-14 120-126-16 120-126-20 120-126-20BL 120-126-20R 120-126-24 120-126-28 120-126-32 120-126-40BL 120-116-1-1-06BP-509 120-116-1-1-06CP 120-116-1-1-16BE 120-116-1-1-28BP 120-123-20 120-123-24 120-123-32 120-125-20 120-125-20Y 120-125-24 120-125-24R 120-125-28Y 120-126-14BL 120-126-16R 120-126-16Y 120-126-24BL 120-126-28BL 120-126-32BL 120-126-40 120-126-48 120-126-48BL 1300980012 1300980105 DBZM-6828 1498 15190-103 R2