



27 Glass Cloth Electrical Tape - OEM

Data Sheet

1. Product Description

3M™ 27 Glass Cloth Electrical Tape is a woven glass cloth tape designed to operate in 600-volt dry applications requiring high mechanical strength and resistance to high temperatures. The adhesive is a pressure-sensitive rubber thermosetting system. The glass cloth is specially treated and prepared to provide corrosion free protection. The glass cloth will not shrink, rot, or burn and has a high tensile strength.

- Contains pressure-sensitive thermosetting adhesive which performs at Class B temperature (130°F/266°C)
- Provides heat stable insulation for hot spot applications
- UL Recognized Component listing for 150°C (Guide OANZ2, File E17385)
- CSA Accepted Component 130°C, File LR93411
- Excellent tensile and dielectric strength

2. Applications

- Insulating electric and induction type furnace power supply leads
- Securing systems requiring high mechanical strength and resistance to high temperatures
- Splicing wire that is rated 130°C
- Insulating motor lead connections, switches and controls for furnaces and ovens
- Reinforcing insulation in electrical installations where heavy loads cause high heat and breakdown of original insulation (e.g., motor leads and switches)

Properties

Typical Values*

Color	White
Total Thickness ¹	7.0 mil (0,177 mm)
Tensile Strength ¹	150 lb./in (262 N/10mm)
Ultimate Elongation ¹	5%
Adhesion to Steel ¹	30 oz/in (3.3 N/10mm)

Electrical Properties

Typical Values*

Dielectric Strength ¹	3000 volts
Electrolytic Corrosion Factor ²	0.9

*These are typical values and should not be used for specification purposes.

Test Methods:

¹ ASTM-D-1000

² 3M Test Method

4. Specifications

3M™ 27 tape is a glass cloth electrical tape with a rubber thermosetting adhesive. The tape shall be white and 7 mils (0,177 mm) thick. The tape shall be coated on one side with pressure-sensitive adhesive, which shall not require heat, moisture, or other preparation prior to or subsequent to application. The adhesive coating shall be smooth and uniform and be free of lumps and bare spots. There shall be no separator between adjacent layers of the roll. The tape shall be UL Recognized under UL Standard 510. The tape shall perform at a temperature of 130°C without loss of physical or electrical properties.

Engineering/Architecture

All splices for 600-volt wire rated at 266°F (130°C) shall be insulated with a minimum of two half-lapped layers of 27 Glass Cloth Electrical Tape.

5. Shelf Life

27 Glass Cloth Electrical Tape has a 3-year shelf life from date of manufacture when stored under the following recommended storage conditions. Store behind present stock in a clean dry place at a temperature of 30°F and 50% relative humidity. Good stock rotation is recommended.

3M is a trademark of 3M.



Electrical Products Division
6801 River Place Blvd
Austin, TX 78726-9000
800-676-8381
<http://www.3M.com/elpd>

© 3M 1998
78-8124-4854-2(A)

Important Notice

Technical information provided by 3M is based on experience and/or tests believed to be reliable, but their accuracy is not guaranteed and the results may not be relevant to every user's application. For this reason 3M does not accept responsibility or liability, direct or consequential, arising from reliance upon any information provided and the user should determine the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence. All questions of liability relating to 3M products are governed by the seller's terms of sale subject where applicable to the prevailing law

If any goods supplied or processed by or on behalf of 3M prove on inspection to be defective in material or workmanship, 3M will (at its option) replace the same or refund to the Buyer the price paid for the goods or services. Except as set out above, all warranties and conditions, whether express or implied, statutory or otherwise are excluded to the fullest extent permissible at law.

3M and Scotchcast are trademarks of the 3M Company. Printed in the UK.

© 3M United Kingdom PLC, 1999

3M United Kingdom PLC
Electrical Products Group
Hudson Road
Bedford MK41 0HR
Tel: 01234 268868
Fax: 01234 229433

3M Ireland
Electrical products Group
3M House, Adelphi Centre
Dun Loaghaire, CO. Dublin, Ireland
Tel: (01) 2803555
Fax: (01) 2803509

3M Innovation

Jan. 2000

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [3m manufacturer](#):

Other Similar products are found below :

[SC401U](#) [98-0003-3071-6](#) [80-0012-6467-2](#) [00-054007-70220-7](#) [00-054007-34717-0](#) [5952-3/4"x15yds](#) [021200-40230](#) [6840-2X50-GRAY](#)
[6A11-A0121-007.0-0](#) [701-W](#) [7993MP-2CIRCLE-100](#) [FDV14-187C](#) [FE-5100-5126-4](#) [FE-5100-5273-4](#) [FE-5100-5492-0](#) [8124/14](#) [812510-100](#)
[8125/17](#) [813216](#) [8204-3LFM](#) [8425-8](#) [MNG14BCX](#) [FP301-1-6"-Clear](#) [FV14-6C](#) [920102-01-25-R](#) [927739-40](#) [929835-01-28-RK](#)
[929974-01-40-R](#) [951240-2520-AR-PR](#) [960X/980X](#) [98-0003-3075-7](#) [HF365/16SF](#) [HF36564-100](#) [HF625/26-30](#) [1/2-5-4492W](#) [1/2-5-5430](#) [1/2-](#)
[5-850S](#) [1/2-5-3431](#) [12X12-6-4056B](#) [12X12-6-433](#) [12X12-6-4930](#) [1311](#) [13-500-NB](#) [14526-EZ5B-300-02C](#) [1-4-4658F](#) [14520-EZAB-300-](#)
[0EC](#) [DSTK9013-3420](#) [DSTK9015-3402](#) [14T26-SZLB-200-0LC](#) [14T50-SZWB-100-0NC](#)