

FLAT TINNED COPPER BRAID, 150°C



BRAID SPECIFICATIONS

Description:

Flat tinned copper braid suitable for earth bonding straps.

Material:

Fully annealed tinned copper wire to BS EN 13602

Construction:

- 64 ends of 0.10 mm wire
(16×4×0.10 mm) – PRO-POWER-FB-10A
- 64 ends of 0.15 mm wire
(16×4×0.10 mm) – PRO-POWER-FB-15A
- 128 ends of 0.15 mm wire
(16×8×0.15 mm) – PRO-POWER-FB-30A
- 240 ends of 0.20 mm wire
(24×10×0.20 mm) – PRO-POWER-FB-63A
- 264 ends of 0.20 mm wire
(24×11×0.20 mm) – PRO-POWER-FB-90A

Part Number	Current rating* Max. (Amps)	Braid		CSA (mm ²)	Nom Width (mm)	Thickness (mm)	DC Resistance Max. @ 20°C (mΩ/ M)
		Type	Set up				
PRO-POWER-FB-10A	10.0	TC BRAID	16×4/ 0.10	0.50	2.00	0.50	40.07
PRO-POWER-FB-15A	15.0	TC BRAID	16×4/ 0.15	1.13	3.00	1.00	15.66
PRO-POWER-FB-30A	30.0	TC BRAID	16×8/ 0.15	2.26	5.00	0.75	7.83
PRO-POWER-FB-63A	63.0	TC BRAID	24×10/ 0.20	7.54	10.0	1.50	2.67
PRO-POWER-FB-90A	90.0	TC BRAID	24×11/ 0.20	8.29	11.0	1.75	2.135

* Note: Current Rating is based on temperature rise of 50°C above ambient and since braids are used under such varying conditions, is for guidance only.

GENERAL PROPERTIES

Working temperature: 150°C Max.

SAFETY CERTIFICATION

RoHS Compliance: In accordance to European Directive 2002/95/EC, issue 13.2.2

©2006 Tyco Electronics Corporation. All International Rights Reserved

Unless stated, all values are nominal.

tyco / *Electronics* / **Raychem**

Faraday Road, Dorcan, SWINDON, Wiltshire. SN3 5HH UK
Tel. 44 1793 528171 Fax 44 1793 572516 <http://www.raychem.com>

REVISION HISTORY

1	17/07/06	MC	Initial Release

Part Number: **PRO-POWER-FB**

Prepared By: M. Coward
Reviewed By: A. Prowse

Page
1 of 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Wire Identification](#) category:

Click to view products by [Pro Power](#) manufacturer:

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)