

308

Wiha SoftFinish®. The Specialist for Dry & General Applications.

6,5×125 Withar Soft



The right tool at a glance, thanks to the printed screw symbol on the handle end.

Due to the solid steel cap and hex blade extending through the handle, there is no loss of impact energy when a precise hammer blow is applied.

Blade with hex bolster for wrenches to use on particularly tight screws.






SoftFinish® Advantages:

- Multi-component SoftFinish® handle provides maximum user comfort
- · Ergonomically perfect handle design
- Available in versions with round blade, hex blade or hex blade with solid steel cap
- Blade made of high quality chrome-vanadium-molybdenum steel, through-hardened and chrome plated
- Wiha ChromTop-finish on tip for a perfect fit every time
- Printed screw symbol on handle end for fast identification

The Wiha SoftFinish® zone features a solid moulded core with soft outer grip. This requires less force, yet achieves 40% more torque than conventional handles. The handle is shaped to fit comfortably in the hand, providing maximum torque forces in dry and general working conditions.

If a stuck screw has to be loosened, a precise hammer blow can be applied to the solid steel cap. Due to the hex blade extending trough the handle to the steel cap, there is no loss of impact energy.







## Wiha SoftFinish®. The Specialist for Dry & General Applications.

#### For Slotted Screws.

# 1 E.5 x (sw. Webs-SoftFinish str.

Slotted Screwdriver.

Blade: Round blade.

Handle:

High quality chrome-vanadium-molybdenum steel, through

hardened, chrome-plated.

Wiha ChromTop finish on tip for a perfect fit every time.

Ergonomic Wiha SoftFinish® handle, multi-component with

roll-off protection.

Standards: DIN 5265, ISO 2380.

Extra: Especially for dry and general applications.

Order-No.	. D:	==	0:	==	•:	-+	-	
00684 6	2.0•	65	0.4	169	2.0	23	10	
006853	2.5	75	0.4	179	2.5	23	10	401-7353
00686 0	3.0•	80	0.5	184	3.0	23	10	330-835
00687 7	3.0	100	0.5	204	3.0	23	10	ď
00689 1	3.0•	150	0.5	254	3.0	23	10	
00690 7	3.0•	200	0.5	304	3.0	23	10	
00691 4	3.5	100	0.6	204	3.5	23	10	401-7365
26931 9	3.5•	200	0.5	304	3.5	23	10	
00692 1	4.0	100	0.8	211	4.0	30	10	130-859
00694 5	4.0•	150	0.8	261	4.0	30	10	
00695 2	4.0•	200	0.8	311	4.0	30	5	
00696 9	4.00	300	0.8	411	4.0	30	5	
00697 6	4.5•	125	0.8	236	4.5	30	10	
006983	5.5	125	1.0	236	5.5	30	10	
00700 3	5.5	150	1.0	261	5.5	30	10	830-872
00701 0	5.5•	200	1.0	311	5.5	30	10	
00702 7	5.5•	300	1.0	411	5.5	30	5	
00704 1	6.5	100	1.2	218	6.0	36	10	
00703 4	6.5	150	1.2	268	6.0	36	10	835-432
00706 5	6.5•	200	1.2	318	6.0	36	5	
0708 9	8.0	150	1.2	274	7.0	41	10	
0707 2	8.0	175	1.2	299	7.0	41	10	130-902
0709 6	8.0	175	1.6	299	7.0	41	5	
07119	10.0	200	1.6	324	8.0	41	5	830 - 926
07126	12.0	250	2.0	374	8.0	41	5	
07133	14.0	250	2.5	374	11.0	41	5	
Non-DIN	sizes.							

#### For Slotted Screws.



308 Slotted Screwdriver.

Blade: Hex blade with hex bolster for additional torque.

High quality chrome-vanadium-molybdenum steel, through

hardened, chrome-plated.

Wiha ChromTop finish on tip for a perfect fit every time.

Ergonomic Wiha SoftFinish® handle, multi-component with

roll-off protection.

Standards: DIN 5265, ISO 2380.

Handle:

Extra: Especially for dry and general applications.

Order-No.	(D)		0;	==	<b>O</b> 1	01	-+		7
00731 7	3.5	75	0.6	186	4.0	-	30	10	
00732 4	4.50	90	0.8	201	4.0	-	30	10	
00733 1	5.5	100	1.0	213	5.0	8	36	10	401-7328
007348	6.5	125	1.2	238	6.0	10	36	10	
00735 5	7.0•	125	1.1	238	6.0	10	36	10	401-7330
00736 2	8.0	150	1.2	268	8.0	13	41	10	
00737 9	9.0•	150	1.4	268	8.0	13	41	10	401-7341
00738 6	10.0	175	1.6	293	8.0	13	41	5	
007393	12.0	200	2.0	318	10.0	16	41	5	
00740 9	14.0	250	2.5	368	10.0	16	41	5	
- NI DINI	-1								

Non-DIN sizes.



Slotted Screwdriver.

Blade: Hex blade extending through handle, hex bolster for

additional torque, solid steel cap.

High quality chrome-vanadium-molybdenum steel, through

hardened, chrome-plated.

Wiha ChromTop finish on tip for a perfect fit every time.

Handle: Ergonomic Wiha SoftFinish® handle, multi-component with

roll-off protection.

Standards: DIN 5265, ISO 2380.

Extra: Especially for dry and general applications.

Order-No.	(D)	==	0;	===	<b>•</b> 1	01	-+		
03223 4	3.5	75	0.6	186	4.0	2	30	10	
03224 1	4.5	90	0.8	201	4.0	-	30	10	
03225 8	5.5	100	1.0	213	5.0	8	36	10	
03226 5	6.5	125	1.2	238	6.0	10	36	10	
03228 9	8.0	150	1.2	271	8.0	13	41	5	
03230 2	10.0	175	1.6	296	8.0	13	41	5	
03231 9	12.0	200	2.0	321	10.0	16	41	5	
03232 6	14.0	250	2.5	371	10.0	16	41	5	
. Non DIN	oizoo								

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

## Click to view similar products for wiha manufacturer:

Other Similar products are found below:

56818	00573	01030	75802	21248	26307	27302	27835	28050	28084	28390	28501	28507	28581	26113	26539	26626	26629	26804
28522	28882	32573	32705	32712	32752	32954	34700	36268	36791	38043	43618	44506	54095	31705	31890	32090	32093	32714
32793	36453	37225	39104	41106	44503	45811	46796	09393	66991	74586	74732							