



Consumer and Office Business Product Information Sheet

Effective : November. 2010

Scotch® Easy Tear Tape



General Description:

Easy to tear light yellow transparent tape for everyday multi-purpose sealing, labeling and repair

Product Name	Description
Scotch® Easy Tear Tape	An easy to tear light yellow transparent tape for everyday multi-purpose sealing, labeling and repair

Product Characteristic	Value*
Backing:	28 microns bi-oriented polypropylene film
Adhesive:	Waterbased Synthetic Acrylic
Adhesion to steel :	125 cN/cm
Tensile strength (on the roll) :	2 daN/cm width
Elongation at break (on the roll) :	20%
Unwind :	2.24 N/cm
Total Thickness:	40 microns
Color:	Light Yellow
	<i>*These are typical values. 3M does not guarantee every roll will have these specific test values.</i>

Features/Advantages Benefits:

Feature (HAS)	Advantage (WHICH MEANS)	Benefit (SO THAT)
Waterbased acrylic adhesive	Long-aging, non-yellowing.	Will not dry out or stain. Saves time and money.
	Good adhesion to a variety of surfaces.	Eliminates the need for multiple tapes for the office.
Bi-oriented Polypropylene backing	Thin	Items taped together are not bulky, helps keep a professional look.
	Extruded film	Non-solvent process. Fewer emissions released into the atmosphere during processing.
	Easy tear	Makes the job to tear by hand easier

APPLICATIONS:

Tape for everyday multi-purpose sealing, labeling and repair.

TECHNICAL NOTES:

Though the product will last almost indefinitely in normal office conditions, the shelf life of the tape is 1 year from the date of manufacture.

Best storage conditions are 20°C and 50% relative humidity

Best applications are for paper to paper, or posting lightweight single-sheet paper to smooth dry surfaces.

Solventless construction with no LAB and no primer coatings

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [3m](#) manufacturer:

Other Similar products are found below :

[SC401U](#) [98-0003-3071-6](#) [80-0012-6467-2](#) [00-054007-70220-7](#) [00-054007-34717-0](#) [5952-3/4"x15yds](#) [6840-2X50-GRAY](#) [6A11-A0121-007.0-0](#) [701-W](#) [7993MP-2CIRCLE-100](#) [FE-5100-5126-4](#) [FE-5100-5273-4](#) [FE-5100-5492-0](#) [8124/14](#) [812510-100](#) [8125/17](#) [813216](#) [8204-3LFM](#) [8425-8](#) [MNG14BCX](#) [FP301-1-6"-Clear](#) [FV14-6C](#) [920102-01-25-R](#) [927739-40](#) [929835-01-28-RK](#) [951240-2520-AR-PR](#) [960X/980X](#) [98-0003-3075-7](#) [HF365/16SF](#) [HF36564-100](#) [HF625/26-30](#) [1/2-5-4492W](#) [1/2-5-5430](#) [1/2-5-850S](#) [1/2-5-3431](#) [12X12-6-4056B](#) [12X12-6-433](#) [12X12-6-4930](#) [1311](#) [13-500-NB](#) [14526-EZ5B-300-02C](#) [1-4-4658F](#) [14520-EZAB-300-0EC](#) [14T26-SZLB-200-0LC](#) [14T50-SZWB-100-0NC](#) [1-5-3437](#) [1-5-4496W](#) [1-5-4943F](#) [1-5-363](#) [1-5-5451](#)