

ALPHA WIRE

CUSTOMER PRODUCT SPECIFICATION

Part Number: B954031
Page 1 of 2 Pages

Issue: 1
Issue Date: 8/23/2010
Effective Date: 10/18/2010

A. Construction

Diameters (mm)

- 1) Component 1 3 X 1 COND
- a) Conductor 22 (7/30) AWG TC
- b) Insulation 0.25 Wall, Nom. PVC, Semi Rigid
- (1) Color Code Alpha Wire Color Code E

0.76
1.27

Cond	Color	Cond	Color	Cond	Color
1	BLACK	2	BROWN	3	RED

- 2) Cable Assembly 3 Components Cabled
- a) Twists: 31.5 Twists/meter (min)
- b) Core Wrap Clear Mylar Tape, 25% Overlap, Min.
- 3) Jacket 0.81 Wall, Nom., PVC 4.45 (4.70 Max.)
- a) Color(s) GREY
- b) Ripcord 1 End 810 Denier Nylon
- c) Print ALPHA WIRE-* P/N B954031
- 0.35MM2 (22AWG) (UL) TYPE CM 105C OR AWM 2464
- VW-1 CE ROHS (SEQ METERS)
- * = Factory Code

B. Applicable Specifications

- 1) UL
 - a) Component 1 AWM/STYLE 10002 105°C / 300 V_{RMS}
 - b) Overall AWM/STYLE 2464 80°C / 300 V_{RMS}
 - CM 105°C
 - VW-1
- 2) IEC EN 60332-1 Flame Behavior
- EN 60332-2 Flame Behavior
- 3) CE: LVD 73/23/EEC Amendment 93/68/EEC

C. Environmental Compliance

- 1) EU Directive 2002/95/EC(RoHS):
All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture.
- 2) REACH Regulation (EC 1907/2006):
This product does not contain any of the substances listed on the European Union REACH Substance of Very High Concern (SVHC) candidate list, dated 30 March 2010, in excess of a concentration of 0.1% weight/weight.

D. Physical & Mechanical Properties

- 1) Temperature Range -30 to 105°C
- 2) Bend Radius 10X Cable Diameter
- 3) Pull Tension 16.5 Lbs, Maximum
- 4) Sunlight Resistance Yes

E. Electrical Properties

- (For Engineering purposes only)
- 1) Voltage Rating 300 V_{RMS}
- 2) Capacitance 77.08 pf/m @1 kHz, Nominal Conductor to Conductor
- 3) Inductance 0.5904 µH/m, Nominal
- 4) Conductor DCR 53.792 Ω/Km @20°C, Nominal

F. Other

- 1) Packaging Flange x Traverse x Barrel (inches)
- a) 3280 FT 18 x 12 x 8 Continuous length
- b) 1640 FT 12 x 10 x 5 Continuous length
- c) 328 FT 10 x 4 x 3.5 Continuous length
- d) 164 FT 6.5 x 4 x 2.5 Continuous length

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE
CUSTOMER PRODUCT SPECIFICATION

Part Number: B954031
Page 2 of 2 Pages

Issue: 1
Issue Date: 8/23/2010
Effective Date: 10/18/2010

[Spool dimensions may vary slightly]

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [alpha](#) manufacturer:

Other Similar products are found below :

[6387-SL001](#) [F2213/64-BK103](#) [2924 GR001](#) [2924 YL005](#) [2916 WH005](#) [2918 BL005](#) [2934 BK001](#) [2924 BL005](#) [2920 BK005](#) [2920 OR001](#)
[2918 SL005](#) [2928 BK005](#) [2920 OR005](#) [2922 GR005](#) [2918 RD001](#) [2916 RD005](#) [2918 WH001](#) [2932 BK001](#) [2936 VI005](#) [2926 BK005](#) [2936](#)
[BR005](#) [2936 GR001](#) [2934 WH005](#) [2926 GR001](#) [2922 GR001](#) [2930 SL005](#) [2936 BL005](#) [2936 SL005](#) [2932 WH005](#) [2936 WH001](#) [2918](#)
[RD005](#) [2916 BL005](#) [2920 YL005](#) [2926 SL005](#) [2916 GR005](#) [2934 WH001](#) [2920 BL005](#) [2920 SL005](#) [2924 GR005](#) [2924 VI005](#) [2920 VI005](#)
[2926 OR005](#) [2934 GR001](#) [2932 OR005](#) [2916 GR001](#) [2934 BK005](#) [2928 OR005](#) [2918 OR005](#) [2922 OR005](#) [2930 OR005](#)