Linemaster Switch Corporation

29 Plaine Hill Road POB 238

Woodstock, CT 06281-0238 USA

Toll Free: (800) 974-3668 (US Only) Telephone: (860) 974-1000 Fax: (860) 974-0691

E-Mail: service_266@linemaster.com Web site: www.linemaster.com

Item # 972-S, Aquiline Foot Switch



Aquiline Foot Switch

- · Maximum versatility, total performance
- SPDT, DPDT, or two-stage Operation.
- Rustproof and corrosionproof reinforced polymeric material for rugged duty.
- Two stage model has cast zinc cover and formed steel base
- · Non-skid base pad.
- Raised ribs on treadle for positive traction during operation.
- Attractive non-glare finish. Custom colors, and color matching available with quantity orders.
- Integrated adjustable strain relief clamp accommodates cord sizes from .250 Dia. to .400 Dia.

SPECIFICATIONS

Description	Two Stage Momentary
Color	Black
Circuit	SPDT Each Stage
Form	С
Electrical Rating	15 A 125-250 VAC 1/2 H.P. 125-250 VAC
Standard	EN 60529 Degree of Protection IP20, 971-SWNO210 &971-SWNO210A are NEMA type 1, 4X, 6 &6P - UL Enclosure 1, 4X, 6 &6P, and IP68
Size	4 x 3 7/16 x 1 5/32 Inch
Weight Approx.	3.6 Oz.
Weight Approx.	Metal Aquiline .9 lbs
Note	Die cast metal housing

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for 9V Battery Snaps & Contacts category:

Click to view products by Linemaster manufacturer:

Other Similar products are found below:

139B 173P 266 491-SC36 642-S 1295 12BC2202-GR 2238 2241 2242 2243 227 236 237 2410.0301-01 262 270 271 121-0626/I-GR 121-0426/IM-GR 121-0626/T-GR 121-1026/I-GR 12BH617T-GR 123-5025-GR 12BC269-GR 12BH615D-GR 121-0624/O-GR GEM-V36 531-SWHOX 971-SB T-91-SC3 632-DA 634-DA 636-S 635-S 632S TWIN DIVIDER 3C-30A2-S 3B-30A2-S 534-SS 491-S L-2-S 971-SO 972-S 606-1300-011 606-1800-012 616-1800-247 6254-OB 6289-PP 6289-CC