Email

Products

Industries

Resources

My Account

Innovation

Support Center

🗓 Share

Home > Products > Product Feature Selector > Product Details

5533286-3 Product Details



Product Highlights:

- Connector
- Plug
- 128 Positions
- PCB Mount Style = Through Hole
 - PCB Mounting Orientation = Right Angle

About TE

View all Features

Quick Links

- Pricing & Availability
- Search for Tooling
- View Connectors (2)
- Product Feature Selector
- Contact Us About This Product

Print

TE Internal Number: 5533286-3 Active

5533286-3











Documentation & Additional Information

• ASSEMBLY, PIN, RIGHT ANGLE, HDI, LEAD-FREE, 4 ROW, W... (PDF, English)

Catalog Pages/Data Sheets:

None Available

Product Specifications:

• Connector, Interconnect, High Density (PDF, English)

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version O)
- 3D Model (IGES, Version O)
- 3D Model (STEP, Version O)

Additional Information:

Product Line Information

Related Products:

- Tooling
- Connectors (2)

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Connector
- Gender = Plug
- PCB Mount Style = Through Hole
- PCB Mounting Orientation = Right Angle
- Make First / Break Last = No
- PCB Mount Retention = Without

Termination Features:

• Termination Post Length (mm [in]) = 3.05 [0.120]

Contact Features:

- Contact Configuration = Four-Beam
- Solder Tail Contact Plating = Tin
- Contact Plating, Mating Area, Material = Gold (30)
- Contact Base Material = Phosphor Bronze
- Underplate Material = Nickel

Housing Features:

- Centerline (mm [in]) = 2.54 [0.100]
- Mating Alignment = Without
- Housing Material = Polyphenylene Sulfide (PPS)
- Housing Color = Brown
- Housing Material Temperature = High

Configuration Features:

- Number of Positions = 128
- Number of Rows = 4
- Center Guide = Without

Industry Standards:

- Government/Industry Qualification = No
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin-in-Paste capable to 245°C, Pin-in-Paste capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

Brand = AMP

Corporate Information
About TE
Investors
News Room
Supplier Portal
Careers
Terms & Conditions

Careers
Terms & Conditions
Privacy Policy
AODA Accessibility Policy
AODA Multi-Year Accessibility
Plan

Quick Links
Distributor Inventory
Product Cross Reference
Documents & Drawings
Product Compliance Support Center
Site Map

Customer Support
Email or Chat With Us
Find a Phone Number
Knowledge Base
Manage Your Account

Keep Me Informed



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

2332816-1 89006-1137LF 650827-1 65762-001LF 73474-201LF 74040-1346 74075-0267 1410191-1 1410337-1 1410368-3 1410964-2 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 2187462-1 2226278-6 KA81-07 91290-101LF 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 2226279-2 22354-8 437-5040-000 5-1393565-0 532449-3 532803-2 34745-0001 0736440217 1-1393708-5 72388-0021LF 73774-1000 740401386 532939-1 5-531355-3 5532901-3 85838-180LF HM1S43TRR460H6PLF 0760205010 1-966831-4 3-1469268-7