

Standard Brass Ended

Our standard range of BS89/IEC51 class 1 or class 0.5 shunts can be current rated from 5A to 10000A with 50mV to 300mV output.

Technical Specification

Operating Temperature:	-20°C TO +40°C
Permissible Overload:	
Continuous	1.2 x rated current
5 seconds	5 x rated current up to 2kA
10 seconds	2 x rated current for 2kA-5kA
Shunt Leads:	Millivolt leads can be supplied upon
	request (standard length = 760mm)
Order example:	A brass ended shunt with 1000A rated
	current and 100mV output, class 1 is:
	SHB1000A100-CLASS1



Dimensions (mm)

	A													
Current (A)	Туре	50mV	60mV	75mV	100mV	150mV	200mV	250mV	300mV	В	С	D	E	F
5-35	1	95	95	95	114	114	172	172	167	22	10	11	-	7
40-200	1	95	95	95	114	114	172	172	267	32	12	13	-	10
225- 440	1	95	95	95	114	121	172	172	267	32	20	25	-	10
450- 1700	2	95	95	95	114	121	172	172	267	67	25	25	41	10
1800- 3400	3	95	95	95	114	121	172	-	-	111	38	81	57	10
3500- 5000	3	95	95	95	114	121	-	-	-	140	38	114	90	12
5500- 7000	4	83	83	96	-	-	-	-	-	230	38	114	90	12
7500- 10000	5	83	83	96	-	-	-	-	-	320	38	114	90	12



brass ended shunts





Contact sales: sales@hobut.co.uk

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Digital Panel Meters category:

Click to view products by Hobut manufacturer:

Other Similar products are found below :

M00558-00 01.098.1658.1 70.360.4828.0 72331-00 85310-25 86427-26 86642-00 87268-13 87316-00 87719-26 98107-56 HB8260-R36-90 DMS-20ACV-3-R-C EM11DINAV81XR1X 25.325.3253.1 25.325.4253.1 25.330.0453.1 25.350.0553.0 20046-20 20182-23 AP1020 AP1021 25.320.5053.0 25.350.3453.1 25.394.3653.1 25.521.3253.0 28006-01 04.630.1080.0 20078-20 EM11DINAV81XO1X 85874-26 87166-00 87895-00 28000-03 K3GN-NDT1-FLK 24VDC 82322K-11 86641-00 87004-00 MV15-DC-20V-110V-CU HB8260R4890 20125-21 86640-00 2CMA100166R1000 N27D 00M0 DMG 100 DMG 110 DMG 800 L01 DMK 01 DMK 01 R1 DMK 11