Product data sheet Characteristics

NSYTBP292412H

PC box IP66 IK08 RAL7035 Int.H275W225D120 Ext.H291W241D128 opaque PC cover H60



Main

IVIAIII		
Range	Thalassa	
Product name	Thalassa TBP	
Device application	Multi-purpose	
Product or component type	Industrial box	
Height	291 mm	
Width	241 mm	
Depth	128 mm	
Internal height	275 mm	
Internal width	225 mm	
Internal depth	120 mm	
Enclosure mounting	Wall mounted	
Device composition	1 x body 1 x cover 4 x cover screw	
Body type	One piece moulded	
Type of front cover	High plain cover	
Cover fixing	Plastic screws	
Lock type	Outside sealed area : flat screwdriver captive screw	
Removable parts	Cover, by captive screws	

Complementary

Polycarbonate	to
Grey (RAL 7035)	
IEC 62208 UL 508 A	Ties Care Care Care Care Care Care Care Care
DEMKO TÜV UL SEMKO	daimer. This do
	Grey (RAL 7035) IEC 62208 UL 508 A DEMKO TÜV UL

Electrical insulation class	Class II
IP degree of protection	IP66 conforming to NEMA 4.4X
IK degree of protection	IK08 conforming to IEC 62262
Fire resistance	960 °C
Ambient air temperature for storage	-1560 °C
Ambient air temperature for operation	-2580 °C

Offer Sustainability

Not Green Premium product	
Compliant - since 0940 - Schneider Electric declaration of conformity	
Schneider Electric declaration of conformity	
Reference not containing SVHC above the threshold	
Reference not containing SVHC above the threshold	
Need no specific recycling operations	

Contractual warranty

	
Warranty period	18 months