

Smart power solutions for car body applications





Content

Introduction	4
High-side switches	7
High-side switches - Single-channel	7
High-side switches - Dual-channel.....	9
High-side switches - Quad-channel	11
High-side switches with SPI and asymmetrical output	12
High-side switches for 24 V applications - Truck devices.....	12
Low-side switches.....	13
OMNIFET III™	13
OMNIFET™	14
Voltage regulators.....	15
Door actuators drivers with embedded Power Management	16
Door modules	18
Power management for automotive systems.....	20
Multifunctional voltage regulators	21
Motor control ICs - DC motor drivers	22
Motor control ICs -	
Application Specific Standard Product	23
Motor Control ICs - Motor pre-drivers.....	23
Special devices.....	24
Reverse battery.....	24
Integrated solenoid driver - Injection gas system.....	24
Ignition drivers	24
Development support tools	25
EZ-Boards: the easiest and smartest way to evaluate VIPower products	26
EZ-Boards for 12 V High Side Switches (M0-7)	26
EZ-Boards for 12 V Full Bridges (VNH5/VNH7)	27
EZ-Boards for 24 V Smart Switches (M0-5T)	27
Evaluation boards for power management and system basis ics	27



Introduction

High-side switches

ST's offer of fully-protected automotive high-side switches (HSDs) is the broadest in the market. Having an unmatched range of packages, on-resistances, number of output channels and diagnostic options, HSDs are able to drive resistive, inductive and capacitive grounded loads in compliance with the stringent safety and reliability requirements of automotive applications.

Based on its proprietary VIPower™ technology, ST's high-side switches have 3 V and 5 V CMOS compatible I/Os for control and vertical mosfet for the power outputs, and are the perfect companions for a microcontroller.

VIPower™ MO-7 SERIES

The MO-7 series is the ultimate VIPower product generation, born to deliver the widest range of on-state resistance and number of channels with full pin-to-pin compatibility in the smallest packages. Further application benefits are:

- Best-in-class EMI performance, short-circuit protection and robustness
- Lower quiescent current
- Precise load-current, battery voltage and device temperature analog feedback

VIPower™ MO-5 SERIES

The MO-5 series is the largest family of VIPower high-side switches developed to drive any kind of automotive load.

The devices are equipped with digital status or analog current sense feedback. Further advantages are available in the MO-5Enhanced options:

4


- Extended load compatibility due to higher current limitation
- Instantaneous diagnosis of short-to-ground or overload
- OFF-state diagnosis for the analog current sense option ('E' types)

VIPower™ Zero series

ST's VIPower™ Zero series offers innovative and high-performance protected switches for driving high power applications. This series covers today's growing demand for intelligent power devices able to drive and protect high-power loads such as those used in high-current fan motors, heaters and protected battery lines in electrical power distribution systems.

KEY FEATURES

- Complete family of low on-resistance protected solutions
- Output re-activation during reverse polarity
- State-of-the-art and adaptable protection strategy
- Sophisticated diagnostics
- Cold-cranking capability (device option)
- Device option with extended diagnostics capability cover a wide range of load currents



5

Door actuator drivers with embedded Power Management

The new L99DZ1x0 Family brings higher performances in the Door Zone Applications: novel devices embed, in the same package, Power management power supply functionality (including various standby modes, as well as LIN and HS CAN physical communication layers) together with all the Actuators for main Door loads. The two low-drop voltage regulators of the devices supply the system microcontroller and external peripheral loads such as sensors and provide enhanced system standby functionality with programmable local and remote wake-up capability.

An advanced driver provides logic and protection for external Mosfet transistors in H-bridge, or Dual Half Bridge, configuration . Other features include integrated bridges for double door-lock control, mirror fold, and mirror-axis control, together with high-side drivers for bulbs and LEDs control. In addition, high-side drivers allow small resistive loads driving for increasing system integration level. An additional gate drive can control an external MOSFET in high-side configuration to supply a resistive load connected to GND (e.g. mirror heater). An electro-chromic mirror glass can be controlled using the integrated SPI-driven module in conjunction with an external MOS transistor.

All the embedded outputs come with protection and supervision features such as Current Monitor (only for High Side outputs), Openload, Overcurrent, Thermal Warming, Thermal Shutdown (increased up to 175 °C as mimimum threshold) and Themal Expiration. Devices include two Fail safe low side switches that are intended to be used to turn off the gates of the external high-side MOSFETs in the power window h-bridge if a fatal error happens. The ST standard SPI interface (4.0) allows control and diagnosis of the device and enables generic software development.

Low-side switches

Fully-protected, low-side switches safely drive resistive, inductive and capacitive loads with one terminal connected to the battery, in compliance with the stringent safety and reliability requirements of automotive applications.

ST's low-side switches offer a power output in addition to control and diagnostic function in one single chip and are available with both single- and dual-channel options.

OMNIFET III

Built in the VIPower M0-5 technology, the OMNIFET III series addresses a broad range of applications in tiny packages, delivering protection and diagnostic features. Key application benefits include:

- Low stand-by current consumption
- Overload and open-load diagnostic
- Optimized EMI performances
- Enhanced short circuit robustness

OMNIFET AND OMNIFET II

ST offers a wide portfolio of low-side switches suitable for any kind of automotive load and applications rated up to 70 V.

Door module drivers

ST's door module drivers family is designed for state-of-the-art automotive door electronics. Devices are characterized by a scalable actuator driving concept, which includes packages and software specially designed to satisfy a wide range of door module variants. Drivers support all regular door module loads such as lock motors, mirror levelling and foldering, defroster, electro-chromic mirror glass, window lift and several lighting functions from incandescent bulbs to LEDs.

Power management ICs for automotive systems

6

Power management ICs come with enhanced power supply functions and they include various standby modes as well as LIN and HS-CAN (also with HS-CAN supporting Partial Network) physical communication layers. They offer two low-drop voltage regulators to supply the system microcontroller and external peripheral loads (sensors) and provide superior system standby functionality with programmable local and remote wake-up capabilities. Other features, like high-side and low-side drivers or operational amplifiers, are embedded to increase the system integration level.

What's more, ST has a wide multifunctional voltage regulator portfolio that meets all automotive infotainment needs. They are protected against load dump and support battery voltage variations and transients, providing multiple linear or switching voltage outputs, with or without an I²C bus, and have a very low standby quiescent current.

Motor control ICs

Taking advantage from the proprietary VIPower™ silicon technology and from miniaturized packaging solutions, the VNH family of fully integrated H-bridges combines in single packages a matchless level of diagnostic and sensing capabilities together with solid protections and robust vertical structure MOSFETs making automotive DC motor control applications - ranging from a few up to hundreds of watts - more robust and compact.

High-side switches

HIGH-SIDE SWITCHES – SINGLE-CHANNEL

Part number	Package	Supply voltage (V_{CC})		Absolute max supply voltage (V)	On-state resistance $R_{DS(ON)}$ (mΩ)	Output current limit (I_{lim}) (A)	Diagnostic feedback	Short-circuit protection
		Min (V)	Max (V)					
VIPower™ M0-7 series (to be preferred for new developments)								
VN7000AY^(*)	PowerSSO-36	3	28	38	1.5	190	Analog multi-sense	Autorestart & Latch-off
VN7003AH	Octapak	3.2	28	38	3.5	100	Analog current sense	Autorestart
VN7003ALH	Octapak	3.2	28	38	3.5	100	Analog current sense	Autorestart & Latch-off
VN7004CH	Octapak	4	28	38	4	100	Analog current sense	Autorestart
VN7004CLH	Octapak	4	28	38	4	100	Analog current sense	Autorestart & Latch-off
VN7007AH	Octapak	4	28	38	7	100	Analog current sense	Autorestart
VN7007ALH	Octapak	4	28	38	7	100	Analog current sense	Autorestart & Latch-off
VIPower™ M0-5 Enhanced (M vers.) series								
VN7008AJ	PowerSSO-16	4	28	38	8.5	98	Analog current sense	Autorestart & Latch-off
VN7010AJ	PowerSSO-16	4	28	38	10	91	Analog multi-sense	Autorestart & Latch-off
VN7016AJ	PowerSSO-16	4	28	38	16	77	Analog multi-sense	Autorestart & Latch-off
VN7020AJ	PowerSSO-16	4	28	38	20	63	Analog multi-sense	Autorestart & Latch-off
VN7040AS	S0-8	4	28	38	40	34	Analog current sense	Autorestart
VN7040AJ	PowerSSO-16	4	28	38	40	34	Analog multi-sense	Autorestart & Latch-off
VN7050AS	S0-8	4	28	38	50	30	Analog current sense	Autorestart
VN7050AJ	PowerSSO-16	4	28	38	50	30	Analog multi-sense	Autorestart & Latch-off
VN7140AS12	S0-8	2.85	28	38	140	12	Analog current sense	Autorestart
VN7140AS	S0-8	4	28	38	140	12	Analog current sense	Autorestart
VN7140AJ	PowerSSO-16	4	28	38	140	12	Analog multi-sense	Autorestart & Latch-off
VIPower™ M0-5 Enhanced series								
VN5E010MH-E	HPAK	4.5	28	41	10	85	Analog current sense	Autorestart
VN5E016MH-E	HPAK	4.5	28	41	16	73	Analog current sense	Autorestart
VN5E025MH-E	PowerSSO-12	4.5	28	41	25	60	Analog current sense	Autorestart
VN5E050MJ-E	PowerSSO-12	4.5	28	41	50	27	Analog current sense	Autorestart
VN5E160MS-E	S0-8	4.5	28	41	160	10	Analog current sense	Autorestart
VIPower™ M0-5 Enhanced series								
VN5E010AH-E	HPAK	4.5	28	41	10	85	Analog current sense	Autorestart
VN5E016AH-E	HPAK	4.5	28	41	16	73	Analog current sense	Autorestart
VN5E025AJ-E	PowerSSO-12	4.5	28	41	25	60	Analog current sense	Autorestart
VN5E050J-E	PowerSSO-12	4.5	28	41	50	27	Analog current sense	Autorestart
VN5E050I-E	PowerSSO-12	4.5	28	41	50	27	Digital status	Autorestart

(*) In development.

HIGH-SIDE SWITCHES – SINGLE-CHANNEL

Part number	Package	Supply voltage (V_{cc})		Absolute max supply voltage (V)	On-state resistance $R_{DS(on)}$ (mΩ)	Output current limit (I_{lim}) (A)	Diagnostic feedback	Short-circuit protection
		Min (V)	Max (V)					
VIPower™ M0-5 series								
VN5E050AJ-E	PowerSSO-12	4.5	28	41	50	27	Analog current sense	Autorestart
VN5E160S-E	S0-8	4.5	28	41	160	10	Digital status	Autorestart
VN5E160AS-E	S0-8	4.5	28	41	160	10	Analog Current Sense	Autorestart
VIPower™ M0-3 series								
VN5E006ASP-E	PowerSO-10	4.5	36	41	6	100	Analog Current Sense	Autorestart
VN5010AK-E	PowerSSO-24	4.5	36	41	10	65	Analog Current Sense	Autorestart
VN5012AK-E	PowerSSO-24	4.5	36	41	12	65	Analog Current Sense	Autorestart
VN5016AJ-E	PowerSSO-12	4.5	36	41	16	60	Analog Current Sense	Autorestart
VN5025AJ-E	PowerSSO-12	4.5	36	41	25	40	Analog Current Sense	Autorestart
VN5030J-E	PowerSSO-12	4.5	36	41	50	18	Digital Status	Autorestart
VN5050AJ-E	PowerSSO-12	4.5	36	41	50	18	Analog Current Sense	Autorestart
VN5160S-E	S0-8	4.5	28	41	160	5	Digital Status	Autorestart
VIPower™ M0-3 series								
VN610SP-E	PowerSO-10	5.5	36	41	10	75	Analog Current Sense	Autorestart
VN920SP-E	PowerSO-10	5.5	36	41	15	45	Analog Current Sense	Autorestart
VN920PEP-E	PowerSSO-24	5.5	36	41	15	45	Analog Current Sense	Autorestart
VN920-E	PENTAWATT	5.5	36	41	16	45	Analog Current Sense	Autorestart
VN920DSP-E	PowerSO-10	5.5	36	41	16	45	Digital Status	Autorestart
VN920B5-E	P²PAK	5.5	36	41	16	45	Analog Current Sense	Autorestart
VN920DBB5-E	P²PAK	5.5	36	41	18	45	Digital Status	Autorestart
VN820SP-E	PowerSO-10	5.5	36	41	40	13	Digital Status	Autorestart
VN820PT-E	P²PAK	5.5	36	41	40	13	Digital Status	Autorestart
VN820B5-E	P²PAK	5.5	36	41	40	13	Digital Status	Autorestart
VN750SMP-E	S0-8	5.5	36	41	55	9	Digital Status	Autorestart
VN750PT-E	P²PAK	5.5	36	41	60	9	Digital Status	Autorestart
VN750PS-E	S0-8	5.5	36	41	60	9	Digital Status	Autorestart
VN750-E	PENTAWATT	5.5	36	41	60	9	Digital Status	Autorestart
VN750B5-E	P²PAK	5.5	36	41	60	9	Digital Status	Autorestart
VN800PT-E	P²PAK	5.5	36	41	135	1.3	Digital Status	Autorestart
VN800PS-E	S0-8	5.5	36	41	135	1.3	Digital Status	Autorestart

(*) In development.

HIGH-SIDE SWITCHES – DUAL-CHANNEL

Part number	Package	Supply voltage (V_{cc})		Absolute max supply voltage (V)	On-state resistance $R_{DS(on)}$ (mΩ)	Output current limit (I_{lim}) (A)	Diagnostic feedback	Short-circuit protection
		Min (V)	Max (V)					
VIPower™ M0-7 series								
WND7004AY	PowerSSO-36	4	28	38	4	100	Analog Multi-Sense	Autorestart & Latch-off
WND7012AY	PowerSSO-36	4	28	38	12	75	Analog Multi-Sense	Autorestart & Latch-off
WND7020AJ	PowerSSO-16	4	28	38	22	63	Analog Current Sense	Autorestart & Latch-off
WND7030AJ	PowerSSO-16	4	28	38	31	56	Analog Current Sense	Autorestart & Latch-off
WND7040AJ	PowerSSO-16	4	28	38	40	34	Analog Multi-Sense	Autorestart & Latch-off
WND7050AJ12	PowerSSO-12	2.85	28	38	50	30	Analog Multi-Sense	Autorestart
WND7050AJ	PowerSSO-16	4	28	38	50	30	Analog Multi-Sense	Autorestart & Latch-off
WND7140AJ12	PowerSSO-12	2.85	28	38	140	12	Analog Current Sense	Autorestart
WND7140AJ	PowerSSO-16	4	28	38	140	12	Analog Multi-Sense	Autorestart & Latch-off
VIPower™ M0-5Enhanced (M vers.) series								
WND5E008MY-E	PowerSSO-36	4.5	28	41	8	85	Analog Current Sense	Autorestart
WND5E012MY-E	PowerSSO-36	4.5	28	41	12	74	Analog Current Sense	Autorestart
WND5E025MK-E	PowerSSO-24	4.5	28	41	25	60	Analog Current Sense	Autorestart
WND5E050MC-E	PowerSSO-24	4.5	28	41	50	27	Analog Current Sense	Autorestart
WND5E050MCJ-E	PowerSSO-12	4.5	28	41	50	27	Analog Current Sense	Autorestart
WND5E160MJ-E	PowerSSO-12	4.5	28	41	160	10	Analog Current Sense	Autorestart
VIPower™ M0-5Enhanced series								
WND5E004C30-E	MultipowerSO-30	4.5	28	41	4	100	Analog Current Sense	Autorestart
WND5E004A-E	PQFN	4.5	28	41	4	100	Analog Current Sense	Autorestart
WND5E006ASP-E	PowerSO-16	4.5	28	41	6	100	Analog Current Sense	Autorestart
WND5E008AY-E	PowerSSO-36	4.5	28	41	8	85	Analog Current Sense	Autorestart
WND5E008ASP-E	PowerSO-16	4.5	28	41	8	85	Analog Current Sense	Autorestart
WND5E012AY-E	PowerSSO-36	4.5	28	41	12	74	Analog Current Sense	Autorestart
WND5E025NAV-E	PowerSSO-36	4.5	28	41	25	60	Analog Current Sense	Autorestart
WND5E025LK-E	PowerSSO-24	4.5	28	41	25	40	Analog Current Sense	Autorestart
WND5E025BK-E	PowerSSO-24	4.5	28	41	25	60	Analog Current Sense	Autorestart
WND5E025AY-E	PowerSSO-36	4.5	28	41	25	47	Analog Current Sense	Autorestart
WND5E025AK-E	PowerSSO-24	4.5	28	41	25	60	Analog Current Sense	Autorestart
WND5E050K-E	PowerSSO-24	4.5	28	41	50	27	Digital Status	Autorestart
WND5E050J-E	PowerSSO-12	4.5	28	41	50	27	Digital Status	Autorestart
WND5E050AC1-E	PowerSSO-24	4.5	28	41	50	27	Analog Current Sense	Autorestart

HIGH-SIDE SWITCHES – DUAL-CHANNEL

Part number	Package	Supply voltage (V_{cc})		Absolute max supply voltage (V)	On-state resistance $R_{DS(on)}$ (mΩ)	Output current limit (I_{lim}) (A)	Diagnostic feedback	Short-circuit protection
		Min (V)	Max (V)					
VIPower™ M0-5 series								
VND5E050AC-E	PowerSSO-12	4.5	28	41	50	27	Analog Current Sense	Autorestart
VND5E160J-E	PowerSSO-12	4.5	28	41	160	10	Digital Status	Autorestart
VND5E160AJ-E	PowerSSO-12	4.5	28	41	160	10	Analog Current Sense	Autorestart
VND5012AK-E	PowerSSO-24	4.5	36	41	12	60	Analog Current Sense	Autorestart
VND5025AK-E	PowerSSO-24	4.5	36	41	25	40	Analog Current Sense	Autorestart
VND5050K-E	PowerSSO-24	4.5	36	41	50	18	Digital Status	Autorestart
VND5050L-E	PowerSSO-12	4.5	36	41	50	18	Digital Status	Autorestart
VND5050AK-E	PowerSSO-24	4.5	36	41	50	18	Analog Current Sense	Autorestart
VND5050AJ-E	PowerSSO-12	4.5	36	41	50	18	Analog Current Sense	Autorestart
VND5160J-E	PowerSSO-12	4.5	36	41	160	5	Digital Status	Autorestart
VND5160AJ-E	PowerSSO-12	4.5	36	41	160	5	Analog Current Sense	Autorestart
VIPower™ M0-3 series								
VND920P-E	S0-28	5.5	36	41	16	45	Analog Current Sense	Autorestart
VND600SP-E	PowerSSO-10	5.5	36	41	30	40	Analog Current Sense	Autorestart
VND600P-E	S0-16L	5.5	36	41	35	40	Analog Current Sense	Autorestart
VND830SP-E	PowerSSO-10	5.5	36	41	60	9	Digital Status	Autorestart
VND830MSP-E	PowerSSO-10	5.5	36	41	60	9	Digital Status	Autorestart
VND830P-E	S0-16L	5.5	36	41	60	9	Digital Status	Autorestart
VND830LSP-E	PowerSSO-10	5.5	36	41	60	23	Digital Status	Autorestart
VND830ASP-E	PowerSSO-10	5.5	36	41	60	9	Analog Current Sense	Autorestart
VND830AEP-E	PowerSSO-24	5.5	36	41	60	10	Analog Current Sense	Autorestart
VND810MSP-E	PowerSSO-10	5.5	36	41	150	0.9	Digital Status	Autorestart
VND810SP-E	PowerSSO-20	5.5	36	41	160	5	Digital Status	Autorestart
VND810PEP-E	PowerSSO-12	5.5	36	41	160	5	Digital Status	Autorestart
VND810P-E	S0-16	5.5	36	41	160	5	Digital Status	Autorestart

(*) In development.

HIGH-SIDE SWITCHES – QUAD-CHANNEL

Part number	Package	Supply voltage (V_{dd})		Absolute max supply voltage (V)	$R_{DS(on)}$ (mΩ)	Output current limit (I_{lim}) (A)	Digital status	Short-circuit protection
		Min (V)	Max (V)					
VIPower™ M0-7 series (to be preferred for new developments)								
VNQ7040AY	PowerSSO-36	4	28	38	40	34	Analog Multi-Sense	Autorestart & Latch-off
VNQ7050AJ	PowerSSO-16	4	28	38	50	27	Analog Current Sense	Autorestart & Latch-off
VNQ7140AJ	PowerSSO-16	4	28	38	140	12	Analog Multi-Sense	Autorestart & Latch-off
VIPower™ M0-5Enhanced (M vers.) series								
VNQ5E050MK-E	PowerSSO-24	4.5	28	41	50	27	Analog Current Sense	Autorestart
VNQ5E050AK-E	PowerSSO-24	4.5	28	41	50	27	Analog Current Sense	Autorestart
VNQ5E160K-E	PowerSSO-24	4.5	28	41	160	10	Analog Current Sense	Autorestart
VNQ5E160AK-E	PowerSSO-24	4.5	28	41	160	10	Digital Status	Autorestart
VNQ5E250AJ-E	PowerSSO-16	4.5	28	41	250	5	Analog Current Sense	Autorestart
VIPower™ M0-5 series								
VNQ5027AK-E	PowerSSO-24	4.5	36	41	27	40	Analog Current Sense	Autorestart
VNQ5050K-E	PowerSSO-24	4.5	36	41	50	18	Digital Status	Autorestart
VNQ5050AK-E	PowerSSO-24	4.5	36	41	50	18	Analog Current Sense	Autorestart
VNQ5160K-E	PowerSSO-24	4.5	36	41	160	5	Digital Status	Autorestart
VIPower™ M0-3 series								
VNQ600P-E	S0-28	5.5	36	41	35	40	Analog Current Sense	Autorestart
VNQ600AP-E	S0-28	5.5	36	41	35	40	Analog Current Sense	Autorestart
VNQ660SP	PowerSSO-10	6	36	41	50	10	Digital Status	Autorestart
VNQ830PEP-E	PowerSO-24	5.5	36	41	60	18	Digital Status	Autorestart
VNQ830P-E	S0-28	5.5	36	41	65	9	Digital Status	Autorestart
VNQ690SP-E	PowerSSO-10	6	36	41	90	14	Digital Status	Autorestart
VNQ05XSP16-E	PowerSSO-16	5.5	36	41	110	7.5	Analog Current Sense	Autorestart
VNQ810PEP-E	PowerSO-24	5.5	36	41	160	7.5	Digital Status	Autorestart
VNQ810P-E	S0-28	5.5	36	41	160	5	Digital Status	Autorestart
VNQ500PEP-E	PowerSO-12	5.5	36	41	500	0.6	Digital Status	Latch-off

HIGH-SIDE SWITCHES WITH SPI AND ASYMMETRICAL OUTPUT

Part number	Package	Supply voltage (V_{cc})		Absolute max supply voltage (V)	On-state resistance $R_{DS(on)}$ (mΩ)	Output current limit (I_{lim}) (A)	Current sense	SPI	Description
		min (V)	max (V)						
VNP7008SY ^(*)	PowerSS0-36	4	28	38	5x40	34	•	•	Output power: 5x21 W
VNQ7003SY ^(*)	PowerSS0-36	4.0	28	38	2x7 2x25	80 35	•	•	Output power: 2x65 W and 2x32 W
VNQ7004SY ^(*)	PowerSS0-36	4.0	28	38	2x9 2x35	80 30	•	•	Output power: 2x65 W and 2x32 W

(*) In development.

HIGH-SIDE SWITCHES FOR 24 V APPLICATIONS – TRUCK DEVICES

Part number	Package	Supply voltage (V_{cc})		Absolute max supply voltage (V)	On-state resistance $R_{DS(on)}$ (mΩ)	Output current limit (I_{lim}) (A)	Current sense
		min (V)	max (V)				
VND5T006ASP-E	PowerSO-10	8	36	58	6	115	•
VND5T016ASP-E	PowerSO-16	8	36	58	16	70	•
VN5T016AH-E	HPAK	8	36	58	16	60	•
VND5T035LAK-E	PowerSS0-24	8	36	58	35	42	Optimized for LED applications
VND5T035AK-E	PowerSS0-24	8	36	58	35	42	•
VND5T050AK-E	PowerSS0-24	8	36	58	50	34	•
VND5T100AJ-E	PowerSS0-12	8	36	58	100	22	Optimized for LED applications
VND5T100AJ-E	PowerSS0-12	8	36	58	100	22	•
VND5T100A-E	S0-16N	8	36	58	100	22	•

Low-side switches

OMNIFET III™

Part number	Package	Number of channels	Clamp voltage typ (V)	Drain current limit (I_{lim}) (A)	On-state resistance $R_{DS(on)}$ (mΩ)	Digital status
VNL5030S5-E	S0-8	1	46	35	30	•
VNL5030J-E	PowerSS0-12	1	46	35	30	•
VNL5050S5-E	S0-8	1	46	27	50	•
VNL5050N3-E	SOT-223	1	46	27	50	•
VNL5090-E	S0-8	2	46	18	90	•
VNL5090S5-E	S0-8	1	46	18	90	•
VNL5090N3-E	SOT-223	1	46	18	90	•
VNL5160-E	S0-8	2	46	5	160	•
VNL5160S5-E	S0-8	1	46	5	160	•
VNL5160N3-E	SOT-223	1	46	5	160	•
VNL5300-E	S0-8	2	46	2	300	•
VNL5300S5-E	S0-8	1	46	2	300	•

Part number	Package	Number of channels	Typ. clamp voltage (V)	Drain current limit (I_{dm}) (A)	On-state resistance $R_{DS(on)}$ (mΩ)
VNV35NV04-E	PowerSO-10	1	45	45	10
VNB35NV04-E	DPAK	1	45	45	10
VNS14NV04P-E	SO-8	1	45	18	35
VND14NV04-1-E	IPAK	1	45	18	35
VND14NV04-E	DPAK	1	45	18	35
VNB14NV04-E	DPAK	1	45	18	35
VND7NV04-E	DPAK	1	45	9	60
VNS7NV04P-E	SO-8	1	45	9	65
VNN7NV04P-E	SO/T-223	1	45	9	65
VNS3NV04DP-E	SO-8	2	45	5	120
VNS3NV04P-E	SO-8	1	45	5	120
VNN3NV04P-E	SO-8; SO/T-223	1	45	5	120
VND3NV04-E	DPAK	1	45	5	120
VNS1NV04DP-E	SO-8	2	45	2.6	250
VNS1NV04P-E	SO-8	1	45	2.6	250
VNN1NV04P-E	SO/T-223	1	45	2.6	250
VND1NV04-1-E	IPAK	1	45	2.6	250
VND1NV04-E	DPAK	1	45	2.6	250
VNN35N07-E	PowerSO-10	1	70	35	28
VNP35N07-E	T0-220	1	70	35	28
VNB35N07-E	DPAK	1	70	35	28
VNV20N07-E	PowerSO-10	1	70	20	50
VNP20N07-E	T0-220	1	70	20	50
VNB20N07-E	DPAK	1	70	20	50
VNP10N07-E	T0-220	1	70	10	100
VNB10N07-E	DPAK	1	70	10	100
VNP5N07-E	T0-220	1	70	5	200
VND5N07-E	DPAK	1	70	5	200

Voltage regulators

Part number	Package	Number of outputs	Regulated output voltage (V)	Output current (I_{out}) (mA)	Output tolerance (%)	Dropout voltage (V_{dp})		Reset output	Enable pin	Early warning	Watchdog timer	Watchdog enable	Typ. supply current (standby) (μA)	Quiescent current at low load typ (μA)
						Typ (mV)	Max (mV)							
L4938ED	S0-20	2	Out1: 5 Out2: 5Adj	Out1: 100 Out2: 400	Out1: ± 1 Out2: ± 2	Out1: 200 Out2: 300	Out1: 400 Out2: 600	•	•	•	•	•	65	65
L4938EPD	PowerSSO-20	2	Out1: 5 Out2: 5Adj	Out1: 100 Out2: 400	Out1: ± 1 Out2: ± 2	Out1: 200 Out2: 300	Out1: 400 Out2: 600	•	•	•	•	•	65	65
L4949ED-E	S0-8	1	5	100	± 1	300	500	•	•	•	•	•	200	200
L4949EP-E	S0-20	1	5	100	± 1	300	500	•	•	•	•	•	200	200
L4979D	S0-8	1	5	150	± 2	200	400	•	•	•	•	•	6	100
L4979MD	S0-20	1	5	150	± 2	200	400	•	•	•	•	•	6	100
L4988D	S0-8	1	5	200	± 2	270	500	•	•	•	•	•	93	93
L4988MD	S0-20	1	5	200	± 2	270	500	•	•	•	•	•	93	93
L4989D	S0-8	1	5	150	± 3	180	400	•	•	•	•	•	110	110
L4989MD	S0-20	1	5	150	± 3	180	400	•	•	•	•	•	110	110
L4993D	S0-8	1	5	150	± 2	200	400	•	•	•	•	•	100	100
L4993MD	S0-20	1	5	150	± 2	200	400	•	•	•	•	•	100	100
L4995RJ	PowerSSO-12	1	5	500	± 2	270	500	•	•	•	•	•	90	90
L4995RK	PowerSSO-24	1	5	500	± 2	270	500	•	•	•	•	•	90	90
L4995AJ	PowerSSO-12	1	5	500	± 2	270	500	•	•	•	•	•	3	90
L4995AK	PowerSSO-24	1	5	500	± 2	270	500	•	•	•	•	•	3	90
L4995J	PowerSSO-12	1	5	500	± 2	270	500	•	•	•	•	•	3	90
L4995K	PowerSSO-24	1	5	500	± 2	270	500	•	•	•	•	•	3	90
L5150BNTR	SOT-223	1	5	150	± 2	500	•(1)	•	•	•	•	•	50	50
L5150CJ	PowerSSO-12	1	5	150	± 2	500	•(1)	•	•	•	•	•	55	55
L5150CS	S0-8	1	5	150	± 2	500	•(1)	•	•	•	•	•	55	55
L5150GJ	PowerSSO-12	1	5	150	± 2	500	•(1)	•	•	•	•	•	5	55
L5300AH7	HPAK	1	5	300	± 2	500	•	•	•	•	•	•	5	55
L5300GJ	PowerSSO-12	1	5	300	± 2	500	•	•	•	•	•	•	5	55
L5300EPT	PPAK	1	5	300	± 2	500	•	•	•	•	•	•	5	55
L5300RPT	PPAK	1	5	300	± 2	500	•	•	•	•	•	•	55	55

(1) Adjustable threshold

Door actuators drivers with embedded Power Management

Door actuators drivers with embedded Power Management

Part number	Package	Driver stages	Max on-state resistance $R_{DS(on)}$ (mΩ)	Current limitation I_{lim} (A)	Extended operative range (V)	PWM control	Motor control driver	Electro-chrome mirror	Heater	Transceivers	Voltage regulators	Thermal clusters	A/D Voltage-temperature conversion thermal clusters
L99DZ120	LQFP64	1 Full Bridge	300	3									
		1 Half Bridge	100	7.5									
		1 Half Bridge	150	7.5									
		1 $R_{DS(on)}$ Configurable High Side	500/1600	1.5/0.35									
		1 $R_{DS(on)}$ Configurable High Side	800/1600	0.8/0.35	3.5 ^(*) to 28								
		3 Current Configurable High Side	2000	0.15/0.35									
		1 Current Configurable High Side	2000	0.25/0.5									
		4 Current Configurable High Side	5000	0.15/0.25									

(*) All SPI communication, logic, voltage regulators and Oscillator are working down to V_{SREG} = 3.5 V

(**) From I_{CMP} to 100 mA

Door modules

Door modules

Part number	Package	Driver stages	Max on-state resistance $R_{DS(on)}$ (mΩ)	Current limitation I_{lm} (A)	Operating range (V)	PWM control	Short-circuit protection	Current sense	Thermal shutdown	Reverse battery protection	Diagnostics and programming	EC control	LED mode	H-bridge control	Description
L99DZ80EP	TQFP64	1 full bridge	150	6											High-end front door module compatible with bulbs/LEDs. Control circuitry for electrochromic mirror glass with possibility for negative discharge. H-Bridge control, for external MOSFETs, with adjustable slew-rate
		2 half bridges	300	3											
		2 half bridges	1600	0.5											
		1 high-side switch	100	5	7 to 28	•		•							
		1 configurable high-side switch	500/1600	1.5/0.35											
		1 configurable high-side switch	800/1600	0.7/0.35											
		2 high-side switches	1600	0.5											
		1 full bridge	150	6											
		1 half bridge	300	3											
		1 configurable high-side switch	500/1600	1.5/0.35	7 to 28	•		•				SPI	-	4x	
L99DZ81EP	TQFP64	1 configurable high-side switch	800/1600	0.7/0.35											High-end front door module compatible with bulbs/LEDs. H-Bridge control, for external MOSFETs, with adjustable slew-rate
		1 high-side switch	1600	0.5											
		1 full bridge	300	3											
		3 half bridges	1600	0.50											
		1 high-side switch	90	6	7 to 28	•		•							
		1 configurable high-side switch	500/1800	1.5/0.35											
		2 high-side switches	1600/1800	0.5											
		1 full bridge	300	3											
		3 half bridges	1600	0.50											
		1 high-side switch	90	6	7 to 28	•		•				SPI	6-bit resolution 1.2V/1.5V	4x	
L99MM70XP	PowerSSO-36	1 high-side switch	500/1800	1.5/0.35											High-end device supporting LIN driven Mechatronic Mirror
		2 high-side switches	1600/1800	0.5											

Power management for automotive systems

Part number	Package	Transceiver	Transmission rate	Voltage regulators				Driver stages	On-board features	Description
				Outputs	Accuracy	Drop voltage $V_{D\phi}$ (typ) (mV)	Reset			
L4969URD-E	SO-20	125 kbaud	Fault-tolerant low-speed CAN transceiver	5 V @ 200 mA	$\pm 2\%$	$250 @ I_{LOAD} = 100 \text{ mA}$	•	•	• Wake-up via CAN for voltage regulator	Basic system chip
L9952GXP	PowerSSO-36	20 kbit/s LIN transceiver	5 V @ 100 mA	5 V @ 250 mA	$\pm 2\%$	$300 @ I_{LOAD} = 100 \text{ mA}$	•	4	HSD 7 Ω @ 120 mA 4 wake-up inputs for contact monitoring Fair-safe output Two op amps for current sense interacting Inhibit input for wake-up from external CAN	Power management IC with LIN
				5 V @ 50 mA	$\pm 4\%$	$400 @ I_{LOAD} = 50 \text{ mA}$	•	1	HSD 1 Ω @ 400 mA Relay drivers (2 Ω)	
L99PM62GXP	PowerSSO-36	LIN and HS CAN transceivers	5 V @ 100 mA	5 V @ 250 mA	$\pm 2\%$	$300 @ I_{LOAD} = 100 \text{ mA}$	•	4	HSD 7 Ω @ 120 mA Complete 3-channel contact monitoring interface with programmable cyclic sense functionality 4 internal PWM timers Two op amps with rail-to-rail outputs (VS) and low-voltage inputs (NS) and programmable periodic system wake-up feature	Power management IC with LIN and high-speed CAN
				5 V @ 50 mA	$\pm 4\% (3\% @ 50 \text{ mA})$	$400 @ I_{LOAD} = 50 \text{ mA}$	•	1	HSD 1 Ω @ 400 mA Relay drivers (2 Ω)	
L99PM60J	PowerSSO-16	LIN transceiver	5 V @ 100 mA	5 V @ 200 mA	$\pm 2\%$	$300 @ I_{LOAD} = 100 \text{ mA}$	•	2	HSD 7 Ω @ 60 mA Configurable fail-safe output ST SPI interface for mode control and diagnostics Direct drive feature for HSD	Power management IC with LIN
				5 V @ 250 mA	$\pm 2\%$	$300 @ I_{LOAD} = 100 \text{ mA}$	•	2	Relay drivers (2 Ω)	
L99PM72GXP	PowerSSO-36	LIN and HS CAN transceivers	5 V @ 100 mA	5 V @ 250 mA	$\pm 2\%$	$300 @ I_{LOAD} = 100 \text{ mA}$	•	4	HSD 7 Ω @ 120 mA Complete 3-channel contact monitoring interface with programmable cyclic sense functionality 4 internal PWM timers Two operational amps with rail-to-rail outputs (VS) and low-voltage inputs (NS) and programmable periodic system wake-up feature	Power management IC with LIN and high-speed CAN supporting selective wake-up functionality according to ISO 11898-6
				5 V @ 50 mA	$\pm 4\% (3\% @ 50 \text{ mA})$	$400 @ I_{LOAD} = 50 \text{ mA}$	•	1	HSD 1 Ω @ 400 mA Relay drivers (2 Ω)	

Multifunctional voltage regulators

Part number	Package	V _{in} (V)	V _{out} (V)	I _{out} (A)	Frequency	Topology	Other features
L4953G	Multiwatt15	ST-BY 2 x LD0s	11 to 18	5	0.1	-	• Enables • 2 x HSD • Warnings
		ST-BY 3 x LD0s	11 to 16	5	0.1	-	• Enables • Reset • 3 x HSD • Warnings
L4954	Multiwatt15	3 x LD0s	11 to 16	10/8.5/5	0.04/0.175/0.65	-	• Enables • I ² C interface • 3 x HSD
		5 x LD0s	9 to 18	10/8.5/5/8-10	0.35/0.175/0.35/0.25/1.0	-	• Enables • I ² C interface • 3 x HSD
L5950	PowerSO20 Multiwatt15	ST-BY LD0s	9 to 18	5	0.3	-	• Enables • HSD
		2 x LD0	6 to 18	8.5	0.5	-	• Enables • HSD
L5956	PowerSO20 Multiwatt15	ST-BY 2 x LD0s	9 to 18	5/3.3	0.8/0.8	-	• Enables • HSD
		LD0	6 to 18	5	0.3	-	• Enables • HSD
L5957	PowerSO20 Multiwatt15	2 x ST-BYs LD0	9 to 18	8.5/3.3	0.5/0.8	-	• Enables • HSD
		2 x ST-BYs 4 x LD0s	9 to 18	5	0.8	-	• Reset • HSD
L5958	Flexiwatt27	5 x ST-BYs	9 to 18	3.3/1.8	0.1/0.1	-	• Reset • HSD
		3 x LD0s	8.5/5/3.3/1.8	0.2/0.3/0.25/0.35	-	-	• Reset • Voltage monitors • 2 x HSD • Enables
L5959	Multiwatt15	ST-BYs 3 x LD0s	9 to 18	3.3	0.1	-	• Reset • Voltage monitors • 2 x HSD • Enables
		Buck	8.5/8- 10/3.3	0.2/0.8	-	-	• Reset • Voltage monitors • 2 x HSD • Enables
L5962	PowerSO36	ST-BY LD01 LD02	4.1 to 27	1.2 to 8	2.5	Up to 400 kHz	Internal power switches
				3.3/5	0.15	-	• I ² C bus for LD02 • Reset • 2 x HSD • Enables for buck
L5963	PowerSO36 VQFPN-48	Buck1 Buck2 ST-BY/LDO	3.5 to 26	5/8.5	0.35	-	Monolithic synchronous, current mode, internal power switches
		Buck1 Buck2 ST-BY/LDO	3.3 to 26	3.3 to 10	1	-	• Power goods • High side driver • Enables
L5964 ^(*)	VQFPN-48 LQFP64	Buck1 controller	3.5 to 26	1 to Vin	2.5	Up to 2MHz	Monolithic synchronous, voltage mode, internal power switches
		Buck2 Buck3 Buck4 Boost LDO Vref	3.3 to 26	0.9 to Vin	3.0	Up to 2MHz	• DC-DC parallel mode (7A) • Watchdog / Reset • Voltage supervisors • Designed for Advanced Driver Assistance Systems
L5965 ^(*)	VQFPN-48	Adjustable by OTP	4 to 32	-	3/1.5	Up to 2.4MHz	• OTP programming • SPI interface • Diagnostics
			3 to 5.5		1.5	Up to 2.4MHz	• Voltage supervisors • Designed for Advanced Driver Assistance Systems
			3 to 5.5		1	Up to 2.4MHz	
			3 to 5.5		0.3	Up to 2.4MHz	
			3 to 5.5		0.6	Up to 2.4MHz	
			-		0.02	Up to 2.4MHz	

(*). In development

Motor control ICs - DC motor drivers

22

Part number	Package	Device description	On-state resistance per leg $R_{DS(on)}$ (mΩ)	Current limitation (I_{lim}) typ (A)	Supply voltage (V_{cc})		Absolute max supply voltage (V)	Highlights
					min (V)	max (V)		
VNH913Y								
	PowerSSO-36	Full bridge Power Stage	13	-	7	28	80	• Temperature protected
VNH7100AS								
	SO-16N	Full bridge	100	18	4	28	38	• Cross-conduction protection • PWM operations up to 20 kHz • Current sense output • Output protected against short-to-ground and short-to-Vcc
VNH7070AS								
	SO-16N	Full bridge	70	22	4	28	38	• Cross-conduction protection • PWM operations up to 20 kHz • Current sense output • Output protected against short-to-ground and short-to-Vcc
VNH7040AY^(*)								
	PowerSSO-36	Full bridge	40	49	4	28	38	• Cross-conduction protection • PWM operations up to 20 kHz • Multisense output • Output protected against short-to-ground and short-to-Vcc
VNH7008AY^(*)								
	PowerSSO-36	Full Bridge High Side driver	8 (per channel)	55	4	28	38	• Cross-conduction protection • PWM operations up to 20 kHz • Current sense output • Output protected against short-to-ground and short-to-Vcc • Drain and source voltage monitoring of the LSD external power MOSFETs
VNH5200AS-E								
	SO-16N	Full bridge	200	12	5.5	18	40	• Cross-conduction protection • Current sense • Output protected against short-to-ground and short-to-Vcc
VNH5180A-E								
	PowerSSO-36	Full bridge	180	12	5.5	18	41	• Cross-conduction protection • PWM operations up to 20 kHz • Current sense • Output protected against short-to-ground and short-to-Vcc
VNH5050A-E								
	PowerSSO-36	Full bridge	50	42	5.5	18	41	• Cross-conduction protection • PWM operations up to 20 kHz • Current sense • Output protected against short-to-ground and short-to-Vcc
VNH5019A-E								
	MultiPowerSSO-30	Full bridge	19	50	5.5	24	41	• Cross-conduction protection • PWM operations up to 20 kHz • Current sense • Charge pump output for reverse-polarity protection
L9997ND								
	SO-20	2 x Half bridge	1400	1.6	7	16.5	26	• Short-circuit • Over-temperature protected

(*) In development

Motor control ICs - Application Specific Standard Product

Part number	Package	Device description	On-state resistance per leg $R_{DS(on)}$ (mΩ)	Over-current protection min(A)	Supply voltage (V _{cc}) min (V)	Supply voltage (V _{cc}) max (V)	Absolute max supply voltage (V)	Highlights
L99MD02XP	PowerSSO-36	6x Half bridge	1600	0.8	6	28	40	<ul style="list-style-type: none"> Optimized for HVAC flaps DC-motor driver 6 H-bridge driver 2 current monitor outputs All outputs short-circuit protected
L99MD01XP	PowerSSO-36	8x Half bridge	1600	0.8	6	28	40	<ul style="list-style-type: none"> Optimized for HVAC flaps DC-stepper motor driver 8 H-bridge driver Intrinsic DC-DC step-up converter 2 current monitor outputs All outputs short-circuit protected
L99SM81VVY	PSS036	Dual H-bridge	1400	1.9	6	28	40	<ul style="list-style-type: none"> Bipolar stepper motor driver Up to 1.35 A current capability with equivalent 10bit resolution 1/16th microstepping Voltage regulator for sensors supply Stall detection
L99SM81VQ6	QFN40L 6x6	Dual H-bridge	1400	1.9	6	28	40	<ul style="list-style-type: none"> Bipolar stepper motor driver Up to 1.35 A current capability with equivalent 10bit resolution 1/16th microstepping Voltage regulator for sensors supply Stall detection

Motor Control ICs - Motor pre-drivers

Part number	Package	Device description	On-state resistance per leg $R_{DS(on)}$ (mΩ)	Current limitation I_{lim} typ (A)	Supply voltage (V _{cc}) min (V)	Supply voltage (V _{cc}) max (V)	Absolute max supply voltage (V)	Highlights
L99H01QF	LQFP-32	Full bridge driver	-	-	6	28	35	<ul style="list-style-type: none"> Programmable free-wheeling Current-sense amplifier/free configuration Sensing circuitry of external MOSFET with embedded thermal sensor
L99H01XP	PowerSSO-36	Full bridge driver	-	-	6	28	35	<ul style="list-style-type: none"> Programmable free-wheeling Current-sense amplifier/free configuration Sensing circuitry of external MOSFET with embedded thermal sensor
L99ASC03	TQFP-48 ExPad	3x half-bridges driver	-	-	6	28	40	<ul style="list-style-type: none"> 3 half-bridges driver to control external MOSFET 5 V voltage regulator (200 mA continuous) Watchdog and fail-safe functionality PWM up to 80 kHz Configurable current sense amplifier Advanced BEMF detection IP Programmable overcurrent protection Drain-source monitoring and openload detection

Special devices

Part number	Package	Driver stages		Operating range V_{cc} (V)	Max supply voltage V_{cc} (V)	Oscillating frequency	Accuracy	Highlights		Description
		High voltage clamp (V_{cl}) typ (V)	High voltage clamp (V_{cl}) max (V)					Low load detection		
L99LD01	LQFP-32	High-efficiency constant-current LED driver		5.6 to 24	40			<ul style="list-style-type: none"> • SPI interface • Programmable LED current Dithering 		LED driver
L99CL01XP	PowerSS0-36	8-channel high-side LED driver		6 to 24	40			<ul style="list-style-type: none"> • Programmable over-current • SPI interface • Configurable $R_{DS(on)}$ 		LED driver
L99MC66J	PowerSS0-16	3 configurable HSD/LSD		6 to 28	40			<ul style="list-style-type: none"> • $R_{DS(on)} = 0.7 \Omega$ at $T_J = 25^\circ\text{C}$ 		Various loads driver H-bridge configuration
VN5MB02-E	SO-16	Smart power driver for motorbike direction indicator		9 to 16	40	+/- 5%	+/- 8%	<ul style="list-style-type: none"> • High accuracy in setting operating frequency and low-load detection • Maximum current detection with latch • Cycle by cycle thermal limitation 		Motorbike indicator driver

REVERSE BATTERY

Part number	Package	Operating range V_{cc} (V)		Max supply voltage V_{cc} (V)	Max on-state resistance $R_{DS(on)}$ (max) (mΩ)	Description
		Part number	Operating range V_{cc} (V)			
VN5R003H-E	HPAK	4.5 to 28	41		3	Reverse-battery protection for an electronic control unit

INTEGRATED SOLENOID DRIVER - INJECTION GAS SYSTEM

Part number	Package	Operating range V_{cc} (V)		Max supply voltage V_{cc} (V)	Max on-state resistance $R_{DS(on)}$ (max) (mΩ)	Recirculation path	Ipeak (A)	Clamp voltage (min) (V)	Description
		Excitation path	Recirculation path						
L99SD01-E	PowerSS0-36	6 to 28	40	60	60		14	44	Current-sense amplifier with internal sense resistor

Ignition drivers

Part number	Package	High voltage clamp (V_{cl}) typ (V)	Current limitation (I_{lim}) max (A)	Power stage saturation voltage ($V_{CE(SAT)}$)		Supply voltage (V_{cc}) min (V)	Supply current on state (I_{cc}) max (mA)	Description	
				max (V)	@ 6 A			max (V)	
VB525SP-E	PowerS0-10	380	11	2		4.5	5.5	40	Quasi-proportional current driving Current flag
VB526SP-E	PowerS0-10	360	11	2		4.5	5.5	40	Quasi-proportional current driving Current flag

Development support tools

TwisterSIM

TwisterSIM is a unique electro-thermal simulator that helps shorten the design solution cycle by enabling complex engineering evaluations. TwisterSIM is available for download at www.st.com/twistersim.

FEATURES

- Accurate dynamic simulations of load compatibility
- Wiring harness optimization
- Fault condition impact analysis
- Diagnostic behavior analysis
- Dynamic thermal performance



VIPower Smart Finder

Find the right VIPower high/low-side switch and H-bridge device for your Automotive application using Android™ and iOS™ portable devices.

Download VIPower Smart Finder for free at www.st.com/vipower-finder

FEATURES


- Smart parametric or part number search capability for product
- Technical datasheet downloading and off-line consulting
- Access to main product specifications: electrical parameters, product general description, key features and marketing status
- “Add to Favorites” the selected products and datasheets
- Ability to share technical documentation via social media or e-mail




EZ-Boards



MO-7 sample kits



OrCAD models



www.st.com/automotive_evalboards

Order code: SAMPLEKITMO-7

www.st.com/automotive_hwmodels

EZ-Boards: the easiest and smartest way to evaluate VIPower products

- Get your application's trials faster
- Cut evaluation costs
- Excellent thermal performances

EZ-BOARDS FOR 12 V HIGH SIDE SWITCHES (M0-7)

Part Number	Channels	$R_{DS(on)}$ max @ 25 °C	Voltage (Vmax, operating range)	Package	Current sense	Multi sense
EV-VN7003AH	1	3 mΩ		Octopak	X	
EV-VN7003ALH	1	3 mΩ		Octopak	X	
EV-VN7004CH	1	4 mΩ	38 V, 4 V to 28 V	Octopak	X	
EV-VN7004CLH	1	4 mΩ		Octopak	X	
EV-VN7007AH	1	7 mΩ	38 V, 4 V to 28 V	Octopak	X	
EV-VN7007ALH	1	7 mΩ		Octopak	X	
EV-VN7008AJ	1	8 mΩ	38 V, 4 V to 28 V	PowerSSO-16	X	
EV-VN7010AJ	1	10 mΩ	38 V, 4 V to 28 V	PowerSSO-16	X	
EV-VN7016AJ	1	16 mΩ	38 V, 4 V to 28 V	PowerSSO-16	X	
EV-VN7020AJ	1	20 mΩ	38 V, 4 V to 28 V	PowerSSO-16	X	
EV-VN7040AJ	1	40 mΩ	38 V, 4 V to 28 V	PowerSSO-16	X	
EV-VN7040AS	1	40 mΩ	38 V, 4 V to 28 V	SO-8	X	
EV-VN7050AJ	1	50 mΩ	38 V, 4 V to 28 V	PowerSSO-16	X	
EV-VN7050AS	1	50 mΩ	38 V, 4 V to 28 V	SO-8	X	
EV-VN7140AJ	1	140 mΩ	38 V, 4 V to 28 V	PowerSSO-16	X	
EV-VN7140AS	1	140 mΩ	38 V, 4 V to 28 V	SO-8	X	
EV-VND7004AY	2	4 mΩ		PowerSSO-36	X	
EV-VND7012AY	2	12 mΩ	38 V, 4 V to 28 V	PowerSSO-36	X	
EV-VND7020AJ	2	22 mΩ	38 V, 4 V to 28 V	PowerSSO-16	X	
EV-VND7030AJ	2	31 mΩ	38 V, 4 V to 28 V	PowerSSO-16	X	
EV-VND7040AJ	2	40 mΩ	38 V, 4 V to 28 V	PowerSSO-16	X	
EV-VND7050AJ	2	50 mΩ	38 V, 4 V to 28 V	PowerSSO-16	X	
EV-VND7140AJ	2	140 mΩ	38 V, 4 V to 28 V	PowerSSO-16	X	
EV-VNQ7040AY	4	40 mΩ	38 V, 4 V to 28 V	PowerSSO-36	X	
EV-VNQ7050AJ	4	50 mΩ	38 V, 4 V to 28 V	PowerSSO-16	X	
EV-VNQ7140AJ	4	140 mΩ	38 V, 4 V to 28 V	PowerSSO-16	X	

EZ-BOARDS FOR 12 V FULL BRIDGES (VNH5/VNH7)

Part Number	Bridge	$R_{DS(on)}$ max @ 25 °C	(V _{max} , operating range)	PWM	Current Sense
EV-VNH5180A	X	180 mΩ	41 V, 5.5 V to 18 V	PowerSSO-36	X
EV-VNH5050A	X	50 mΩ	41 V, 5.5 V to 18 V	PowerSSO-36	X
EV-VNH5200AS	X	200 mΩ	41 V, 5.5 V to 18 V	SO-16N	X
EV-VNH7040 ^(*)	X	40 mΩ	38 V, 4 V to 28 V	PowerSSO-36	X
EV-VNH7100AS	X	100 mΩ	41 V, 4 V to 28 V	SO-16N	X
EV-VNH7070AS	X	70 mΩ	41 V, 4 V to 28 V	SO-16N	X
STEVAL-VNH5180A	X	180 mΩ	41 V, 5.5 V to 18 V	PowerSSO-36	X
STEVAL-VNH5019A	X	18mΩ	41 V, 5.5 V to 18 V	MultipowerSO-30	X
STEVAL-VNH5050A	X	50 mΩ	41 V, 5.5 V to 18 V	PowerSSO-36	X

EZ-BOARDS FOR 24 V SMART SWITCHES (M0-5T)

Part Number	Channels	$R_{DS(on)}$ max @ 25 °C	(V _{max} , operating range)	PWM	Current Sense	Digital Status
EV-VND5T006ASP ^(*)	1	6 mΩ	58 V, 8 V to 36 V	PowerSO-10	X	
EV-VND5T016ASP ^(*)	2	16 mΩ	58 V, 8 V to 36 V	PowerSO-16	X	
EV-VND5T035AK	2	35 mΩ	58 V, 8 V to 36 V	PowerSSO-24	X	
EV-VND5T050AK ^(*)	2	50 mΩ	58 V, 8 V to 36 V	PowerSSO-24	X	
EV-VND5T100AJ	2	100 mΩ	58 V, 8 V to 36 V	PowerSSO-12	X	

EVALUATION BOARDS FOR POWER MANAGEMENT AND SYSTEM BASIS ICs

Part Number	V_{IN} (V _{MAX} , Operating Range)	V_{OUT} (DC-DC1, DC-DC2, LD0)	Frequency (DC-DC1, DC-DC2)	Package
EVAL-L5963	40 V, 3.5 V to 26 V	1.2 V@2.5 V, 5 V@3 A, 3.3 V@250 mA adjustable	2 MHz, 250 kHz adjustable	PowerSSO-36 (exp. pad)
EVAL-L5963Q	40 V, 3.5 V to 26 V	1.2 V@2.5 V, 5 V@3 A, 3.3 V@250 mA adjustable	2 MHz, 250 kHz adjustable	QFPN-48

^(*) In development.

life.augmented



© STMicroelectronics - February 2017 - Printed in United Kingdom - All rights reserved
The STMicroelectronics corporate logo is a registered trademark of the STMicroelectronics group of companies
All other names are the property of their respective owners



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power Switch ICs - Power Distribution category:

Click to view products by STMicroelectronics manufacturer:

Other Similar products are found below :

[AP22652AW6-7](#) [MAPDCC0001](#) [L9349TR-LF](#) [MAPDCC0005](#) [NCP45520IMNTWG-L](#) [VND5050K-E](#) [MP6205DD-LF-P](#) [FPF1015](#) [FPF1018](#)
[DS1222](#) [NCV380HMUAJAATBG](#) [TCK2065G,LF](#) [SZNCP3712ASNT3G](#) [L9781TR](#) [NCP45520IMNTWG-H](#) [MC17XS6500BEK](#) [SP2526A-1EN-L/TR](#) [SP2526A-2EN-L/TR](#) [MAX4999ETJ+T](#) [MC22XS4200BEK](#) [MAX14575BETA+T](#) [VN1160C-1-E](#) [VN750PEP-E](#) [TLE7244SL](#)
[L9352B-TR-LF](#) [BTS50060-1EGA](#) [MAX1693HEUB+T](#) [MC07XSG517EK](#) [TLE7237SL](#) [MIC2033-05BYMT-T5](#) [MIC2033-12AYMT-T5](#)
[MIC2033-05BYM6-T5](#) [MP6513LGJ-P](#) [NCP3902FCCTBG](#) [AP22811BW5-7](#) [SLG5NT1437VTR](#) [SZNCP3712ASNT1G](#) [NCV330MUTBG](#)
[DML1008LDS-7](#) [MAX4987AEETA+T](#) [KTS1670EDA-TR](#) [MAX1694EUB+T](#) [KTS1640QGDV-TR](#) [KTS1641QGDV-TR](#) [IPS160HTR](#)
[BTS500251TADATMA2](#) [MC07XS6517BEKR2](#) [SIP43101DQ-T1-E3](#) [DML10M8LDS-13](#) [MAX1922ESA+C71073](#)