



## STANDARD CIRCULAR CONNECTORS



✓ Active

TE CONNECTIVITY (TE)

### SQUARE FLANGE RECEPTACLE

DEUTSCH | 38999 Series III

D38999/20ME08PN

TE Internal Number: YACT20ME08PNV00100

Mil-Spec: D38999/20ME08PN

Alias ID: ACT20ME08PNV001

Always EU RoHS/ELV Compliant

Product Type **Connector**

Mounting Style **Square Flange**

Shell Plating Material **Electroless Nickel**

Shell Material **Composite**

Polarization Code **N**

No documentation available.

Please review product documents or [contact us](#) for the latest agency approval information.

#### Product Type Features

Product Type	<b>Connector</b>
Connector System	<b>Wire-to-Panel</b>
Shell Size	<b>E (17)</b>
Sealed	<b>Yes</b>
Connector Style	<b>Receptacle</b>
Shell Type	<b>Square Flange Receptacle</b>
Assembly Type	<b>Electrical Connector</b>

#### Configuration Features

Number of Power Positions	<b>8</b>
Preloaded	<b>No</b>
Number of Positions	<b>8</b>
Factory Installed Backshell	<b>No</b>
Positions Unloaded	<b>All</b>
Keying	<b>Keyway Polarization N</b>
Position Keyed	<b>N</b>

#### Electrical Characteristics

Operating Voltage	<b>900 VAC [ 1250 VDC ]</b>
Voltage (Vrms)	<b>2300</b>

Body Features	Shell Plating Material	<b>Electroless Nickel</b>
	Shell Material	<b>Composite</b>
	Insulation Material	<b>Hard Dielectric/Silicone</b>
	Hermetically Sealed	<b>No</b>
	Weight	<b>19.1 g [ .0422 lb ]</b>
	Fluid Type	<b>Coolanol 25, M2-V, MIL-DTL-5624 (JP-4, JP-5), MIL-DTL-83133 (JP-8), MIL-PRF-23699, MIL-PRF-5606, MIL-PRF-7808, SEA-AMS1424 Type I</b>
	Environmental Protection Type	<b>Elastomer Sealed</b>
	O-Ring Material	<b>Silicone</b>
	Environmental Protection	<b>Yes</b>
	Feedthrough Type	<b>No</b>
	Peripheral Seal Material	<b>Silicone</b>
Entry Style	<b>Rear Insertion</b>	
Contact Features	Contact Layout	<b>E08</b>
	Contact Type	<b>Pin</b>
	Contact Quantity (Size 16)	<b>8</b>
Mechanical Attachment	Mounting Style	<b>Square Flange</b>
	Polarization Code	<b>N</b>
	Mating Alignment Type	<b>Keyed</b>
	Mating Retention	<b>With</b>
	Flange	<b>Square Flange</b>
	Mating Retention Type	<b>Triple Start Threaded</b>
	Panel Mount Retention	<b>With</b>
	Panel Mount Retention Type	<b>Square Flange</b>
Housing Features	Alignment Keyed	<b>Clocking</b>
Dimensions	Accepts Wire Insulation Diameter Range	<b>1.65 – 2.77 mm [ .065 – .109 in ]</b>
	Assembly Length	<b>31.5 mm [ 1.24 in ]</b>
Usage Conditions	Operating Temperature Range	<b>-65 – 200 °C [ -85 – 392 °F ]</b>
	Fluid Resistance	<b>Yes</b>

Operation/Application	Durability Rating (Cycles)	<b>500</b>
Packaging Features	Packaging Quantity	<b>1</b>

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Circular MIL Spec Connector](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[89075GULPR](#) [0025-262-542](#) [0025-264-3014](#) [58-570121-04S](#) [0134-213-1208](#) [0134-213-2209](#) [0025-258-000](#) [60-042022-07P](#) [60-042022-19P](#)  
[60-042022-23P](#) [60-042217-10P](#) [0114-201-1278](#) [012-0467-000](#) [602GB06EG24-61SN](#) [0134-201-1207](#) [0134-213-1006](#) [6104-207-2302](#) [6104-](#)  
[208-1902](#) [61-168211-04P](#) [61-168617-10P](#) [6131-202-19149P](#) [6131-204-21149P](#) [6131-208-13149P](#) [6131-209-17149P](#) [6131-210-11149P](#) [6131-](#)  
[211-19149P](#) [6131-216-19149P](#) [6131-259-21149P](#) [6131-259-23149P](#) [6131-265-17149P](#) [6131-265-19149P](#) [CS3100A18-1P-472](#) [CS3100A-36-](#)  
[77P](#) [CS3101A-16-55P](#) [CS3102A-10SL-55P](#) [CS3102A-14S-58P](#) [CS3102A-32-17P](#) [CS3102A32-25S](#) [CS3102C18-4P-472](#)  
[CS3106A10SL3S004](#) [CS3106A-18-73S](#) [CS3108A-14S-52S](#) [CS3108A-28-51S](#) [6162-233-1277](#) [6162-324-1231](#) [M243082296Z](#)  
[M2884010AC1S1](#) [CT0-24-10SC](#) [CT0M20-7PCAU](#) [M28840/17AC1G3](#)