

71-533720/729		DOCUMENT NO.
REV.	SHEET 1 OF 2	F
REVISIONS		
LTR	DESCRIPTION	DATE
F	(CLII) SEE ECN: B9450	10/13/14 Pratt

71-533720/729




SHEET 1 OF 2

REV.


C

B


A



INK STAMP "AMPHENOL", ASSEMBLY NUMBER (SEE COLUMN) AND DATE CODE (9-3895) APPROX .047 HIGH PER 9-3856-5. EXAMPLE: AMPHENOL 71-533728-18P 1452



6	I	10-330914-XXI	GASKET	
5	I	10-1018XX-()P/S 10-2528XX-()P/S	INSERT	8
4		SEE CONTACT TABLE	CONTACTS	2, 8
3		SEE COLUMN	PACKING	9
2		10-123017-XX3	NUT	
1		10-150903-XX3	SHELL	
POS	QTY	PART NUMBER	DESCRIPTION	NOTE

PARTS LIST						
APPROVALS		DATE	AMPHENOL CORPORATION 40-60 DELAWARE AVENUE SIDNEY, N.Y. 13838			
PREPARED BY L. Pratt		07-Oct-14				
ENGINEER IN CHARGE A. Prescott						
DESIGN MANAGER A. Polishak						
DESIGN ACTIVITY GROUP C & I						
THIRD ANGLE PROJECTION			RECEPTACLE, ELECTRICAL CONNECTOR TYPE PT07C(), SPECIAL, OLIVE DRAB CADMIUM PLATED			
			SIZE C	CAGE CODE 77820	DOCUMENT NO. 71-533720/729	REV. F
SCALE: 1.0 REF: 71-147706/750					SHEET 1 OF 2	

UNLESS OTHERWISE SPECIFIED	SPECIFICATIONS
LINEAR DIMENSIONS ARE IN INCHES TOLERANCES: .XXXX = ±.0005 ANGLES= ±2° .XXX = ±.010 .XX = ±.03 .X = ±.1 DIM. & TOL. PER ASME Y14.5M; DRM PER MIL-DTL-31000; OTHER Amphenol Sds. PER 9-3800 LEGENDS: =FLAG NOTE CALL OUT REFERENCE ONLY	MATERIAL SPEC. N/A
	PROCESS SPEC. SEE NOTES 9 & 10

PRO/ENGINEER INFORMATION	
N/A	Pro/e Model Used:
N/A	71-5337XXP.S.ASSEM
Drawing Name:	
71-533720_729	
NEXT ASSEMBLY	


SEE SHEET 2

NOTES:

THE USE OF THIS DOCUMENT IS UNLIMITED. HOWEVER, DOCUMENTS REFERENCED HEREON MAY CONTAIN LIMITED RIGHTS DATA.

DOCUMENT NO.	SHEET 1 OF 2	REV.
71-533720/729		F

ASSEMBLY NUMBER	PT NUMBER	PACKING	C +.010 -.025	D +.010 -.025	E +.010 -.020	G PANEL THICKNESS		K +.011 -.010	M	ØN +.001 -.005	P HEX +.017 -.016	S	U MAX	Z +.025 -.035	RR THREAD (PLATED) CLASS 2A	ØSS +.000 -.016	ZZ +.000 -.010
						MIN	MAX										
71-533720-()	PT07C- 6-()	10-090351-015	.337	.025	.085	.062	.125	.125	.696	.348	.625	.812	.153	.376	.4375-28 UNEF	.439	.405
71-533721-()	PT07C- 8-()	10-090351-017	.337	.025	.085	.062	.125	.125	.696	.473	.750	.938	.153	.376	.5625-24 UNEF	.563	.530
71-533722-()	PT07C-10-()	10-090351-019	.337	.025	.085	.062	.125	.125	.696	.590	.875	1.062	.153	.376	.6875-24 UNEF	.680	.655
71-533723-()	PT07C-12-()	10-090351-022	.337	.025	.085	.062	.125	.125	.696	.750	1.062	1.250	.153	.376	.8750-20 UNEF	.859	.818
71-533724-()	PT07C-14-()	10-090351-024	.337	.025	.085	.062	.125	.125	.696	.875	1.188	1.375	.153	.376	1.0000-20 UNEF	.984	.942
71-533725-()	PT07C-16-()	10-090351-026	.337	.025	.085	.062	.125	.125	.696	1.000	1.312	1.500	.153	.376	1.1250-18 UNEF	1.108	1.066
71-533726-()	PT07C-18-()	10-090351-028	.337	.025	.085	.062	.125	.125	.696	1.125	1.438	1.625	.153	.376	1.2500-18 UNEF	1.233	1.191
71-533727-()	PT07C-20-()	10-090351-128	.399	.087	.147	.062	.250	.156	.884	1.250	1.562	1.812	.215	.367	1.3750-18 UNEF	1.358	1.316
71-533728-()	PT07C-22-()	10-090351-130	.399	.087	.147	.062	.250	.156	.884	1.375	1.688	1.938	.215	.367	1.5000-18 UNEF	1.483	1.441
71-533729-()	PT07C-24-()	10-090351-132	.399	.087	.147	.062	.250	.156	.917	1.500	1.812	2.062	.215	.334	1.6250-18 UNEF	1.610	1.566



CONTACTS	
SIZE	PART NUMBER
20L PIN	10-497534-06D
20L SOCKET	10-597859-FFF
20 PIN	10-497512-06D
20 SOCKET	10-664164-FFF OR 10-497513-06D
16L PIN	10-247924-167
16L SOCKET	10-247926-167
16 PIN	10-247920-168
16 SOCKET	10-247922-168
12 PIN	10-733100-05D
12 SOCKET	—

5. SEE DRAWING 71-146606/50 FOR REQUIRED MATING PLUG ASSEMBLY.
 4. INDICATED DIMENSION IS DISTANCE BETWEEN END OF SHELL AND THE POINT AT WHICH A GAGE PIN, HAVING THE SAME BASIC DIAMETER AS THE MATING CONTACT AND A SQUARE FACE, ENGAGES SOCKET CONTACT SPRING.
 3. TO COMPLETE ASSEMBLY NUMBER AND PT NUMBER, ADD APPLICABLE INSERT ARRANGEMENT SUFFIX TO BASE NUMBERS LISTED ABOVE PER 9-2437-1.
 2. FOR CONTACT ARRANGEMENTS, SEE DRAWINGS L-15206/50-().
 1. UNIT ILLUSTRATED MEETS THE APPLICABLE REQUIREMENTS OF MIL-C-26482.
10. PROCESS SPEC:
ASSEMBLY 9-3605-1
9-2437-1, 9-3856-5, 9-3895
TEST 9-3353-1
 9. FOR MAXIMUM SEALING EFFICIENCY, APPLY A LIGHT COAT OF COMPOUND (MIL-S-8660) TO PACKING.
 8. INSERTS AND CONTACTS ARE NOT REMOVABLE.
 7. SEE SEPERATE PARTS LIST FOR COMPONENT PART NUMBERS AND QUANTITIES.
 6. SEE WORK ORDER FOR PERMISSIBLE ADDITIONAL OR ALTERNATE STAMPING.

NOTES:

THE USE OF THIS DOCUMENT IS UNLIMITED.
HOWEVER, DOCUMENTS REFERENCED HEREON
MAY CONTAIN LIMITED RIGHTS DATA.

SIZE C	CAGE CODE 77820	DOCUMENT NO. 71-533720/729	REV. F
SCALE: 1.0		REF. 71-147706/750	SHEET 2 OF 2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Circular MIL Spec Connector](#) ***category:***

Click to view products by [Amphenol](#) ***manufacturer:***

Other Similar products are found below :

[89075GULPR](#) [0025-262-542](#) [0025-264-3014](#) [58-570121-04S](#) [0134-213-1208](#) [0134-213-2209](#) [0025-258-000](#) [60-042022-07P](#) [60-042022-19P](#)
[60-042022-23P](#) [60-042217-10P](#) [0114-201-1278](#) [012-0467-000](#) [602GB06EG24-61SN](#) [0134-201-1207](#) [0134-213-1006](#) [6104-207-2302](#) [6104-](#)
[208-1902](#) [61-168211-04P](#) [61-168617-10P](#) [6131-202-19149P](#) [6131-204-21149P](#) [6131-208-13149P](#) [6131-209-17149P](#) [6131-210-11149P](#) [6131-](#)
[211-19149P](#) [6131-216-19149P](#) [6131-259-21149P](#) [6131-259-23149P](#) [6131-265-17149P](#) [6131-265-19149P](#) [CS3100A18-1P-472](#) [CS3100A-36-](#)
[77P](#) [CS3101A-16-55P](#) [CS3102A-10SL-55P](#) [CS3102A-14S-58P](#) [CS3102A-32-17P](#) [CS3102A32-25S](#) [CS3102C18-4P-472](#)
[CS3106A10SL3S004](#) [CS3106A-18-73S](#) [CS3108A-14S-52S](#) [CS3108A-28-51S](#) [6162-233-1277](#) [6162-324-1231](#) [M243082296Z](#)
[M2884010AC1S1](#) [CT0-24-10SC](#) [CT0M20-7PCAU](#) [M28840/17AC1G3](#)