



SPECIFICATION

CUSTOMER : _____

PRODUCT TYPE : SMD GLASS SEALING XTAL 3.2 × 2.5

NOMINAL FREQ. : 24.576000MHz

TXC P/N : 7V24580009

REVISION : A3

CUSTOMER P/N : _____

Customer Signature & Date

- (1) TXC requires one copy returned with signature and title of authorized individual that signifies acceptance of the attached specifications.
- (2) Orders received and accepted by TXC after return of signed copy of specification will be produced per these specifications.
- (3) Any changes to these specifications must be agreed upon by both parties and new revision of the Product Specification Sheet will be issued.
- (4) Any issuance of purchase order prior to consigning back the Approval page of "Specification Sheets" from customers will be regarded as the agreement on the contents of these specifications.

PE/RD	QA	MFG
<i>Robin Huang</i>	<i>Samson Xiong</i>	<i>Jake Liu</i>
Robin Huang	Samson Xiong	Jake Liu

RoHS Compliant

Spec Sheet Contents

No.	Content	Page
1	ELECTRICAL SPECIFICATIONS	P.3
2	DIMENSIONS	P.4
3	MARKING	P.4
4	FACTORY LOCATION	P.4
5	SUGGESTED REFLOW PROFILE& MANUAL SOLDER CONDITION	P.4
6	STRUCTURE ILLUSTRATION	P.5
7	EMBOSS CARRIER TAPE & REEL	P.6
8	PACKING	P.7
9	RELIABILITY SPECIFICATIONS	P.8~9

■ ELECTRICAL SPECIFICATIONS

Standard atmospheric conditions

Unless otherwise specified, the standard range of atmospheric conditions for making measurement and tests are as follow:

Ambient temperature : $25 \pm 5^{\circ}\text{C}$
 Relative humidity : 40%~70%

If there is any doubt about the results, measurement shall be made within the following limits:

Ambient temperature : $25 \pm 3^{\circ}\text{C}$
 Relative humidity : 40%~70%

Measure equipment

Electrical characteristics measured by S&A250B or equivalent.

Crystal cutting type

The crystal is using AT CUT (thickness shear mode).

Unit Weight:

0.018±0.001 g/pcs

Country of origin:


Made in China/TXC Ningbo Factory

Made in China/TXC Chungking Factory

	Parameters	SYM.	Electrical Spec.				Notes
			MIN	TYP	MAX	UNITS	
1	Nominal Frequency	FL	24.576000			MHz	-
2	Oscillation Mode	-	Fundamental			-	-
3	Load Capacitance	CL	8			pF	-
4	Frequency Tolerance	-	± 15			ppm	at $25 \pm 3^{\circ}\text{C}$
5	Frequency Stability	-	± 20			ppm	Over Operating Temp. Range (Reference 25°C)
6	Operating Temperature	-	-10	~	85	$^{\circ}\text{C}$	-
7	Aging	-	± 3			ppm	1st Year
8	Drive Level	DL	-	50	300	μW	-
9	Equivalent Resistance Rr	Rr	-	-	50	Ω	-
10	Shunt Capacitance C0	C0	-	-	3	pF	-
11	2 times reflow	-	-	-	-	-	All electric characteristics should be guaranteed after twice reflow.
12	Spurious	-	-	-	-	-	Frequency of 3F0 +/- 100kHz response 3dB or more.
13	Insulation Resistance	-	500	-	-	M Ω	at DC 100V
14	Storage Temperature Range	-	-40	~	85	$^{\circ}\text{C}$	-


■ DIMENSIONS

(Unit:mm)



*Coplanarity of solderable areas Camber 0.10 mm Max

■ MARKING



Date Code:


YEAR		MONTH													
		JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC		
2005	2009	2013	2017	A	B	C	D	E	F	G	H	J	K	L	M
2006	2010	2014	2018	N	P	Q	R	S	T	U	V	W	X	Y	Z
2007	2011	2015	2019	a	b	c	d	e	f	g	h	j	k	l	m
2008	2012	2016	2020	n	p	q	r	s	t	u	v	w	x	y	z

*This date code will be cycled every four years

■ SUGGESTED REFLOW PROFILE(QCII-P1-06)


Pb-free Reflow Profile		
CONDITION	S=REFLOW	W=REFLOW
REFLOW		
PEAK TEMP/TIME	240°C/5s ≥	230°C/5s
220°C ≤	20 ~ 40s	20 ~ 40s
PREHEAT		
150 ~ 190°C	90 ~ 120s	90 ~ 120s
MOISUTURE PROOF	(It is not necessary)	
OPEN-1st REFLOW	-	-
1st-2nd	-	-
Measure Ponit	SURFACE OF COMPONENT	
Storage Condition	0 ~ 30°C, 70%RH ≥	

■ STRUCTURE ILLUSTRATION



NO	COMPONENTS	MATERIALS		FINISH/SPECIFICATIONS
			supplier	
1	Cap	Ceramic (Al ₂ O ₃)	Kyocera	-
2	Package	Ceramic (Al ₂ O ₃)	Kyocera	-
3	PAD	Au	included in Kyocera base	Tungsten metalize +W plating 10~20um + Ni plating 1.27~8.89um + Au plating 0.2~1.0um The substrate(W or Ni) should not be seen due to less Au.
4	Crystal blank	SiO ₂	TXC	-
5	Conductive adhesive	Resin+Ag	FUJIKURA	-
6	Electrode	Noble Metal	SOLAR	-
7	Sealing Glass	Glass(PbO)	included in Kyocera base	-

■ **EMBOSS CARRIER TAPE & REEL**



DIMENSIONS	A	B	C	D	E	F	G	H	
	1.65±0.10	3.40±0.10	2.70±0.10	4.00±0.10	8.00±0.20	4.00±0.10	1.55±0.10	1.75±0.10	(UNIT : mm)


Release strength of cover tape. It has to be between 20g~80g under following condition.

Pulling Direction : keep angle 165°to 180°

Speed : 300mm/Min.

TAPE	Material	TAPE	Material
Carrier tape	ABS or PS	Cover tape	PS or PET

REMARK :



DIMENSIONS	L	L1	W	W1	
	178±1.00	13±0.50	11.5±0.20	8±0.10	(UNIT : mm)


PACKING

Reel Quantity :

- 1. Reel X 6 (6 Reels)
- 2. Reel X 12 (12 Reels)
- 3. Reel X 25 (12 Reels + 13 Reels)
- 4. Reel X 50 (12 Reelsx2 + 13 Reelsx2)

Box Size:

- 1. L200 X W200 X H140mm
- 2. L200 X W200 X H250mm
- 3. L400 X W200 X H250mm
- 4. L400 X W400 X H280mm



(Label A) Size:80 X 40mm

TXC CORPORATION		QA PASS
DATE CODE:	QTY:	2011/09/02
LOT NO:	<div style="display: flex; align-items: center;"> <div style="border: 1px solid black; padding: 2px; margin-right: 5px;">RoHS</div> </div>	
PART NO:		
FREQ:		

(Label C-3) Size:100 X 50mm

CUSTOMER : Sharp Manufacturing Corporation (M) Sdn Bhd

ORDER NO:

115632- 10

(3N) 1 RCRSCA243WJZZY

(3N) 2 3000 2014/01/17

(1P) 7V24080028

DELIVERY : 2014/01/17

TXC CORPORATION EIAJ C- 3 MADE IN CHINA

(Label B) Size:100 X 100mm

發注者 (CUSTOMER)	Sharp Manufacturing Corporation (M) Sdn Bhd		
受渡場所名 (DELIVERY POINT)	馬來西亞		
客戶訂單號碼: (FRANS NO.)	115632- 10		
客戶料號: (PART NO.)	RCRSCA243WJZZY		
品名: (PART NAME)	7V24080028		
入數/納入數量: (QTY/TOTAL QTY)	3000/150000	單位: (UNIT)	PC
備考: REMARK		Package Count	

(3N) 1 RCRSCA243WJZZY

(3N) 2 3000 2014/01/17

(1P) 7V24080028

[STORAGE]

- 1.The storage time to be 1 year maximum.
- 2.Don't be caught in the rain.
- 3.The storage environment shall be 5℃ ~40℃ temperature and 30% ~ 75%RH humidity and free from the sun shine.
- 4.If customers have special requirements, we can paste labels according to it.



■ **RELIABILITY SPECIFICATIONS**

■ It guarantees after reflow twice by pretreatment.

	Items	Conditions	Specifications								
1	FINE LEAK	He bombing 4.5kg/cm ² for 2 hours	<1 × 10 ⁻⁹ Pa.m ³ /sec								
	GROSS LEAK	Standard sample for automatic gross leak detector, test pressure: 2kg/cm ²	<1.5 × 10 ⁻⁵ Pa.m ³ /sec								
2	Solder heat-resistance Test (Flow Soldering)	Flow Soldering : 260°C±3°C , ≥5 Sec ; (Preheating : 110~120°C ≥70 Sec)	Based on QCII-P1-04 '-8ppm ≤ ΔF ≤ 8ppm -5Ω ≤ ΔF ≤ 5Ω								
3	Solder heat-resistance Test (Hand Soldering)	Hand Soldering : 380°C , ≥3 Sec	Based on QCII-P1-04 '-8ppm ≤ ΔF ≤ 8ppm -5Ω ≤ ΔF ≤ 5Ω								
4	Solder heat-resistance Test (Reflow Soldering)	Reflow Soldering (Whole Heating) Peak Temperature (Solder joint) 240°C MAX ≤5S 220°C以上 ≥40S (Preheat 150~190°C 90±30S) The Reflow count is 2 times or more.	Based on QCII-P1-04 '-8ppm ≤ F ≤ 8ppm -5Ω ≤ F ≤ 5Ω								
5	Solderability	Pb free:240°C±5°C , 5 Sec. 8hours±15min Steam Conditioning(125°C , 120Sec. Preheated)	Based on QCII-P1-02 95% Covered								
6	Solder Joint Strength	1. TEMP. CYCLE TEST <table border="1" style="margin-left: 20px;"> <tr> <td>MINI TEMP.</td> <td>-40°C</td> </tr> <tr> <td>MAX TEMP.</td> <td>+125°C</td> </tr> <tr> <td>TIME</td> <td>Each 30 minutes</td> </tr> <tr> <td>CYCLES</td> <td>200</td> </tr> </table> 2. Measurement Item Bend Test (EIAJ ED-4702) 3.Measurement cycle : INITIAL, (100) , 200 4.Measurement SMPL : ≥5POINTS	MINI TEMP.	-40°C	MAX TEMP.	+125°C	TIME	Each 30 minutes	CYCLES	200	Based on SHARP reliability standard Reliability Test Standard for QC II -P1-05 1.The variation must be 50% 2.After test measured items mustbe 75%
MINI TEMP.	-40°C										
MAX TEMP.	+125°C										
TIME	Each 30 minutes										
CYCLES	200										
7	Board Flex	Apply pressure in the direction of the arrow at a rate of about 0.5 mm/s until bent width reaches 3 mm and hold for 60 s. <div style="text-align: center; margin-top: 20px;"> </div>	-10ppm ≤ ΔF ≤ 10ppm -5Ω ≤ ΔF ≤ 5Ω								

■ **RELIABILITY SPECIFICATIONS**

■ It guarantees after reflow twice by pretreatment.

	Items	Conditions	Specifications
8	Terminal Strength(SMD)	<p>Applied Force: 1.8 kg , Duration Time: 60 ±1 Sec</p> <p>Refer to AEC_Q200 METHOD - 006</p> 	<p>-10ppm ≤ ΔF ≤ 10ppm</p> <p>-5Ω ≤ ΔF ≤ 5Ω</p>
9	Core body strength	<p>A static load of 10 N using a R 0.5 scratch tool shall be applied on the core of the component and in the direction of the arrow and held for 10 ±1S.</p> 	<p>-10ppm ≤ ΔF ≤ 10ppm</p> <p>-5Ω ≤ ΔF ≤ 5Ω</p>
10	Electrical resistance to solvents	<p>Ultrasonic cleaning Cleaning agent shall be Isopropyl Alcohol. Condition shall be 20mW/cm³, 28KHz, 60 sec (at room temperature.) Immersion cleaning the specimen shall be cleansed at normal temperature for 90s using isopropyl alcohol.</p>	<p>-10ppm ≤ ΔF ≤ 10ppm</p> <p>-5Ω ≤ ΔF ≤ 5Ω</p> <p>Appearance without distinct</p>

RELIABILITY SPECIFICATIONS

It guarantees after reflow twice by pretreatment.

Items	Conditions	Specifications															
11 Vibration	Frequency range: 10-2000Hz, Amplitude: 1.52m/20G, Sweep time: 20 minutes 3 directions for X,Y,Z axis 12 hours	Frequency: ±5ppm Cl: ±5Ω															
12 Mechanical Shock	Peak Acceleration:1000G,Number of Shock: 3 Planes* 6 Shock ;Duration Time:0.3ms.	Frequency: ±5ppm Cl: ±5Ω.															
13 Drop Test	Height 150cm, 3 times on concrete	Frequency: ±5ppm Cl: ±8Ω															
14 Thermal shock test	-40°C to 125°C ,15min dwell time at each temperatureextreme.1 min. maximum transition time.300cycles. measurement taken after 1 hours. <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th></th> <th>Temperature</th> <th>Duration</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>-40±3°C</td> <td>15 minutes</td> </tr> <tr> <td>2</td> <td>25°C</td> <td>Within 1 minute</td> </tr> <tr> <td>3</td> <td>125±2°C</td> <td>15 minutes</td> </tr> <tr> <td>4</td> <td>25°C</td> <td>Within 1 minute</td> </tr> </tbody> </table>		Temperature	Duration	1	-40±3°C	15 minutes	2	25°C	Within 1 minute	3	125±2°C	15 minutes	4	25°C	Within 1 minute	Frequency: ±10ppm Cl: ±5Ω
	Temperature	Duration															
1	-40±3°C	15 minutes															
2	25°C	Within 1 minute															
3	125±2°C	15 minutes															
4	25°C	Within 1 minute															
15 High Temp. Storage test	125°C ± 3°C, 500 hours,measurement taken after 1 hours.	Frequency: ±10ppm Cl: ±5Ω															
16 Low Temp. Storage test	-40°C ± 3°C, 500 hours,measurement taken after 1 hours.	Frequency: ±10ppm Cl: ±5Ω															
17 High Temp and Humidity test	85°C ± 3°C, RH 85% , 1000 hours,measurement taken after 1 hours.	Frequency: ±10ppm Cl: ±5Ω															
18 Packing Test-Vibration	10~55~10Hz..1minute, 2 hours for each directions (X,Y,Z axis) Box Material: Carton	Frequency: ±10ppm Cl: ±5Ω															
19 Packing Test-Drop test	Height 100cm, onto stainless steel. 1edge, 3 corner, 6 side, Box Material: Carton	Frequency: ±15ppm Cl: ±10Ω															

REMARK**1. Connection before change**

When the alternation of specification, material, production process and control system of this product is changed, Quality and reliability data shall be submitted in advance, and information documents shall be submitted to both of Engineering Department and Quality and Reliability Control Center in SHARP Digital Information Appliance Group.

2. Use regulation of ozone depleting substances

The substances for regulation:CFCs, Furiong, 4 chlorination carbon, 1-1-1 trichloroethane(Methyl Chloroform)

2-1 The above-mentioned substances is not contained on this products or parts.

2-2 The above-mentioned substances is not contained in the manufacturing process of this produce of parts.

3. Manufacturing Factory

TXC Ningbo Factory

No. 189 Huang Shan West Road, Dagong Industrial City

Ningbo Economic & Technical Development Zone, Ningbo Zhejiang China PC315800

TEL : 86-574-86874666 FAX : 86-574-86874066

TXC Chungking Factory

Post cpde:401329

No.22 Fung Sheng Rd.,Jiulongpo District,Chungking.China

TEL : 86-023-61511888 FAX : 86-023-61511889

4. This product will be screening by 2 times reflow (Peak temp. 240°C/5s Min.)**Notice**

- Order items are manufactured according to specification. As to conditions, which are not indicated in this specification and unpredictable such as applied condition and oscillation margin, please check them beforehand.
- If you intend to use products listed on this specification for application that may result in loss of life or assets (controls relating to safety, medical equipments, aeronautical equipment, space equipment, etc.) not please do fail to advise us of your intention beforehand.
- Information contained in this specification must not be quoted, reproduced or used for other purposes
- Please do not use of ultrasonic cleaning machines for clean crystals due to avoid influence for performance.
- Storing crystal unit at high temperature and humidity may deteriorate the soldering condition of terminal. Please do not store in direct sunlight and damp environments.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Crystals category](#):

Click to view products by [TXC Corporation manufacturer](#):

Other Similar products are found below :

[CS325S24000000ABJT](#) [718-13.2-1](#) [MC405 32.0000K-R3:PURE SN](#) [FC-135R 32.7680KF-A3](#) [7A-40.000MAAE-T](#) [7B-27.000MBBK-T](#)
[FL2000085](#) [9B-15.360MBBK-B](#) [9C-7.680MBBK-T](#) [ASH7K-32.768KHZ](#) [AT-41.600MAGQ-T](#) [BTD1062E05A-513](#) [LFXTAL066198Cutt](#)
[9C-14.31818MBBK-T](#) [FA-238 50.0000MB30X-K3](#) [FC-12M 32.7680KA-AC3](#) [SSPT7F-9PF20-R](#) [FX325BS-38.88EEM1201](#)
[LFXTAL065253Cutt](#) [LFXTAL066431Cutt](#) [XT9S20ANA14M7456](#) [XT9SNLANA16M](#) [646G-24-2](#) [7A-24.576MBBK-T](#) [7B-30.000MBBK-T](#)
[WX26-32.768K-6PF](#) [9B-14.31818MBBK-B](#) [CD1AM](#) [7B-25.000MAAE-T](#) [7A-14.31818MBBK-T](#) [6504-202-1501](#) [6526-202-1501](#) [FA-118T](#)
[27.1200MB50P-K0](#) [FC-135R 32.7680KA-A3](#) [ABM12-104-37.400MHZT](#) [ABLS-10.000MHZ-D3W-T](#) [BTJ112E01E-513](#) [BTJ722K01C-7067](#)
[BTL-20-513](#) [TSX-3225 24.0000MF15X-AC](#) [TSX-3225 16.0000MF18X-AC](#) [BTJ120E02C](#) [BTL-12-513](#) [7A-10.000MBBK-T](#) [7A-](#)
[11.0592MBBK-T](#) [ABM12-103-24.000MHZT](#) [CS325S25000000ABJT](#) [ABM3B-25.000MHZ-B2-X-T](#) [FC-135 32.7680KA-A5](#) [FX0800015](#)