

ADAM-6150

ADAM-6151/6156

ADAM-6160

15-ch Isolated Digital I/O Real-time Ethernet Module

16-ch Isolated Digital Input/ Digital Output Real-time Ethernet Module

6-ch Relay Real-time Ethernet Module



ADAM-6150/6151/6156

FCC CE RoHS

Specifications

Digital Input

- **Channels** ADAM-6150: 8
ADAM-6151: 16
- **Dry Contact** Logic level 0: open
Logic level 1: close to DGND
- **Wet Contact** Logic level 0: 0 ~ 3 V_{DC} or 0 ~ -3 V_{DC}
Logic level 1: 10 ~ 30 V_{DC} or -10 ~ -30 V_{DC}
(Dry/Wet Contact decided by switch)
- **Input Impedance** 5.2 kΩ (Wet Contact)
- **Transition Time** From logic level 0 to 1: 0.2 ms
From logic level 1 to 0: 0.2 ms

Digital Output

- **Channels** ADAM-6150: 7
ADAM-6156: 16
- **Output Voltage Range** 8 ~ 35 V_{DC}
- **Normal Output Current** 100 mA (per channel)

Ordering Information

- **ADAM-6150EI** 15-ch Isolated DI/O EtherNet/IP Module
- **ADAM-6151EI** 16-ch Isolated DI EtherNet/IP Module
- **ADAM-6156EI** 16-ch Isolated DO EtherNet/IP Module
- **ADAM-6150PN** 15-ch Isolated DI/O PROFINET Module
- **ADAM-6151PN** 16-ch Isolated DI PROFINET Module
- **ADAM-6156PN** 16-ch Isolated DO PROFINET Module



ADAM-6160

FCC CE RoHS

Specifications

Relay Output

- **Channels** 5 Form C and 1 Form A
- **Contact Rating** 250 V_{AC} @ 5A
30 V_{DC} @ 5A
- **Max. Switching Voltage** 400 V_{AC}
300 V_{DC}
- **Breakdown Voltage** 500 V_{AC} (50/60Hz)
- **Max. Breakdown Capacity** 1250 VA
- **Frequency of Operation** 360 operations/hour with load
72,000 operations/hour without load
- **Set/Reset Time** 8 ms/8 ms
- **Mechanical Endurance** > 15 x 10⁶ operations
- **Isolation between Contact** 1000 V_{rms}
- **Insulation Resistance** > 10 GΩ @ 500 V_{DC}

Ordering Information

- **ADAM-6160EI** 6-ch Relay EtherNet/IP Module
- **ADAM-6160PN** 6-ch Relay PROFINET Module

Common Specifications

General

- **LAN** 10/100Base-T(X)
- **Power Consumption** ADAM-6150: 3 W @ 24 V_{DC}
ADAM-6151: 2.7 W @ 24 V_{DC}
ADAM-6156: 3.2 W @ 24 V_{DC}
ADAM-6160: 4.5 W @ 24 V_{DC}
- **Connectors** 2 x RJ-45 LAN, (Daisy Chain)
Plug-in screw terminal block (I/O and power)
- **Watchdog** System (1.6 second)
- **Power Input** 10 ~ 30 V_{DC}

Protection

- **Over Voltage Protection** ±35 V_{DC}
- **Isolation Protection** 2,500 V_{DC}
- **Power Reversal Protection**

Environment

- **Operating Temperature** -10 ~ 70°C (14 ~ 158°F)
- **Storage Temperature** -20 ~ 80°C (-4 ~ 176°F)
- **Operating Humidity** 20 ~ 95% RH (non-condensing)
- **Storage Humidity** 0 ~ 95% RH (non-condensing)
0 ~ 95% RH (non-condensing)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Controllers](#) category:

Click to view products by [Advantech](#) manufacturer:

Other Similar products are found below :

[CS1WCN223](#) [CS1WCN713](#) [CS1WKS001E](#) [61F-11NH](#) [61FGPN8DAC120](#) [61F-GP-NT AC110](#) [61F-GPN-V50-AC110](#) [70177-1011](#) [F03-03](#)
[HAS B](#) [F03-03 HAS C](#) [F03-31](#) [81513201](#) [81513535](#) [81550401](#) [FT1A-C12RA-W](#) [88981106](#) [H2CAC24A](#) [R88A-CAGA005S](#) [R88A-](#)
[CRGB003CR-E](#) [R88ARR080100S](#) [R88A-TK01K](#) [DCN1-1](#) [DTB4896VRE](#) [DTB9696CVE](#) [DTB9696LVE](#) [MR-50LF+](#) [E53-AZ01](#) [E53E8C](#)
[E5CWLQ1TCAC100240](#) [B300LKL21](#) [NE1ASCPU02EIPVER11](#) [NE1SCPU01](#) [NE1SDRM21U](#) [NSCXDC1V3](#) [NSH5-232CW-3M](#)
[NT20SST122BV1](#) [NV3Q-SW41](#) [NV4W-ATT01](#) [NV-CN001](#) [OAS-160-N](#) [K31S6](#) [K33-L1B](#) [K3TX-AD31A](#) [L595020](#) [SRS2-1](#) [G32X-V2K](#)
[26546803](#) [26546805](#) [26546831](#) [CJ1W-OD204](#)