



Fittings with fixed external thread

- HG-45 45° Elbow, IP66

45° elbow external thread.

Features and Benefits

- One piece, fast fit
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus
- Metric threads supplied with locknuts



HelaGuard HG-45 45° Elbow, IP66.

Fittings with UNEF and NPT threads available on request. Please contact us!

MATERIAL	Polyamide 6.6 (PA66)
Operating Temperature	-50 °C to +135 °C
Flammability	UL94 V2
Specifications	UL-Recognised



TYPE	Nominal Ø	Thread Size (metric)	Thread Size (PG)	Min. Bore Size	Outside Ø max.	Length (L)	A/F Body	Thread Length	Pack Cont.	Colour	Article-No.
HG16-45-PG13	16	-	PG13.5	14.0	29	58	26	11	10 pcs.	Black (BK)	166-23406
HG16-45-M20	16	M20	-	14.0	29	58	27	13	10 pcs.	Black (BK)	166-23400
HG21-45-PG13	21	-	PG13.5	14.0	32	61	26	11	10 pcs.	Black (BK)	166-23407
HG21-45-PG16	21	-	PG16	14.0	32	61	27	11	10 pcs.	Black (BK)	166-23408
HG21-45-M20	21	M20	-	14.0	32	61	27	13	10 pcs.	Black (BK)	166-23401
HG28-45-PG21	28	-	PG21	19.0	44	73	35	12	10 pcs.	Black (BK)	166-23409
HG28-45-M25	28	M25	-	19.0	44	73	32	15	10 pcs.	Black (BK)	166-23402
HG34-45-PG29	34	-	PG29	24.5	51	81	44	12	10 pcs.	Black (BK)	166-23410
HG34-45-M32	34	M32	-	24.5	51	81	40	16	10 pcs.	Black (BK)	166-23403
HG42-45-PG36	42	-	PG36	39.0	63	98	57	12	2 pcs.	Black (BK)	166-23411
HG42-45-M50	42	M50	-	39.0	63	98	60	16	2 pcs.	Black (BK)	166-23404
HG54-45-M50	54	M50	-	39.0	76	106	60	16	2 pcs.	Black (BK)	166-23405

All dimensions in mm. Subject to technical changes.

Colour grey available on request. Minimum Order Quantity (MOQ) may differ from package content.



Please note! Not all products listed on this page may have this approval. For product specific approvals please refer to the Appendix.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Conduit Fittings & Accessories](#) category:

Click to view products by [Hellermann](#) manufacturer:

Other Similar products are found below :

[S53.35A](#) [260-416](#) [DM0240-1/2A](#) [817.612.0](#) [55506625](#) [1.511.2001.50](#) [1.533.1601.50](#) [1.533.2001.50](#) [52005810](#) [817.716.0](#) [712.015.0](#) [216-420](#) [2276](#) [2663-P](#) [C2070-P](#) [3582V](#) [2643-P](#) [4975](#) [2644-P](#) [90480](#) [2404-P](#) [1047561](#) [2723-P](#) [55506355](#) [1.513.1101.14](#) [55502461](#) [55502462](#) [55502463](#) [55502464](#) [55502473](#) [166-22214](#) [166-22215](#) [166-24800](#) [166-25801](#) [166-30318](#) [SHR-C1](#) [2037 12-20 LGR](#) [2037 16-24 LGR](#) [HP50SS](#) [55502470](#) [SH PA6 BL ND10](#) [5308 946](#) [295.012.0](#) [2955 M16](#) [2955 M25](#) [2955 M32](#) [2955 M40](#) [297.212.0](#) [297.240.0](#) [298.012.0](#)