



Differential pressure gauge operated with smartphone

testo 510i

Compact professional measuring instrument from the Testo Smart Probes series, for use with smartphones/tablets

Measurement of gas flow and static pressure, as well as volume flow

Measurement menu for pressure-drop test including alarms

Easy configuration and determination of the volume flow

Measurement data analyzed and sent via testo Smart Probes App

Magnetic fixture for better attachment

Space-saving and easy to transport



mbar

m/s



Bluetooth
+ App

testo Smart Probes App
for free download



The differential pressure gauge testo 510i, in combination with a smartphone or tablet, is suitable for measurements of gas flow and static pressure, pressure drops on ventilators and filters, and for pressure-drop tests on gas pipes. In addition to this, the compact measuring instrument can be used for determining air flow velocity and volume flow. Via the testo Smart Probes App installed on the end

device, users can comfortably read off their measurement values, configure volume flow measurements quickly and easily, and reliably determine timed and multi-point mean values. The App also includes a measurement menu for the pressure-drop test including alarm. All measurement data can be presented either as a diagram or in tabular form. The measurement protocols can then be directly sent as PDF or Excel files.

Technical data/accessories

testo 510i

testo 510i, differential pressure gauge operated with smartphone, incl. hose set (\varnothing 4 mm and 5 mm) with adapter, batteries and calibration protocol

Order no. 0560 1510



testo Smart Probes App

The App turns your smartphone/tablet into the display of the testo 510i. The operation of the measuring instrument as well as the display of the measurement values take place by Bluetooth via the Testo Smart Probes App on your smartphone or tablet – independently of the measurement location. In addition to this, you can use the App to create measurement reports, add photos and comments to these, and send them by e-mail. For iOS and Android.



Sensor type

Pressure

Measuring range	-150 to 150 mbar
Accuracy ± 1 digit	± 0.05 mbar (0 to 1 mbar) $\pm (0.2 \text{ mbar} + 1.5 \% \text{ of m.v.})$ (1 to 150 mbar)
Resolution	0.01 mbar

General technical data

Compatibility	requires iOS 8.3 or newer / Android 4.3 or newer
	requires mobile end device with Bluetooth 4.0
Storage temperature	-20 to +60 °C
Operating temperature	-20 to +50 °C
Battery type	3 micro batteries AAA
Battery life	150 hrs
Dimensions	148 x 36 x 23 mm
Warranty	2 years

Accessories

Order no.

testo Smart Case (VAC) for the storage and transport of testo 405i, testo 410i, testo 510i, testo 605i, testo 805i and testo 905i, dimensions 270 x 190 x 60 mm

0516 0260

ISO calibration certificate pressure, accuracy > 0.6 % of final value

0520 0005

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Testo manufacturer:](#)

Other Similar products are found below :

[206 PH1](#) [TESTO 316-1 0632 0316](#) [TESTO 470 0563 0470](#) [TESTO 770-1 0590 7701](#) [TESTO 905-T1 0560 9055](#) [0572 0500](#) [0590 0016](#) [0602](#)
[4592](#) [0590 0008](#) [0590 0018](#) [0602 0645](#) [0635 1025](#) [0628 0020](#) [TESTO 435-2 0563 4352](#) [TESTO 605I 0560 1605](#) [TESTO 755-2](#) [0590 7552](#)
[TESTO 770-2 0590 7702](#) [TESTO 869 + TESTO 745](#) [TESTO 869 + TESTO 750-3](#) [465](#) [410-2](#) [460](#) [0572 6172](#) [0590 0001](#) [0614 2272](#) [TESTO](#)
[417 0560 4170](#) [0609 7072](#) [TESTO 174-H SET](#) [TESTO 176-T4](#) [TESTO 176-P1](#) [TESTO 830-T2](#) [TESTO 103](#) [TESTO 905-T1](#) [TESTO 108-2](#)
[TESTO 905I](#) [TESTO 108](#) [0563 4403](#) [0590 7703](#) [TESTO 435-3 0560 4353](#) [TESTO 735-1 0560 7351](#) [TESTO 760-3 0590 7603](#) [TESTO 770-3](#)
[0590 7703](#) [0590 0013](#) [0602 4892](#) [TESTO 635-2 0563 6352](#) [TESTO 750-3 0590 7503](#) [TESTO 760-1 0590 7601](#) [816-1](#) [TESTO 174-T SET](#)
[TESTO 605-H1](#)