

Data sheet


Connection line M12 X-coded, 5.0 m
M12 plug straight - M12 plug angled
8-pole, position of coding 315°

Page 1/6


P/N
142M2X19050
EAN 4250184174912

2018-13-02


Illustrations



Dimensional drawing



Wiring



See enlarged drawings at the end of document

Product specification

- shielded M12-M12 Ethernet connection line
- Cat.6A, 8-pole, X-coded
- side 1: M12 connector, straight
- side 2: M12 connector, angled, position of coding 315°
- extrusion-coated cable on M12 connectors
- stranded wires 4x2xAWG26/7 PiMF
- overall shield tinned copper braid
- 1:1 pin assignment
- green cable, PUR
- variants: 1.0 m, 2.0 m, 5.0 m, 10.0 m
- other cable lengths on request



Data sheet

Page 2/6

Connection line M12 X-coded, 5.0 m M12 plug straight - M12 plug angled 8-pole, position of coding 315°

P/N

142M2X19050

EAN 4250184174912

2018-13-02

Technical Data

General Data

Fields of application

Industrial Ethernet

Design

Ethernet-Connection line

Shielding

shielded

Transmission technology

Copper

Cable Type

S/FTP

Number of twisting elements

4

Twisting element

Pair

Wiring

1 - 1

Color coding fiber/ wire(s)

white/orange, orange, white/green, green, white/brown, brown, white/blue, blue

Color

green

Dimensions

Dimension - Interface 1 (L x W x H)

48.50 x 19.00 x 21.50 mm

Dimension - Interface 1 (L x W x H)

1.909 x 0.748 x 0.846 in.

Dimension - Interface 2 (L x W x H)

50.50 x 15.00 x 15.00 mm

Dimension - Interface 2 (L x W x H)

1.988 x 0.591 x 0.591 in.

Cable length (m)

5.00 m

Labeling option

identification label carrier

Transmission characteristics

Category (ISO)

7

Connections/interfaces

Connector technology interface 1

M12-plug

Connector technology interface 2

M12-plug

Coding interface 1

X-coded

Coding interface 2

X-coded

Number of positions/contacts interface 1

8

Number of positions/contacts interface 2

8

Termination data, stranded wire (min. - max.)

Conductor cross section, stranded wire

AWG 26/7

Conductor cross section, stranded wire

0.141 mm²

Conductor diameter, stranded wire (bare copper)

0.483 mm

Conductor diameter, stranded wire (bare copper)

0.019 in.



Data sheet

Page 3/6

Connection line M12 X-coded, 5.0 m M12 plug straight - M12 plug angled 8-pole, position of coding 315°

P/N

142M2X19050

EAN 4250184174912

2018-13-02

Technical Data

Connections/interfaces

Cable sheath diameter (min. - max.)

Cable sheath diameter 6.40 mm

Cable sheath diameter 0.236 in.

Electrical characteristics

Current carrying capacity 0.5 A

Insulation resistance min. 100 MOhm

Mechanical characteristics

Maximum operating bending radius 64 mm

Maximum operating bending radius 2.52 in.

Maximum installation load 32 mm

Maximum installation load 1.26 in.

Shielding braid coverage 70 %

Materials and material properties

Material - Conductor Cu (copper)

Material - Conductor Insulation Polyethylen

Material - Cable jacket PUR

Material - Body interface 1 Plastics

Material - Body interface 2 Plastics

Material - Contact interface 1 CuZn (brass)

Material - Contact interface 2 CuZn (brass)

Material - Contact finish interface 1 Au (gold)

Material - Contact finish interface 2 Au (gold)

Material - Contact carriers interface 1 Plastics

Material - Contact carriers interface 2 Plastics

Material - Union nut interface 1 CuZn (brass)

Material - Union nut interface 2 CuZn (brass)

Material - Union nut finish interface 1 Ni (nickel)

Material - Union nut finish interface 2 Ni (nickel)

Material - Pair shield plastic film

Material - Pair shield finish Al (Aluminium)

Material - Main shield Cu (copper) braid

Material - Main shield finish Sn (tin)



P | Cabling

Data sheet

Page 4/6

Connection line M12 X-coded, 5.0 m M12 plug straight - M12 plug angled 8-pole, position of coding 315°

P/N

142M2X19050

EAN 4250184174912

2018-13-02

Technical Data

Materials and material properties

Flame retardancy	yes
Halogen free	yes
Oil resistance	yes
UV-resistance	yes

Environmental conditions

Temperature (min. - max.)	
Temperature - Operating °C	-30 - 90 °C
Temperature - Operating °F	-22 - 194 °F
Particulate ingress interface 1	IP6X when plugged in
Liquid ingress/immersion interface 1	IPX5, IPX7 when plugged in
Pollution degree interface 1	2
Pollution degree interface 2	2

Approvals

RoHS	compliant
------	-----------

The product meets the following standards

Connectors for electronic equipment	
Free and fixed connectors	IEC 60603-7-51
circular connector	DIN EN 61076-2-109
Multi-element metallic cables used in analogue and digital communication and control	DIN EN 50288-4-2
Test for vertical flame propagation for a single insulated wire or cable	DIN EN 60332-1-2
Measurement of smoke density of cables burning	IEC 61034

Classifications

ETIM 5.0	EC002599
ETIM 6.0	EC002599



P | Cabling

Data sheet

Page 5/6

Connection line M12 X-coded, 5.0 m
M12 plug straight - M12 plug angled
8-pole, position of coding 315°

P/N

142M2X19050

EAN 4250184174912

2018-13-02

Technical Data

Packing details

Type of packaging

1 pc(s) / plastic bag



P | Cabling

Data sheet

Page 6/6

Connection line M12 X-coded, 5.0 m
M12 plug straight - M12 plug angled
8-pole, position of coding 315°

P/N


142M2X19050

EAN 4250184174912


2018-13-02

Illustrations

Dimensional drawing



Wiring



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Metz](#) manufacturer:

Other Similar products are found below :

[142M4D95050](#) [ASP0631006](#) [4898-454G](#) [4895-454G](#) [4887-454G](#) [4897-454G](#) [ASP0460622](#) [142M2X25005](#) [ASP0440222](#) [1108861321](#)
[1108311319](#) [1108501319](#) [11089313](#) [834HTC-900ML](#) [130920-E](#) [150240C30610E](#) [110304412004](#) [1108831326](#) [150240C30310S](#) [135015-](#)
[SSC-E](#) [1528SBGT19E](#) [1401110012KE](#) [142M2X15010](#) [11085813](#) [810-500](#) [810-50](#) [31336104](#) [ASP0430922](#) [SP06502VBNF](#) [31217103](#)
[142M1D19020](#) [SR99S01VBNN0001](#) [31213102](#) [31251104](#) [AST0820406](#) [1108811319](#) [142M2XB5050](#) [834B-375ML](#) [841ER-1.17L](#)
[31009105](#) [31020205](#) [31024102](#) [31027103](#) [31383106](#) [130922-03-E](#) [130924-E](#) [11027605](#) [1108841319](#) [1108341319](#) [15024AD206-E](#)