

DO NOT  
SCALE FROM  
THIS PRINT

| TABLE 1<br>LEAD STYLE SPECIFICATION |                |              |                          |                                        |
|-------------------------------------|----------------|--------------|--------------------------|----------------------------------------|
| -XX                                 | -S, -D, -T, -P | -S-RA, -P-RA | -D-RA                    | -T-RA                                  |
| -01                                 | C-08-1-XXX     | N/A          | N/A                      | N/A                                    |
| -02                                 | C-08-2-XXX     | C-08-2-XXX   | C-08-2-XXX<br>C-08-3-XXX | C-08-2-XXX<br>C-08-3-XXX<br>C-08-5-XXX |
| -03                                 | C-08-3-XXX     | C-08-3-XXX   | C-08-3-XXX<br>C-08-5-XXX | N/A                                    |
| -04                                 | C-08-5-XXX     | C-08-5-XXX   | N/A                      | N/A                                    |
| -06                                 | C-08-6-XXX     | N/A          | N/A                      | N/A                                    |
| -21                                 | C-17-1-XXX     | N/A          | N/A                      | N/A                                    |
| -22                                 | C-17-2-XXX     | C-17-2-XXX   | C-17-2-XXX<br>C-17-3-XXX | C-17-2-XXX<br>C-17-3-XXX<br>C-17-5-XXX |
| -23                                 | C-17-3-XXX     | C-17-3-XXX   | C-17-3-XXX<br>C-17-5-XXX | N/A                                    |
| -24                                 | C-17-5-XXX     | C-17-5-XXX   | N/A                      | N/A                                    |

| TABLE 2    |                 |                            |             |            |            |
|------------|-----------------|----------------------------|-------------|------------|------------|
| LEAD STYLE | "B"             | "G"                        | "C" REF     |            |            |
|            | -S(-RA), -D, -T | -D, -T                     | -S-RA       | -D-RA      | -T-RA      |
| -01, -21   | .104[2.64]      | .005 [ .13]                | N/A         | N/A        | N/A        |
| -02, -22   | .194[4.93]      | .005 [ .13]                | .100[2.54]  | .100[2.54] | .100[2.54] |
| -03, -23   | .394[10.01]     | +.010/-0.012 [+ .25/- .31] | .300[7.62]  | .300[7.62] | N/A        |
| -04, -24   | .584[14.83]     | +.010/-0.012 [+ .25/- .31] | .490[12.45] | N/A        | N/A        |
| -06        | .124[3.15]      | .005 [ .13]                | N/A         | N/A        | N/A        |

| TABLE 4    |               |
|------------|---------------|
| ROW OPTION | BODY          |
| -S         | SSW-XX-S      |
| -D         | SSW-XX-D      |
| -D-N       | NSW-XX-D-N-XX |
| -T         | SSW-XX-T      |
| -P         | SSW-XX-P      |
| -Q         | SSW-XX-T      |

PLATING SPECIFICATION

-G: 20µ" GOLD IN CONTACT AREA,  
3µ" GOLD ON TAIL  
-T: MATTE TIN CONTACT AND TAIL  
(CONTACT -21 THRU -24 N/A)  
-S: 30µ" SELECTIVE GOLD IN CONTACT AREA,  
MATTE TIN ON TAIL  
-H: 30µ" HEAVY GOLD IN CONTACT AREA,  
3µ" GOLD ON TAIL  
-E: 50µ" EXTRA HEAVY GOLD IN CONTACT AREA,  
3µ" GOLD ON TAIL  
(CONTACT -01 & -02 STRAIGHT ONLY)  
-F: 3µ" FLASH SELECTIVE GOLD IN CONTACT AREA,  
MATTE TIN ON TAIL  
-STL: 30µ" SELECTIVE GOLD IN CONTACT AREA,  
TIN/LEAD (90/10 ± 5%) TAIL  
-TL: TIN/LEAD (90/10 ± 5%) CONTACT AND TAIL  
(AVAILABLE ONLY ON LEAD STYLES -01)  
-TM: MATTE TIN CONTACT AND TAIL (CONTACT -21 THRU -24 N/A)  
-SM: 30µ" SELECTIVE GOLD IN CONTACT AREA,  
MATTE TIN ON TAIL  
-FM: 3µ" FLASH GOLD SELECTIVE IN CONTACT AREA,  
MATTE TIN ON TAIL  
-L: 10µ" LIGHT SELECTIVE GOLD IN CONTACT AREA,  
MATTE TIN ON TAIL

No OF POSITIONS  
-01 THRU -50  
(-P OPTION: 36 POS MAX)  
  
LEAD STYLE  
(SEE TABLE 1)  
-01 THRU -06 (STD. INS. FORCE)  
-21 THRU -24 (LOW INS. FORCE)


OPTION  
-LL: LOCKING LEAD  
(SEE FIG 4, SHT 2)  
(N/A IN SINGLE ROW,  
1 & 2 POSITION)

POLARIZING OPTION  
INDICATE POS, SEE FIG 3, SHT 3

OPTION  
-RA: RIGHT ANGLE (SEE FIG 2, SHT 2)  
(STYLE -01 & -21 N/A)  
-N: NOTCH (SEE FIG 6, SHT 3)  
(ONLY AVAILABLE IN -D ROW)  
(ONLY AVAILABLE IN 5, 7, 8, 10, 12,  
13, 15, 17, 20, 25, 32, 36 POSITIONS)  
(USE NSW-XX-D-N-XX BODY,  
SEE TABLE 6)

ROW SPECIFICATION

-S: SINGLE  
-D: DOUBLE  
-T: TRIPLE  
-P: SINGLE  
-Q: TRIPLE WITH ONLY OUTER 2 ROWS  
FILLED



- NOTES:
1. © REPRESENTS A CRITICAL DIMENSION.
  2. MAXIMUM CUT FLASH: .015[0.38] WITH NO FLASH BELOW STANDOFFS OR IN CONTACT HOLES.
  3. MINIMUM CONTACT PUSHOUT FORCE: 1.5 LBS
  4. MAXIMUM ALLOWABLE BOW: .003[0.08] INCH/INCH
  5. NOTE DELETED.
  6. MAXIMUM ALLOWABLE VARIATION BETWEEN ROWS: .010[0.25]
  7. "END WALLS" AFTER CUTTING SHOULD BE .020±.003 [0.51±0.08].
  8. NOTCH ON -P-RA & -D-RA-N OPTIONS TO BE ORIENTED AS SHOWN.
  9. SHEAR LOCATION TO BE WITHIN .001[0.03] OF THE BREAK OFF CENTER LOCATION.
  10. SHEAR LOCATION TO BE WITHIN .001[0.03] OF THE BREAK OFF CENTER LOCATION FOR MACHINE FILL.
  11. LEAD STYLE X2 (SINGLE AND DOUBLE) -RA's TO BE LAYER PACKAGED. ALL OTHER -RA LEAD STYLES: UNDER 5 POSITION TO BE LAYER PACKAGED, 5 AND UP TO BE PACKAGED IN TUBES.




FIG 1

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES.

TOLERANCES ARE:

|                    |        |
|--------------------|--------|
| DECIMALS           | ANGLES |
| .XX: ±.01 [0.3]    | 2°     |
| .XXX: ±.005 [0.13] |        |

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC, INC.

MATERIAL:

INSULATOR: DO NOT SCALE DRAWING

-S, -D, -D-N: VECTRA E130I, COLOR: BLACK UL94 V0

-P, -T: PCTI, COLOR: BLACK UL94 V0

CONTACT: PHOSPHOR BRONZE, SPRING TEMPER ALLOY 511 OR 510

(TENSILE STRENGTH 90-100 KSI)

(YIELD STRENGTH @ 2% OFFSET 88-98 KSI)

PER MIL 8-13501

THICKNESS: .0160±.001 [0.635±0.03]

DESCRIPTION:

ASSEMBLY, SOCKET STRIP .016 X .031 TAIL

DWG. NO.

SSW-1XX-XX-XXX-X-XX-XXX-XX




BY: PURVIS 06/12/1987 SHEET 1 OF 3

**samtec**

520 PARK EAST BLVD, NEW ALBANY, IN 47150

PHONE: 812-944-6733 FAX: 812-948-5047

e-Mail info@SAMTEC.com code 55322



| TABLE 3           |              |              |              |
|-------------------|--------------|--------------|--------------|
| IN-PROCESS        | "D"          | "E"          | "F"          |
| SSW-1XX-X2-X-D-RA | .194 [4.93]  | .394 [10.01] | -----        |
| SSW-1XX-03-X-D-RA | .394 [10.01] | .594 [15.09] | -----        |
| SSW-1XX-02-X-T-RA | .194 [4.93]  | .394 [10.01] | .594 [15.09] |







FIG 2  
RIGHT ANGLE OPTION  
ALL OPTIONS DIFFERENT AS SHOWN, OTHERWISE SAME AS -S-RA



CRIMP LOCATIONS  
ODD POSITIONS  
■ = CRIMP LOCATION



CRIMP LOCATIONS  
EVEN POSITIONS  
■ = CRIMP LOCATION



CRIMP DETAIL  
ALL CONFIGURATIONS

FIG 4  
LOCKING LEAD OPTION  
ALL OPTIONS SAME AS -S-XX-LL  
UNLESS OTHERWISE SHOWN


\* PROPRIETARY NOTE \*  
THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC, INC.

DO NOT SCALE DRAWING  
SHEET SCALE: 2:1




520 PARK EAST BLVD, NEW ALBANY, IN 47150  
PHONE: 812-944-6733 FAX: 812-948-5047  
e-Mail info@SAMTEC.com code 55322


DESCRIPTION:  
ASSEMBLY, SOCKET STRIP .016 X .031 TAIL  
DWG. NO.  
SSW-1XX-XX-XXX-X-XX-XXX-XX  
BY: PURVIS 06/12/1987 SHEET 2 OF 3




SSW-1XX-03-XXX-S-RA  
SSW-1XX-23-XXX-S-RA




SSW-1XX-04-XXX-S-RA  
SSW-1XX-24-XXX-S-RA



SSW-1XX-03-XXX-D-RA  
SSW-1XX-23-XXX-D-RA







SSW-1XX-03-XXX-D-RA-N  
SSW-1XX-23-XXX-D-RA-N



SSW-1XX-XX-XXX-T-RA  
SSW-1XX-XX-XXX-Q-RA

FIG 5  
PACKAGING VIEWS  
(SEE NOTE 11)

| TABLE 5<br>TUBE SPECIFICATION                  |                |       |
|------------------------------------------------|----------------|-------|
| PART NUMBER                                    | TUBE           | PLUG  |
| SSW-1XX-03-XXX-S-RA<br>SSW-1XX-23-XXX-S-RA     | PT-3-24-01-01  | TP-03 |
| SSW-1XX-04-XXX-S-RA<br>SSW-1XX-24-XXX-S-RA     | PT-1-24-01-34  | TP-03 |
| SSW-1XX-03-XXX-D-RA<br>SSW-1XX-23-XXX-D-RA     | PT-1-24-06-40  | TP-07 |
| SSW-1XX-03-XXX-D-RA-N<br>SSW-1XX-23-XXX-D-RA-N | ASP-90341-01-S | TP-07 |
| SSW-1XX-XX-XXX-T-RA<br>SSW-1XX-XX-XXX-Q-RA     | PT-1-24-04-40  | TP-07 |



-S, -P, -S-RA & -P-RA

-D, -D-RA

-D-N, -D-RA-N

-T, -Q, -T-RA & -Q-RA

FIG 3

POLARIZATION LOCATION  
(INSERT PK-06-N INTO SPECIFIED POSITION & BREAK OFF TAB)  
(-RA OPTION SHOWN FOR ORIENTATION PURPOSE ONLY)

| TABLE 6     |               |
|-------------|---------------|
| POS PER ROW | NSW-XX-D-N-XX |
| 5           | NSW-47-D-N-05 |
| 7           | NSW-47-D-N-07 |
| 8           | NSW-44-D-N-08 |
| 10          | NSW-43-D-N-10 |
| 12          | NSW-38-D-N-12 |
| 13          | NSW-41-D-N-13 |
| 15          | NSW-47-D-N-15 |
| 17          | NSW-35-D-N-17 |
| 20          | NSW-20-D-N    |
| 25          | NSW-25-D-N    |
| 32          | NSW-32-D-N    |
| 36          | NSW-36-D-N    |




FIG 6  
NOTCH OPTION  
DIFFERENT AS SHOWN, OTHERWISE SAME AS FIG 1

PROPRIETARY NOTE  
THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC, INC.

DO NOT SCALE DRAWING

SHEET SCALE: 2:1



520 PARK EAST BLVD, NEW ALBANY, IN 47150  
PHONE: 812-944-6733 FAX: 812-948-5047  
e-Mail info@SAMTEC.com code 55322

DESCRIPTION:  
ASSEMBLY, SOCKET STRIP .016 X .031 TAIL  
DWG. NO.  
SSW-1XX-XX-XXX-X-XX-XXX-XX  
BY: PURVIS 06/12/1987 SHEET 3 OF 3

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for*** [Board to Board & Mezzanine Connectors](#) ***category:***

***Click to view products by*** [Samtec](#) ***manufacturer:***

Other Similar products are found below :

[10135583-642402LF](#) [89885-310LF](#) [589158040000018](#) [6-1393048-0](#) [68683-613](#) [MDF7-12DP-2.54DSA](#) [MDF7-18P-2.54DSA\(01\)](#) [MDF7-20DP-2.54DSA](#) [MDF7-26D-2.54DSA\(55\)](#) [MDF7-3P-2.54DSA\(01\)](#) [MDF7B-3P-2.54DSA\(55\)](#) [MDF7C-11P-2.54DSA\(55\)](#) [MDF7C-18P-2.54DSA\(55\)](#) [MDF7C-5P-2.54DSA\(01\)](#) [MDF7P-5P-2.54DSA\(55\)](#) [75234-0516](#) [FCN-230C068-11](#) [FCN-268F012-G/BD](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [FCN-360C008-C](#) [FCN-360C040-C](#) [FCN-723J004/1](#) [MIS-048-01-F-D-DP-K](#) [832-10-034-10-001000](#) [93696-325LF](#) [11828-1FA](#) [AXK630345P](#) [18097-0013](#) [ICA-328STT](#) [2007042-2](#) [304400-2](#) [FCN-214Q030-G/0](#) [FCN-215Q040-G/0](#) [FCN-230C068-ESA](#) [FCN-234P048-G/0](#) [FCN-235D050-G/C](#) [FCN-360A3](#) [FCN-360C040-B](#) [210-93-314-41-105000](#) [2-22603-0](#) [379-064-521-202](#) [MDF7-12P-2.54DSA\(01\)](#) [MDF7-16P-2.54DS\(56\)](#) [MDF7-40DP-2.54DSA\(55\)](#) [MDF7-8P-2.54DSA\(55\)](#) [MDF7B-16P-2.54DSA\(55\)](#) [AXG720047](#) [5031084030](#)