



## Datasheet for part number KPSE07F24-61SW

|                                         |                                                                                                |
|-----------------------------------------|------------------------------------------------------------------------------------------------|
| Our Catalog Part Number: KPSE07F24-61SW |                                                                                                |
| Brand: Cannon                           | Product Category: Circular Product Line: 26482 - Style Series I & Mil Battery Series: KPT / SE |

| Product Datasheet                      |                                                                                                                      |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Shell Style                            | Jam nut receptacle                                                                                                   |
| Endbell Style                          | Grommet seal with strain relief                                                                                      |
| Gender                                 | Socket                                                                                                               |
| Shell Size                             | 24                                                                                                                   |
| Contact Arrangement                    | 24-61                                                                                                                |
| Number of contacts                     | 61 contacts size 20                                                                                                  |
| Contact Type                           | Crimp Contacts                                                                                                       |
| Contact Plating                        | Size 12 & 16: gold plated<br>Size 20: Contact body: tin / Contact area: gold plated                                  |
| Contacts installed                     | not assembled, packed separately                                                                                     |
| Insulator Rotation                     | 90°                                                                                                                  |
| Shell Material                         | Aluminium alloy                                                                                                      |
| Shell Plating                          | Olive drab chromate over cadmium plating                                                                             |
| Insulator and Gromet Material          | Polychloroprene                                                                                                      |
| Contact Material                       | Copper alloy                                                                                                         |
| Water Tightness                        | Acc. To VG95319 Part 2, Test No. 5.9.2                                                                               |
| Operating Temperature                  | -55°/+125°C<br>(-67/257°F)                                                                                           |
| Mating Cycles                          | 500 min                                                                                                              |
| Vibration                              | 200 m/s <sup>2</sup> at 10 to 2000 Hz                                                                                |
| Contact Rating AWG20                   | 7,5 A                                                                                                                |
| Insulator Resistance                   | ≈5000 MOhm                                                                                                           |
| Test Voltage                           | 1500 Vrms                                                                                                            |
| Operating Voltage                      | In case of voltages greater than 50V the connector must be used in accordance with DIN VDE part 410, IEC 60364-4-41. |
| Safety Provisions                      | IP67 acc. to DIN 40 050<br>(0,2 bar pressure over 48 hrs)                                                            |
| General Info                           | <i>All tests in accordance with VG95319 and/or if applicable with VG95210</i>                                        |
| Harnessing Info: Contact Cross-Section | <a href="#">See assembly instruction</a>                                                                             |
| Harnessing Info: Insulator Diameter    | <a href="#">See assembly instruction</a>                                                                             |
| DISCLAIMER                             | Our facility is not currently certified by the DLA and this product is not covered by the QPL/QML.                   |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for [itt](#) manufacturer:***

Other Similar products are found below :

[BKAF3-68102-25](#) [MDM-37PCBR-F222](#) [CA3108E14S-5PBA176A232](#) [KPSE06F20-41SA206F0](#) [CB2-18-3SCA232](#) [MS3106E22-14P](#)  
[CT6E18-11SCA206](#) [CA3101E10SL-4SF80DN](#) [MS3100F14S-7S](#) [CA3101E10SL-4PBA176F42](#) [MS3101E181SW](#) [024251-0016-R](#) [024253-](#)  
[0025](#) [024265-0001](#) [024270-0015](#) [024271-0022](#) [024273-0043](#) [024288-0001](#) [M24308/24-21F](#) [M24308/24-33Z](#) [CT1F22-7SS](#) [CT2-20-23SWS](#)  
[CT2-20-23SXS](#) [CT2-36-10PCAU](#) [CT6-24-11PSA206](#) [CT6F36-10PCA152](#) [CT6F9767-14-4-14S-5PC](#) [CT6T9767-14-4-14SA7SS](#)  
[D38999/20FG16PA-LC -](#) [MD1-21PS](#) [MDM-15PH001B-A174](#) [MDM-15PH003B-A174](#) [MDM-21SCBR-A174](#) [MDM-21SCBRP-A174](#)  
[MDM-21SH003B](#) [MDM25PH003BF222](#) [MDM-31SBRP](#) [MDM-37PBRT](#) [MDM37SH004PA174](#) [MDM-37SH013P](#) [MDM-51PSF](#) [MDM-](#)  
[51SCBRPL56](#) [MDM96514-336](#) [MDM-9PCBRM7](#) [MDM-9PH006B-A174](#) [MDM9SSM5](#) [MDMV96638-13](#) [MDVB1-21SL1](#) [MEB97318-219](#)  
[MIKQ67SH019](#)