




STANDARD CIRCULAR CONNECTORS



✓ Active

TE CONNECTIVITY (TE) STRAIGHT PLUG

DEUTSCH | 38999 Series III

D38999/26ME08PN

TE Internal Number: YACT26ME08PNV00100

Mil-Spec: D38999/26ME08PN

Alias ID: ACT26ME08PN[V001]

Always EU RoHS/ELV Compliant

Product Type **Connector**

Mounting Style **Plug**

Shell Plating Material **Electroless Nickel**

Shell Material **Composite**

Polarization Code **N**

No documentation available.

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features

Product Type	Connector
Connector System	Wire-to-Wire
Shell Size	E (17)
Sealed	Yes
Connector Style	Plug
Shell Type	Plug
Assembly Type	Electrical Connector

Configuration Features

Number of Power Positions	8
Preloaded	No
Number of Positions	8
Factory Installed Backshell	No
Positions Unloaded	All
Keying	Key Polarization N
Position Keyed	N

Electrical Characteristics

Operating Voltage (VAC)	900
Operating Voltage (VDC)	1250

	Voltage (Vrms)	2300
Body Features	Shell Plating Material	Electroless Nickel
	Shell Material	Composite
	Insulation Material	Hard Dielectric/Silicone
	Hermetically Sealed	No
	Weight	20.9 g [.0461 lb]
	Fluid Type	Coolanol 25, M2-V, MIL-DTL-5624 (JP-4,JP-5), MIL-DTL-83133 (JP-8), MIL-PRF-23699, MIL-PRF-5606, MIL-PRF-7808, SEA-AMS1424 Type I
	Environmental Protection Type	Elastomer Sealed
	Environmental Protection	Yes
	Feedthrough Type	No
	Entry Style	Rear Insertion
Contact Features	Contact Layout	E08
	Contact Type	Pin
	Contact Quantity (Size 16)	8
Mechanical Attachment	Mounting Style	Plug
	Polarization Code	N
	Mating Alignment Type	Keyed
	Mating Retention	With
	Mating Retention Type	Triple Start Threaded
	Panel Mount Retention	Without
Housing Features	Alignment Keyed	Clocking
Dimensions	Accepts Wire Insulation Diameter Range	1.65 – 2.77 mm [.065 – .109 in]
	Assembly Length	31.5 mm [1.24 in]
Usage Conditions	Operating Temperature Range	-65 – 200 °C [-85 – 392 °F]
	Fluid Resistance	Yes
Operation/Application	Durability Rating (Cycles)	500
Packaging Features	Packaging Quantity	1

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Circular MIL Spec Connector](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[89075GULPR](#) [0025-262-542](#) [0025-264-3014](#) [58-570121-04S](#) [0134-213-1208](#) [0134-213-2209](#) [0025-258-000](#) [60-042022-07P](#) [60-042022-19P](#)
[60-042022-23P](#) [60-042217-10P](#) [0114-201-1278](#) [012-0467-000](#) [602GB06EG24-61SN](#) [0134-201-1207](#) [0134-213-1006](#) [6104-207-2302](#) [6104-](#)
[208-1902](#) [61-168211-04P](#) [61-168617-10P](#) [6131-202-19149P](#) [6131-204-21149P](#) [6131-208-13149P](#) [6131-209-17149P](#) [6131-210-11149P](#) [6131-](#)
[211-19149P](#) [6131-216-19149P](#) [6131-259-21149P](#) [6131-259-23149P](#) [6131-265-17149P](#) [6131-265-19149P](#) [CS3100A18-1P-472](#) [CS3100A-36-](#)
[77P](#) [CS3101A-16-55P](#) [CS3102A-10SL-55P](#) [CS3102A-14S-58P](#) [CS3102A-32-17P](#) [CS3102A32-25S](#) [CS3102C18-4P-472](#)
[CS3106A10SL3S004](#) [CS3106A-18-73S](#) [CS3108A-14S-52S](#) [CS3108A-28-51S](#) [6162-233-1277](#) [6162-324-1231](#) [M243082296Z](#)
[M2884010AC1S1](#) [CT0-24-10SC](#) [CT0M20-7PCAU](#) [M28840/17AC1G3](#)