



FEATURES

- Low Noise Output LDO: $40\mu\text{V}_{\text{RMS}}$ Possible
- 1% Initial Accuracy
- Very Low Quiecent Current: $70\mu\text{A}$
- Low Dropout Voltage (210mV at 150mA)
- Current and Thermal Limiting
- Reverse-Battery Protection
- Wide Range of Fix Output Voltages: 1.2V, 1.5V, 1.8V, 2.0V, 2.5V, 2.8V, 3.0V, 3.3V and 5.0V
- Zero Off-Mode Current
- Small 5-Pin SOT-23
- Pin Compatible to MIC5205/MAX8877 (fixed Options Only) and AS3815

Fixed Output Voltage



Adjustable Output Voltage



APPLICATIONS

- PDA
- Battery Powered Systems
- Cellular Phone
- Cordless Telephones
- Radio Control Systems
- Laptop, Palmtop, and Notebook Computers


Now Available in Lead Free Packaging

- Portable Consumer Equipment
- Portable Instrumentation
- Bar Code Scanners
- SMPS Post-Regulator

DESCRIPTION

The SPX5205 is a positive voltage regulator with very low dropout voltage, output noise and ground current ($750\mu\text{A}$ at 100mA). V_{OUT} has a tolerance of less than 1% and is temperature compensated. Fixed output voltages 1.2V, 1.5V, 1.8V, 2.0V, 2.5V, 2.8V, 3.0V, 3.3V, and 5.0V and an adjustable version are available in a small 5-pin SOT-23 package. Other key features include zero off-mode current, reverse battery protection, thermal shutdown and current limit. The SPX5205 is an excellent choice for use in battery-powered applications, and where power conservation is desired such as: cellular/ cordless telephones, radio control systems, and portable computers.

TYPICAL APPLICATION CIRCUIT



150mA, Low-Noise LDO Voltage Regulator

ABSOLUTE MAXIMUM RATINGS

Thermal Shutdown	Internally Limited	Input Supply Voltage	-20V to +20V
Lead Temperature (Soldering, 5 seconds)	260°C	Enable Input Voltage	-20V to +20V
Operating Junction Temperature Range	-40°C to +125°C		

RECOMMENDED OPERATING CONDITIONS

Input voltage	+2.5V to 16V
Operating Junction Temperature Range	-40°C to +125°C
Enable Input Voltage	0V to V _{IN}
SOT-23-5 (θ_{JA})	See Note 1

ELECTRICAL CHARACTERISTICS

T_J=25°C, V_{IN} = V_{OUT} + 1V, I_L = 100μA, C_L = 1μF, and V_{ENABLE} ≥ 2.4V. The ♦ denotes the specifications which apply over full temperature range -40°C to +85°C, unless otherwise specified.


PARAMETER	MIN	TYP	MAX	UNITS	CONDITIONS
Output Voltage Tolerance (V _{OUT})	-1 -2		+1 +2	%V _{NOM}	♦
Output Voltage Temperature Coefficient		57		ppm/°C	♦
Line Regulation		0.03	0.1 0.2	%/V	V _{IN} = V _{OUT} +1 to 16V and V _{EN} ≤ 6V ♦ V _{IN} = V _{EN} = V _{OUT} +1 ≤ 8V
			0.2	%/V	V _{IN} = V _{EN} = V _{OUT} +1 to 16V Ta = 25°C to 85°C
Load Regulation		0.1	0.2 0.5 1.0	%	V _{IN} = V _{OUT} + 1V ≥ 2.5V ♦ I _L = 1mA to 150mA ♦ I _L = 100μA to 1mA
Dropout Voltage (See Note 2) (V _{IN} - V _O)		30	50 70	mV	I _L = 100μA
		140	190 230	mV	I _L = 50mA
		180	250 300	mV	I _L = 100mA
		210	275 350	mV	I _L = 150mA
Quiescent Current (I _{GND})		0.05	1 5	μA	♦ V _{ENABLE} ≤ 0.4V V _{ENABLE} ≤ 0.25V
Ground Pin Current (I _{GND})		70	125 150	μA	I _L = 100μA
		350	600 800		I _L = 50mA
		750	1000 1500		I _L = 100mA
		1300	1900 2500		I _L = 150mA
Ripple Rejection (PSRR)		70		dB	
Current Limit (I _{LIMIT})		360	500	mA	V _{OUT} = 0V
Output Noise (e _{NO})		300		μV _{RMS}	I _L = 10mA, C _L = 1μF, C _{IN} = 1μF (10Hz - 100kHz.)
		40		μV _{RMS}	I _L = 10mA, C _L = 10μF, C _{BYP} = 1μF, C _{IN} = 1μF, (10Hz - 100kHz)
Input Voltage Level Logic Low (V _{IL})			0.4	V	OFF
Input Voltage Level Logic High (V _{IH})	2.0				ON
ENABLE Input Current		0.01 3	2 20	μA	V _{IL} ≤ 0.4V V _{IH} ≥ 2.0V

Note 1: The maximum allowable power dissipation is a function of maximum operating junction temperature, T_J (max), the junction to ambient thermal resistance, and the ambient, θ_{JA}, and the ambient temperature T_A. The maximum allowable power dissipation at any ambient temperature is given: P_D (max) = (T_J (max) - T_A)/θ_{JA}, exceeding the maximum allowable power limit will result in excessive die temperature; thus, the regulator will go into thermal shutdown. The θ_{JA} of the SPX5205 is 220°C/W mounted on a PC board.


Note 2: Not applicable to output voltages of less than 2V.

150mA, Low-Noise LDO Voltage Regulator


TYPICAL PERFORMANCE CHARACTERISTICS




Ground Current vs Load Current



Ground Current vs Input Voltage




Ground Current vs Load Current in Dropout




Output Voltage vs Input Voltage

150mA, Low-Noise LDO Voltage Regulator



TYPICAL PERFORMANCE CHARACTERISTICS



Dropout Voltage vs Load Current




Output Voltage vs Load Current


Ground Current vs Temperature at $I_{LOAD} = 100\mu A$ Ground Current vs Temperature at $I_{LOAD} = 100mA$

150mA, Low-Noise LDO Voltage Regulator


TYPICAL PERFORMANCE CHARACTERISTICS




Ground Current in Dropout vs Temperature



Output Voltage vs Temperature



ENABLE Voltage, ON threshold vs Input Voltage



Output Noise vs. Bypass Capacitor Value

APPLICATION INFORMATION

The SPX5205 requires an output capacitor for device stability. Its value depends upon the application circuit. In general, linear regulator stability decreases with higher output currents. In applications where the SPX5205 is putting out less current, a lower output capacitance may be sufficient. For example, a regulator sourcing only 10mA, requires approximately half the capacitance as the same regulator sourcing 150mA.

Bench testing is the best method for determining the proper type and value of the capacitor since the high frequency characteristics of electrolytic capacitors vary widely, depending on type and manufacturer. A high quality $2.2\mu\text{F}$ aluminum electrolytic capacitor works in most application circuits, but the same stability often can be obtained with a $1\mu\text{F}$ tantalum electrolytic.

With the SPX5205 adjustable version, the minimum value of output capacitance is a function of the output voltage. The value decreases with higher output voltages, since closed loop gain is increased.

Typical Applications Circuits

A 10nF capacitor on BYP pin will significantly reduce output noise but it may be left unconnected if the output noise is not a major concern. The SPX5205 start-up speed is inversely pro-

portional to the size of the BYP capacitor. Applications requiring a slow ramp-up of the output voltage should use a larger C_{BYP} . However, if a rapid turn-on is necessary, the BYP capacitor can be omitted.

The SPX5205's internal reference is available through the BYP pin.

The Typical Application Circuit shown on page 1 represents a SPX5205 standard application circuit. The EN (enable) pin is pulled high ($>2.0\text{V}$) to enable the regulator. To disable the regulator, $\text{EN} < 0.4\text{V}$.

The SPX5205 in Figure 1 illustrates a typical adjustable output voltage configuration. Two resistors (R_1 and R_2) set the output voltage. The output voltage is calculated using the formula:

$$V_{OUT} = 1.235\text{V} \times (1 + R_1/R_2)$$

R_2 must be $> 10\text{k}\Omega$ and for best results, R_2 should be between $22\text{k}\Omega$ and $47\text{k}\Omega$. A capacitor placed between adjustable and ground will provide improved noise performance.





Figure 1. Typical Adjustable Output Voltage.

150mA, Low-Noise LDO Voltage Regulator



ORDERING INFORMATION

PART NUMBER	TOP MARK	ACC.	OUTPUT VOLTAGE	PACKAGE
SPX5205M5-L.....	H1WW	1%	Adj	5 Pin SOT-23
SPX5205M5-L/TR	H1WW	1%	Adj	5 Pin SOT-23
SPX5205M5-L-1-2	R12	1%	1.2V	5 Pin SOT-23
SPX5205M5-L-1-2/TR	R12	1%	1.2V	5 Pin SOT-23
SPX5205M5-L-1-5	R15	1%	1.5V	5 Pin SOT-23
SPX5205M5-L-1-5/TR	R15	1%	1.5V	5 Pin SOT-23
SPX5205M5-L-1-8	R18	1%	1.8V	5 Pin SOT-23
SPX5205M5-L-1-8/TR	R18	1%	1.8V	5 Pin SOT-23
SPX5205M5-L-2-0	R20	1%	2.0V	5 Pin SOT-23
SPX5205M5-L-2-0/TR	R20	1%	2.0V	5 Pin SOT-23
SPX5205M5-L-2-5	R25	1%	2.5V	5 Pin SOT-23
SPX5205M5-L-2-5/TR	R25	1%	2.5V	5 Pin SOT-23
SPX5205M5-L-2-8	R28	1%	2.8V	5 Pin SOT-23
SPX5205M5-L-2-8/TR	R28	1%	2.8V	5 Pin SOT-23
SPX5205M5-L-3-0.....	R30	1%	3.0V	5 PIN SOT-23
SPX5205M5-L-3-0/TR	R30	1%	3.0V	5 PIN SOT-23
SPX5205M5-L-3-3	R33	1%	3.3V	5 Pin SOT-23
SPX5205M5-L-3-3/TR	R33	1%	3.3V	5 Pin SOT-23
SPX5205M5-L-5-0	R50	1%	5.0V	5 Pin SOT-23
SPX5205M5-L-5-0/TR	R50	1%	5.0V	5 Pin SOT-23

All Packaging is lead free. A bar is added to indicate lead-free parts and can be mistaken as a "1" or an "I".

/TR = Tape and Reel. Pack quantity is 2,500 for 5pin SOT-23

For further assistance:

Email: customersupport@exar.com
 EXAR Technical Documentation: <http://www.exar.com/TechDoc/default.aspx?>



Exar Corporation
Headquarters and
Sales Office
 48720 Kato Road
 Fremont, CA 94538
 main: 510-668-7000
 fax: 510-668-7030

EXAR Corporation reserves the right to make changes to the products contained in this publication in order to improve design, performance or reliability. EXAR Corporation assumes no responsibility for the use of any circuits described herein, conveys no license under any patent or other right, and makes no representation that the circuits are free of patent infringement. Charts and schedules contained here in are only for illustration purposes and may vary depending upon a user's specific application. While the information in this publication has been carefully checked; no responsibility, however, is assumed for inaccuracies.

EXAR Corporation does not recommend the use of any of its products in life support applications where the failure or malfunction of the product can reasonably be expected to cause failure of the life support system or to significantly affect its safety or effectiveness. Products are not authorized for use in such applications unless EXAR Corporation receives, in writing, assurances to its satisfaction that: (a) the risk of injury or damage has been minimized; (b) the user assumes all such risks; (c) potential liability of EXAR Corporation is adequately protected under the circumstances.