


**HER
YELLOW
GREEN**

**HLMP-M200/M201
HLMP-M300/M301
HLMP-M500/M501**


**HLMP-M250/M251
HLMP-M350/M351
HLMP-M550/M551**

PACKAGE DIMENSIONS



FEATURES

- Wide viewing angle
- Excellent for backlighting small areas
- Solid state reliability
- Choice of tinted clear or tinted diffused package



DESCRIPTION

Bright illumination and wide viewing angle are two outstanding features of the 4 mm flat top lamps. The cylindrical shape and flat emitting surface make these lamps particularly well suited for applications requiring high light output in minimal space.

NOTES: ALL DIMENSIONS ARE IN INCHES (mm).

ABSOLUTE MAXIMUM RATING (T_A = 25°C)

Parameters	HER	YELLOW	GREEN	UNITS
Power Dissipation	135	120	135	mW
Peak Forward Current (1 μS pulse width, 0.3% duty cycle)	90	60	90	mA
Reverse Voltage	5	5	5	V
Lead Soldering Time at 260° C	5	5	5	sec
Continuous Forward Current	30	20	30	mA
Operating Temperature	-55 to +100	-55 to +100	-55 to +100	°C
Storage Temperature	-55 to +100	-55 to +100	-55 to +100	°C

ELECTRICAL / OPTICAL CHARACTERISTICS (T_A =25°C)

Parameter	HER HLMP-M200/M201	YELLOW HLMP-M300/M301	GREEN HLMP-M500/M501	Condition
Luminous Intensity (mcd)				I _F = 20mA
Minimum	3.4 / 5.4	3.6 / 5.7	4.2 / 6.7	
Typical	5.0 / 7.0	5.0 / 7.0	7.0 / 10.0	
Forward Voltage (V)				I _F = 20mA
Maximum	3.0	3.0	3.0	
Typical	2.2	2.2	2.3	
Peak Wavelength (nm)	635	585	565	I _F = 20mA
Reverse Voltage (V)	5	5	5	I _R = 100μA
Viewing Angle (°)	135	135	135	I _F = 20mA

ELECTRICAL / OPTICAL CHARACTERISTICS (T_A =25°C)

Parameter	HER HLMP-M250/M251	YELLOW HLMP-M350/M351	GREEN HLMP-M550/M551	Condition
Luminous Intensity (mcd)				I _F = 10mA
Minimum	3.4 / 5.4	3.6 / 5.7	4.2 / 6.7	
Typical	5.0 / 7.0	5.0 / 7.0	10.0 / 16.0	
Forward Voltage (V)				I _F = 20mA
Maximum	3.0	3.0	3.0	
Typical	2.2	2.2	2.3	
Peak Wavelength (nm)	635	585	565	I _F = 10mA
Reverse Voltage (V)	5	5	5	I _R = 100μA
Viewing Angle (°)	80	80	80	I _F = 10mA

TYPICAL PERFORMANCE CURVES ($T_A = 25^\circ\text{C}$)




Fig. 1 Forward Current vs. Forward Voltage




Fig. 2 Relative Luminous Intensity vs. DC Forward Current




Fig. 3 Relative Intensity vs. Peak Wavelength




Fig. 4 Radiation Diagram




Fig. 5 Current Derating Curve

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.