



Heyco® PVC and Nylon LED Spacers

Fits T-1 (3 mm) HLED S2	Fits T-1 3/4 (5 mm) HLED S3	Fits T-1 (3 mm) HLED S1E	Fits T-1 3/4 (5 mm) HLED S2E
--	--	---	---

in.	A mm.	PART NO. Black PVC*	DESCRIPTION	PART NO. Black PVC	DESCRIPTION	PART NO. Natural	DESCRIPTION	PART NO. Natural	DESCRIPTION
.187	4,8			11025	HLED S3-03	11032	HLED S1E-03	11041	HLED S2E-03
.250	6,4	11019	HLED S2-04	11026	HLED S3-04	11033	HLED S1E-04	11042	HLED S2E-04
.375	9,5	11020	HLED S2-06	11027	HLED S3-06	11034	HLED S1E-06	11043	HLED S2E-06
.500	12,7	11021	HLED S2-08	11028	HLED S3-08	11035	HLED S1E-08	11044	HLED S2E-08
.625	15,9	11022	HLED S2-10	11029	HLED S3-10	11036	HLED S1E-10	11045	HLED S2E-10
.750	19,1	11023	HLED S2-12	11030	HLED S3-12	11037	HLED S1E-12	11046	HLED S2E-12
.875	22,2					11038	HLED S1E-14	11047	HLED S2E-14
1.000	25,4					11039	HLED S1E-16	11048	HLED S2E-16

Standard as color noted.

*V-0 material available, consult Heyco.

For Heyco PCB Surface Mount Miniature Connectors for LED PCB's, contact Heyco.

Heyco® Transistor Insulators



PART NO. Black	DESCRIPTION	PART NO. Black	DESCRIPTION	PART NO. Black	DESCRIPTION
12015	IEC-220-18 GF	12016	IEC-220V-18 GF	12017	IEC-218-18 GF

Material	HLED S2 PVC	HLED S3 PVC	HLED S1E & HLED S2E Nylon 6/6	Transistor Insulators Nylon Glass-filled 6/6
Flammability Rating	94HB	94HB	94V-2	94HB
Temperature Range	32°F (0°C) to 185°F (85°C) (All)	see HLED S2	see HLED S2	-22°F (-30°C) to 284°F (140°C)