

HEYCO



Heyco® Open/Closed Bushings

Mounting Hole Diameter Range: .375" (9,5 mm) to 2.500" (63,5 mm)

MOUNTING HOLE DIAMETER		PART NO.	DESCRIPTION	PART DIMENSIONS					
				A Inside Diameter		B Head Diameter		C Overall Height	
in.	mm.	Black		in.	mm.	in.	mm.	in.	mm.

Multiple Locking Steps for Panel Thickness up to .125" (3,2 mm)



	.375	9,5	2865	OCB 375	.27	6,7	.42	10,7	.39	9,9
	.437	11,1	2867	OCB 437	.33	8,4	.50	12,7		
	.500	12,7	2871	OCB 500	.31	7,9	.56	14,3		
NEW!	.512	13,0	2875	OCB 512	.35	9,0	.59	14,9		
	.562	14,3	2869	OCB 562	.39	9,9	.64	16,3		
	.625	15,9	2872	OCB 625	.45	11,1	.69	17,5		
NEW!	.650	16,5	2914	OCB 650	.48	12,3	.73	18,6		
	.750	19,1	2873	OCB 750	.55	12,7	.78	19,8		
NEW!	.866	22,0	2917	OCB 866	.68	17,3	.98	24,8	.41	10,3
	.875	22,2	2874	OCB 875	.67	14,3	.92	23,4		
NEW!	.984	25,0	2920	OCB 984	.80	20,4	1.04	26,4		
	1.000	25,4	2878	OCB 1000	.81	19,1	1.05	26,6		
	1.093	27,8	2879	OCB 1093	.88	20,6	1.16	29,4		
	1.250	31,8	2881	OCB 1250	1.05	25,8	1.34	34,1		
	1.375	34,9	2882	OCB 1375	1.17	25,4	1.47	37,3		
	1.500	38,1	2883	OCB 1500	1.25	26,9	1.58	40,1	.42	10,7
	2.000	50,8	2900	OCB 2000	1.73	43,9	2.12	53,9		

Multiple Locking Steps for Panel Thickness up to .250" (6,4 mm)

2.500	63,5	2909	OCB 2.5	2.00	50,8	2.60	66,0	.72	18,3
-------	------	-------------	---------	------	------	------	------	-----	------

Standard color black. Consult Heyco for white and other colors.

- **Split design allows side entry** and encirclement of preassembled harnesses, capillary tubes, computer cables, power cords, or other assemblies that have segments larger than the bushing's I.D.
- May also be assembled into holes that already contain cable, wire or other filaments.
- Fingertip pressure snap-locks the bushing into its mounting hole.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Multiple sizes for use in mounting holes from .375" (9,5 mm) to 2.500" (63,5 mm).



ALL NEW PRODUCTS!

Heyco® Open/Closed Shorty Bushings

Single Locking Step for Panel Thickness up to .062" (1,6 mm)

Mounting Hole Diameter Range: 7,0 mm (.276") 27,0 mm (1.063")

MOUNTING HOLE DIAMETER		PART NO.	DESCRIPTION	PART DIMENSIONS					
				A Inside Diameter		B Head Diameter		C Overall Height	
in.	mm.	Black		in.	mm.	in.	mm.	in.	mm.
.276	7,0	2934	SOCB 07M	.22	5,6	.35	8,9	.24	6,0
.512	13,0	2938	SOCB 13M	.38	9,7	.56	14,2		
.630	16,0	2941	SOCB 16M	.52	13,2	.71	18,0		
.748	19,0	2943	SOCB 19M	.63	16,0	.83	21,1	.25	6,4
.866	22,0	2945	SOCB 22M	.75	19,1	.98	24,9		
.945	24,0	2947	SOCB 24M	.82	20,8	1.06	26,9		
1.063	27,0	2950	SOCB 27M	.95	24,8	1.13	28,7	.26	6,5

Standard color black. Consult Heyco for white and other colors.

- **For use in panels .062" (1,6 mm) and thinner.**
- Lower overall height protrudes less through thin mounting panels; thus Shorty Open/Closed Bushings occupy less "real estate" inside your application.
- **Split design allows side entry** and encirclement of preassembled harnesses, power cords, capillary tubes or other assemblies that have segments larger than the bushing's ID.
- May also be assembled into holes that already contain cable, wire or other filaments.
- Fingertip pressure snap-locks the bushing into its mounting hole.

Material	Nylon 6/6
Certifications	Recognized under the Component Program of Underwriters' Laboratories File E15331 Certified by the Canadian Standards Association File 8919
Flammability Rating	94V-2
Temperature Range	-4°F (-18°C) to 221°F (105°C)