



Heyco® Nylon Male/Female Threaded Hex Supports




4-40 x .187" MALE /
4-40 x .187" FEMALE
1/4" ACROSS FLATS

MFS4




6-32 x .250" MALE /
6-32 x .250" FEMALE
1/4" ACROSS FLATS

MFS6



8-32 x .375" MALE /
8-32 x .375" FEMALE
1/4" ACROSS FLATS

MFS8



M3 x 8,0 mm MALE /
M3 x 8,0 mm FEMALE
5,0 mm ACROSS FLATS

MFSM3

	Thread Length		Mounting Hole Diameter		Thread Length		Mounting Hole Diameter		Thread Length		Mounting Hole Diameter		Thread Length		Mounting Hole Diameter	
	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.
Male end	.187	4,8	4-40		.250	6,4	6-32		.375	9,5	8-32				8,0	.315
Female end	.187	4,8	4-40		.250	6,4	6-32		.375	9,5	8-32				8,0	.315
	A	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	A	PART NO.	DESCRIPTION	A	PART NO.	DESCRIPTION	
in.	mm.	Natural		Natural		Natural		Natural		mm.	in.		mm.	in.		
.250	6,4	11800	MFS4-04	11820	MFS6-04 †	11840	MFS8-04 †			10,0	.394	11860	MFSM3-M10			
.276	7,0	11801	MFS4-04.4							12,0	.472	11861	MFSM3-M12			
.312	7,9	11802	MFS4-05*	11822	MFS6-05*					15,0	.590	11862	MFSM3-M15			
.375	9,5	11803	MFS4-06	11823	MFS6-06	11843	MFS8-06 ††			18,0	.709	11863	MFSM3-M18			
.437	11,1	11804	MFS4-07	11824	MFS6-07	11844	MFS8-07			20,0	.787	11864	MFSM3-M20			
.500	12,7	11805	MFS4-08	11825	MFS6-08	11845	MFS8-08			25,0	.984	11865	MFSM3-M25			
.562	14,3	11806	MFS4-09	11826	MFS6-09	11846	MFS8-09									
.600	15,2	11807	MFS4-09.6													
.625	15,9	11808	MFS4-10	11828	MFS6-10	11848	MFS8-10									
.687	17,4			11829	MFS6-11*											
.750	19,1	11810	MFS4-12	11830	MFS6-12	11850	MFS8-12									
.875	22,2	11811	MFS4-14	11831	MFS6-14	11851	MFS8-14									
.937	23,8			11832	MFS6-15											
1.000	25,4	11813	MFS4-16	11833	MFS6-16	11853	MFS8-16									
1.125	28,6	11814	MFS4-18	11834	MFS6-18	11854	MFS8-18									
1.250	31,8	11815	MFS4-20	11835	MFS6-20	11855	MFS8-20									
1.312	33,3			11836	MFS6-21											
1.375	34,9	11817	MFS4-22	11837	MFS6-22	11857	MFS8-22									
2.000	50,8	11818	MFS4-32	11838	MFS6-32	11858	MFS8-32									

Standard color natural.

† Female thread depth is .190" (4,8 mm)

†† Female thread depth is .200" (5,1 mm)

* Special order.

*Quick
Specs*

Material Nylon 6/6
Flammability Rating 94V-2
Temperature Range -40°F (-40°C) to 185°F (85°C)