# A7BS/A7BL

CSM\_A7BS/A7BL\_DS\_E\_6\_1

## Wide Range of Locking-type **Models Available**

- Character height of 4.8 or 3.2 mm makes for easy-toview display.
- Installation is easy with snap-in mounting.
- The series includes a complete range of locking-type models that prevent accidental operation.



### **Ordering Information**

### **Switches (Single Switch Units)**

Model	A7	BS	A7BS-	-20□-S			
	Snap-in (fro	nt mounting)	Snap-in (front mounting)				
Classification (See note 1.)			With external stopped				
Character height	Decimal: 4.8 mm He	exadecimal: 3.2 mm	m 4.8 mm				
Terminals		Solder te	erminals *1 Light gray Black				
Color	Light gray	Black	Light gray	Black			
Output code number	With external stoppers  ter height Decimal: 4.8 mm Hexadecimal: 3.2 mm						
06 (binary coded decimal)	A7BS-206 *2	A7BS-206-1 *2	A7BS-206-S	A7BS-206-S-1			
07 (binary coded decimal, with component adding provision) *3	A7BS-207 *2	A7BS-207-1 *2	A7BS-207-S	A7BS-207-S-1			
19 (decimal code, with component-adding provision)	A7BS-219	A7BS-219-1					
54 (binary coded hexadecimal)	A7BS-254	A7BS-254-1					
55 (binary coded hexadecimal, with component-adding provision) *3	A7BS-255	A7BS-255-1					

Model	A7	BL			
	Snap-in (fro	nt mounting)			
Classification (See note 1.)					
Character height	4.8	mm			
Terminals	Solder terminals *1				
Color	Light gray	Black			
Output code number	Мо	del			
06 (binary coded decimal)	A7BL-206 *2	A7BL-206-1 *2			
07 (binary coded decimal, with component-adding provision) *3	A7BL-207 *2 A7BL-207-1 *				

- Note: 1. The classification diagrams show 4 Switch Units combined with End Caps to create 4-digit displays.
- 2. The model numbers given above are for Switch Units.

  3. Models with +, displays can also be produced. Add "-PM" (+/- alternating display) or "-MP" (-/+ alternating display) after the "206" or "207" in the model number (e.g., A7BS-206-PM, A7BS-207-PM-1, or A7BS-206-MP). There is no "-MP" type available, however, for A7BS-20□-S models.

  \*1. For models with PCB terminals, add "-P2" to the model number (e.g., A7BS-
- 207-P2-1).
- \*2. Models with internal stoppers are also available. Add "-S□□" after the "206" or "207" in the model number and specify the display range in the  $\Box\Box$ . For example, to specify the range 0 to 6, add "-S06" to the model number (e.g., A7BS-206-S06-1).
  - For structural reasons, models with stoppers cannot be manufactured for the A7BS-254 and A7BS-255.
- \*3. Models with diodes are available. Add "-D" to the model number (e.g., A7BS-207-D or A7BS-207-D-1).

### **Accessories (Order Separately)**

Use accessories, such as End Caps, Spacers, and Connectors with the Switch Units.

### **End Caps, Spare Units, and Connectors**

Accessory	Color	Light gray	Black		
End Caps (1 p	pair)	A7B-M	A7B-M-1		
Spacer		A7B-P□ (See note.)	A7B-P□-1 (See note.)		
Connectors	Solder terminals	A7E	3-C		
Connectors	PCB terminals	A7B-CP			

Note: The  $\square$  in the Spacer model number stands for a letter in the range A to U. (Refer to the table in the following explanation about Spacers.)

### **End Caps**

End Caps are used on the Switch Units at each end and allow all the Switch Units to be securely mounted to a panel. They come in pairs, one for the left and one for the right.

### **Spacers**

- Spacers are used for creating extra space or gaps between the Switch Units and have the same dimensions as the Switch Units themselves.
- There are also Spacers with engraved characters or symbols that can be used for indicating units, such as time and length. (Refer to the following table.) Consult your OMRON representative for details.

Symbol	Α	В	С	D	E	F	G
Stamp	No des- ignation	SEC	MIN	Н	g	kg	mm
Symbol	Н	J	K	L	Q	Т	U
Stamp	cm	m	°C	PCS	x 10 SEC	0	•

### **Specifications**

		3.3 to 28 VDC or 50 VAC				
Switching ca	apacity (resistive load)	1 mA to 0.1 A				
Continuous	carry current	1 A max.				
Contact resi	stance	300 mΩ max.				
Insulation	Between non-connected terminals	10 MΩ min. (at 500 VDC)				
resistance	Between terminal and non-current carrying part	1,000 MΩ min. (at 500 VDC)				
Dielectric	Between non-connected terminals	600 VAC, 50/60 Hz for 1 min				
strength	Between terminal and non-current carrying part	1,000 VAC, 50/60 Hz for 1 min				
Vibration res	sistance	10 to 55 Hz, 1.5-mm double amplitude				
Shock resist	ance	490 m/s <sup>2</sup> min.				
Durability	Mechanical	100,000 operations min.				
Durability	Electrical	50,000 operations min.				
Ambient tem	perature	Operating: -10°C to 65°C (with no icing) Storage: -20°C to 80°C				
Ambient hur	midity	Operating: 45% to 85%				
Max. operati	ng force	5.39 N max.				


**Dimensions** (Unit: mm)

5.5-

### **Switches**


### A7BS-2□□(-1) **Solder Terminals**







3.8-

-0.8 6.9 В



22 4+0.4





Note: 1. The dimensions above include both End Caps, and will increase 8 mm for each Spacer inserted.


2. Unless otherwise specified, a tolerance of ±0.4 mm applies to all dimensions. The tolerance for multiple connection is ±(number of units x 0.4) mm.

### **Thumbwheel Switches with External Stoppers:** A7BS-20□-S(-1)


- Use A7BS-S Stopper Pins to make dial display restrictions for these Switches.
- Insert the Stopper Pins in the positions required to give the desired display range. For example, for a display range of 0 to 5, insert a Stopper Pin at position 1 (see following diagram) to stop the display from going above 5 when the (+) button is pressed, and insert a Stopper Pin at position 2 to stop the display from going below 0 when the (-) button is pressed.

Refer to page 7 for details.






if the output code is 07, the dimension is 43.5.



### **Stopper Pins**





Note: 1. Two pins constitute one set.
2. The first shipment is free and is attached to the Switch.


Order the A7BS-S separately if it is required for maintenance.

A7BL-206(-1) A7BL-207(-1) Solder Terminals, **Locking Models** 










\* If the output code is 06, the dimension is 32.5; if the output code is 07, the dimension is 43.5.




Number of Switches (n)	Size A (n x 8 + 8)	Size B (n x 8 + 6)	Size C
1	16	14	14.4
2	24	22	22.4
3	32	30	30.4
4	40	38	38.4
5	48	46	46.8
6	56	54	54.8
7	64	62	62.8
8	72	70	70.8
9	80	78	78.8
10	88	86	86.8


- Note: 1. The dimensions above include both End Caps, and will increase 8 mm for each Spacer inserted.
  - 2. Unless otherwise specified, a tolerance of ±0.4 mm applies to all dimensions. The tolerance for multiple connection is ±(number of units x 0.4) mm.


3

### **Accessories (Order Separately)**

## End Caps for Push-operated Switches A7B-M(-1) Snap-in Panel Mounting








## Spacers for Push-operated Switches A7B-P□(-1) Snap-in Panel Mounting






The  $\square$  in the Spacer model number stands for a letter in the range A to U. (Refer to the table under the explanation about Spacers on page 2.)

Note: Unless otherwise indicated, dimensional tolerances for dimensions in the models above are  $\pm\,0.4$  mm.

Connectors (These devices allow Switches to be quickly removed for maintenance and inspection of connectivity, and quickly re-installed.)


### A7B-C Solder Terminals






### A7B-CP PCB Terminals





### **Inserting Connectors**

Insert Connectors with the "UP" arrow pointing up.



Note: Unless otherwise indicated, dimensional tolerances for dimensions in the models above are  $\pm\,0.4$  mm.

### **Output Codes/Terminals**


- Switches with output codes 06 or 07 both use binary coded decimal but Switches with output code 07 have a component-adding provision. Similarly, Switches with output codes 54 or 55 both use binary coded hexadecimal but Switches with output code 55 have a component-adding provision.
- How to Read Output Codes
   For example, when the dial position is "3," the common terminal C on the Switch is connected to terminals 1 and 2. When the Switch is inserted into the Connector, the common terminal C becomes connector terminal 2, and terminals 1 and 2 become connector terminals 4 and 5 respectively.

Output code number	Terminals	Output codes									
06	P=2.54  P=2.54	Model 06 07	Switch Conr		Commo minal nu C 2 1 0 1	umber	1 4 4	rmina c 2 5	omm		8 7 7
					2 3		•				
07	Twenty-eight, 8+3+3+2  Component-adding provision		Dial  4 5 6 7 8 9  Note: The solid dot ● indicates (i.e., connected to the continuous cont		5 6 7 8 9 tes that the	es that the internal s		is ON		•	•
					Terminal (	connec	cted to	o com	mon		
		Dial	0		2 3	4	5	6	7	8	9
		0	•								
	1,3	2		•	<b>D</b>						
	-0-0-9 0 B	3			•						
19	9 P=3.6 20.6	4				•					
10		5					•				
	Nineteen.	6						•			
	1-dia. holes 15 15 2.5 2.5	7							•		
		8								•	
		-	solid do	t <b>a</b> indica	tes that the	internal	ewitch	is ON	1		
	Nineteen, 1-dia. holes 15 2.5 2.5				common te			13 011			

Output code number	Terminals	Output codes							
		Model	Switch Unit or Connector	Common ter- minal number	Terr	ninals c	onnect	ed to	
	P=2.54		Switch Unit	С	1	2	4	8	
54 20.6		54	Connector	2	4	5	6	7	
	20.6	55	Connector	1	4	5	6	7	
	======================================			0					
	Fourteen, 1-dia. holes		1		•				
	<del>-1</del> 3 <del>+1-</del> 2		2			•			
			3		•	•			
			4				•		
			5		•		•		
			6		•	•	•		
		Dial		7		•	•		
			8					•	
	P=2.54			9	•			•	
	F=< 0     (0 0 0 )			A		•			
	FX (0.74)   (0.76)			B C	•	•	•		
55	5.08		D		•		•		
	0000000 0 0 C		E			•	•		
Twenty-eight, -8+3+3+3-2 Component-adding provis	1-dia. holes		F		•	•	•		
	Component-adding provision	Note: 1. T		cates that the interna					
				ne common terminal					

### **Ordering Procedure**

Place orders as shown in the example below, specifying the model and number. Standard products are not factory-assembled for shipment. Contact your OMRON representative for details on ordering factory-assembled sets.



1. A7BS-206 (Switch Unit): 2 pieces

2. A7BS-207 (Switch Unit): 2 pieces

A7B-PA (Spacer): 1 piece
 A7B-M (End Caps): 1 pair

### **Safety Precautions**

Refer to Precautions for Correct Use on page in the Technical Guide for Thumbwheel Switches.

### **Precautions for Correct Use**


### Handling

- The molded components of the Switch use polyacetal resin and ABS resin. It is recommended that alcohol is used to wipe off dirt and smudges from the molded components. Take care to prevent the alcohol from getting inside.
- A7BS/A7BL Thumbwheel Switches are not drip-proof. Do not use them in areas subject to water or oil.
- Do not allow solder flux or alcohol to enter the Switch.

## Setting Numbers Locking Type




- Set with the setting button by raising it.
- Return the button to its original position after setting. It is then locked to prevent rotation, and the set numbers will not change accidentally.
- To separate the Switches, use a flat-blade screwdriver as shown in the following figure to release the hooks on the top and bottom and then separate the Switches. Be careful not to bend the hooks.



### Models with External Stoppers (A7BS-20□-S)

With the A7BS-20□-S, any range can be set externally using the Stopper Pin. Insert the Stopper Pin using the following procedure:



Example: To Display the Range 0 to 7

- Any number within the range of (0 to 7) can be chosen to limit the numbers displayed in the display window. (In this example, 8 and 9 are outside of this range.)
- First, insert the Stopper Pin in the hole in front of the lower limit ("0") for the number to be defined.
- Next, inset the Stopper Pin in the hole past the upper limit ("7") for the number to be defined. (The Stopper Pins then surround the exact range to be defined.)
- Confirm that the (+) push-button can no longer be pushed after reaching the upper limit of ("7").
- Confirm that the (-) push-button can no longer be pushed after reaching the lower limit of ("0"). This completes the setting.



### Terms and Conditions Agreement

#### Read and understand this catalog.

Please read and understand this catalog before purchasing the products. Please consult your OMRON representative if you have any questions or comments.

### Warranties.

- (a) Exclusive Warranty. Omron's exclusive warranty is that the Products will be free from defects in materials and workmanship for a period of twelve months from the date of sale by Omron (or such other period expressed in writing by Omron). Omron disclaims all other warranties, express or implied.
- (b) Limitations. OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, ABOUT NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OF THE PRODUCTS. BUYER ACKNOWLEDGES THAT IT ALONE HAS DETERMINED THAT THE

PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE.

Omron further disclaims all warranties and responsibility of any type for claims or expenses based on infringement by the Products or otherwise of any intellectual property right. (c) Buyer Remedy. Omron's sole obligation hereunder shall be, at Omron's election, to (i) replace (in the form originally shipped with Buyer responsible for labor charges for removal or replacement thereof) the non-complying Product, (ii) repair the non-complying Product, or (iii) repay or credit Buyer an amount equal to the purchase price of the non-complying Product; provided that in no event shall Omron be responsible for warranty, repair, indemnity or any other claims or expenses regarding the Products unless Omron's analysis confirms that the Products were properly handled, stored, installed and maintained and not subject to contamination, abuse, misuse or inappropriate modification. Return of any Products by Buyer must be approved in writing by Omron before shipment. Omron Companies shall not be liable for the suitability or unsuitability or the results from the use of Products in combination with any electrical or electronic components, circuits, system assemblies or any other materials or substances or environments. Any advice, recommendations or information given orally or in writing, are not to be construed as an amendment or addition to the above warranty.

See http://www.omron.com/global/ or contact your Omron representative for published information.

### Limitation on Liability; Etc.

OMRON COMPANIES SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR PRODUCTION OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED IN CONTRACT, WARRANTY, NEGLIGENCE OR STRICT LIABILITY.

Further, in no event shall liability of Omron Companies exceed the individual price of the Product on which liability is asserted.

### Suitability of Use.

Omron Companies shall not be responsible for conformity with any standards, codes or regulations which apply to the combination of the Product in the Buyer's application or use of the Product. At Buyer's request, Omron will provide applicable third party certification documents identifying ratings and limitations of use which apply to the Product. This information by itself is not sufficient for a complete determination of the suitability of the Product in combination with the end product, machine, system, or other application or use. Buyer shall be solely responsible for determining appropriateness of the particular Product with respect to Buyer's application, product or system. Buyer shall take application responsibility in all cases.

NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY OR IN LARGE QUANTITIES WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON PRODUCT(S) IS PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.

### Programmable Products.

Omron Companies shall not be responsible for the user's programming of a programmable Product, or any consequence thereof.

#### Performance Data.

Data presented in Omron Company websites, catalogs and other materials is provided as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of Omron's test conditions, and the user must correlate it to actual application requirements. Actual performance is subject to the Omron's Warranty and Limitations of Liability.

### Change in Specifications.

Product specifications and accessories may be changed at any time based on improvements and other reasons. It is our practice to change part numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifications of the Product may be changed without any notice. When in doubt, special part numbers may be assigned to fix or establish key specifications for your application. Please consult with your Omron's representative at any time to confirm actual specifications of purchased Product.

<u>Errors and Omissions.</u> <u>Information presented by Omron Companies has been checked and is believed to be accurate; however, no responsibility is accurate.</u> assumed for clerical, typographical or proofreading errors or omissions.

2014.9

In the interest of product improvement, specifications are subject to change without notice.

