

Material	High Conductivity Seamless Copper Tube
Plating	Electro-Tin
Wire Size	350 STR/FLEX
Wire Type	Stranded Copper: Class G, H, I, K, M, Locomotive
Wire Strip Length	2-9/16 in.
Stud Size	1/2 in.
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
UL Temperature Rating	90° C
C.S.A Certified Wire Connector	Yes
Panduit Color Code on Barrel	BLUE
Panduit Die Index No. on Barrel	P76
Alternate Industry Die Index No. () on Barrel	(19)



1.54±.04

PANDUIT


350 STR/FLEX
LCCX350-12H

.63±.04

1.75±.02

.63 R Ref

.53±.02 DIA
(2) PLS



Beveled wire entry

$1.06 \pm .01$

$.84 \pm .01$

$2.50 \pm .04$

Wire inspection window

3.16 REF

$45^\circ \pm 5^\circ$

$.22 \pm .01$

5.47 REF

						 PANDUIT CORP. TINLEY PARK, ILLINOIS
						LCCX350-12H-6
00	6/03	SAC	SAC	RELEASED	10850	Copper Lug - Two-Hole, Long Flex Barrel with Window, 45° Angle Tongue
REV	DATE	BY	CHK	DESCRIPTION	ECN	SCALE N/A DRAWING NO / CAD FILE LCCX350-12H-CUST