


4

3

2


1

REVISIONS				
ZONE	ITEM	DESCRIPTION	DATE	APPROVED
—	A	CHG'D PER DCO* T-02587	W.J.	



Raychem
PART NO.
MTC100-JB2-PII-T15

DATE CODE



⑤ WEIGHT (MAX): $\frac{\text{LBS.}}{.0090}$ $\frac{\text{GRAMS}}{4.08}$

④ PIN ONE: PIN NUMBER ONE MARKED IN CONTRASTING COLOR ON INTERFACIAL SEAL.

3. WAFER: WAFER MEETS THE REQUIREMENTS OF RAYCHEM SPECIFICATION D-6012.

2. FINISH: 2-A PIN WAFER: FINISH TO BE AS MOLDED.
2-B PIN CONTACT: GOLD PLATE PER MIL-G-45204, CLASS I.
2-C CONTACT TAIL: COATED WITH SOLDER PER QQ-S-571.

1. MATERIAL: 1-A PIN WAFER: HIGH GRADE POLYARYLENE THERMO-PLASTIC.
1-B PIN CONTACT: COPPER ALLOY PER QQ-B-613 OR QQ-C-502.
1-C INTERFACIAL SEAL: SILICONE ELASTOMER PER MIL-R-25988.
1-D SOLDERPAK® TERMINATORS ASSY: REFER TO RAYCHEM DWG. CTA-0036 FOR DATA.

NOTES

If this document is printed it becomes uncontrolled.
Check with the web for latest revision.

DO NOT SCALE THIS DRAWING

SPECIFICATION CONTROL DRAWING

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES BRACKETED DIMENSIONS () ARE METRIC AND TOLERANCES ARE: .XXX: $\pm .005$ (0.13 M.M.) .XX: $\pm .02$ (0.51 M.M.) Δ: $\pm$ —	DRAWN	W.V.J.	1-15-81	Raychem RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025 TITLE KIT, 2" PIN WAFER "B" WITH SOLDERPAK® TERMINATORS, FOR ROUND WIRE (20-26 AWG), 125 °C TEMPERATURE RATING MTC 100 SERIES	
	CHECKED	JS			
	APPROVED	JS	1-22-81		
	APPROVED	JS	2-6-81		
	APPROVED			SIZE	CODE IDENT
				C	NO. 06090
				DWG. NO.	MTC100-JB2-PII-T15
				WEIGHT	Δ
				SHEET	OF 1