

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	OWN	APVD
AD	00		B2	REVISED PER ECO-11-004587	11MAR11	RK	HMR

D







FIG 1



CONTENT ARRANGEMENT



C

B










FIG 2



A

1. FOR ADDITIONAL SPECIFICATIONS SEE AMP PRODUCT SPEC 108-7519.
2. SWITCH SHOWN IN OPEN POSITION.
3. ALL CHARACTERS AND ROCKERS ARE WHITE, HOUSING IS BLACK.
4. STAMPING WILL VARY ON 2 AND 3 POSITION TOPS DUE TO SPACE RESTRICTIONS.
5. STRIPPABLE TRANSPARENT SEAL, SEE FIG 6.
6. .315 DIMENSION APPLIES AT TERMINAL TIPS. TERMINALS ARE .300+.010 / -.000 AT MOUNTING SURFACE.
7. NO POSITION MARKING.
8. NO PART NO. MARKING.
9. STRIPPABLE TAPE SEAL, SEE FIGURE 8.
10. ALL MATERIALS AND FINISHES SHALL COMPLY WITH EU DIRECTIVE 2002/95/EC OF 27JAN2003 (ROHS)
11. MATERIAL: HOUSING AND ROCKERS - POLYESTER
CONTACT & SOLDER LEAD - COPPER ALLOY
12. FINISH: CONTACT - GOLD OVER NICKEL
SOLDER LEAD - TIN OVER NICKEL
13. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

13 OBSOLETE	FIG 2	FIG 3A& 7	—	1.08	10	6-5435802-3
	FIG 1	FIG 3B	9	.88	8	3-5435802-8
	FIG 2	7 8	5	.88	8	3-5435802-0
	FIG 2	7 8	5	.48	4	2-5435802-9
	FIG 2	FIG 3A	5	1.28	12	2-5435802-2
	FIG 2			1.18	11	2-5435802-1
	FIG 2			1.08	10	2-5435802-0
	FIG 2			.98	9	1-5435802-9
	FIG 2			.78	7	1-5435802-8
	FIG 2			.68	6	1-5435802-7
13 OBSOLETE	FIG 2			.58	5	1-5435802-6
	FIG 2	8	—	.48	4	1-5435802-5
	FIG 2	FIG 3A	—	1.28	12	1-5435802-2
	FIG 1	8	—	.28	2	1-5435802-0
	FIG 2	FIG 3A	5	.88	8	5435802-9
	FIG 2			1.08	10	5435802-8
	FIG 2			.98	9	5435802-7
	FIG 2			.78	7	5435802-6
	FIG 2			.68	6	5435802-5
	FIG 2			.58	5	5435802-4
5435802-1 SHOWN	FIG 2	8	—	.48	4	5435802-3
	FIG 2	8	—	.38	3	5435802-2
	FIG 2	FIG 3A	—	.88	8	5435802-1
	HOUSING	MARKING	PROTECTIVE SEAL	A	NO OF POSN	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. TALLEY 19-9-89		 TE Connectivity				
DIMENSIONS: INCHES		CHK R. MILLER 19-9-89						
	TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD H. LEITER 19-9-89		NAME SWITCH ASSY, DIP, TYPE C, 7000 SERIES, SPST, SIDE ACTUATED —			
	0 PLC ± —		PRODUCT SPEC					
	1 PLC ± —		—					
	2 PLC ± —		APPLICATION SPEC					
	3 PLC ± .005		—		SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
	4 PLC ± —		WEIGHT —		A2	00779	C=5435802	—
	ANGLES ± —							
MATERIAL	FINISH	CUSTOMER DRAWING			SCALE	SHEET		REV
					4:1	1 of 2		B2




FIG 3A




FIG 3B





FIG 4



PROTECTIVE SEAL

FIG 6





FIG 7



PROTECTIVE SEAL




FIG 8

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. TALLEY 19-9-89	 TE Connectivity									
		CHK R. MILLER 19-9-89										
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME SWITCH ASSY, DIP, TYPE C, 7000 SERIES, SPST, SIDE ACTUATED —								
		APVD H. LEITER 19-9-89										
		PRODUCT SPEC —										
		APPLICATION SPEC —										
MATERIAL		FINISH		WEIGHT		SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO			
SEE SHEET 1		SEE SHEET 1		—		A2	00779	C-5435802	—			
CUSTOMER DRAWING						SCALE		4:1	SHEET	2 OF 2	REV	B2