








PANEL CUT OUT




2.00-3.00	19.8-0.1	13.0+0.1
1.25-2.00	19.4-0.1	13.0+0.1
0.75-1.25	19.2-0.1	13.0+0.1
PANEL THICKNESS	X	Y

SWITCH FUNCTION D1
CIRCUIT DIAGRAM




SWITCH FUNCTION D2
CIRCUIT DIAGRAM




1571079-5 SHOWN
(TWO ROCKER BUTTON POSITIONS)




LOC	DIST	REVISIONS				
AD	00	P	LTR	DESCRIPTION	DATE	DWN
				SEE SHEET 1	-	-



PANEL CUT OUT




2.00-3.00	19.8-0.1	13.0+0.1
1.25-2.00	19.4-0.1	13.0+0.1
0.75-1.25	19.2-0.1	13.0+0.1
PANEL THICKNESS	X	Y





SWITCH FUNCTION D3
CIRCUIT DIAGRAM



SWITCH FUNCTION D4
CIRCUIT DIAGRAM



SWITCH FUNCTION D5
CIRCUIT DIAGRAM



1-1571079-4 SHOWN
(THREE ROCKER BUTTON POSITIONS)

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN M.BINNER	25FEB2002	TE Connectivity		
DIMENSIONS: mm		CHK J.MOSIER	-			
		APVD -	-	NAME POWER ROCKER SWITCH, 13.0mm X 19.2mm PANEL CUT-OUT SIZE, SINGLE POLE, DOUBLE-THROW, THREE TERMINALS, NON-ILLUMINATED		
		PRODUCT SPEC	NOT APPLICABLE	SIZE A2	CAGE CODE 00779	DRAWING NO C=1571079
		APPLICATION SPEC	NOT APPLICABLE	RESTRICTED TO -		
		WEIGHT -	-	SCALE 3:1	SHEET 2 of 3	REV L1
MATERIAL		FINISH	-	CUSTOMER DRAWING		

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By -

ALL RIGHTS RESERVED.

LOCAD

DIST00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

ALCOSWITCH PART NUMBER

X₁X₂

X₃

X₄

X₅X₆

X₇X₈

X₉

X₁₀

X₁₁

X₁₂

X₁₃

X₁₄

SWITCH TYPE: X₁X₂ = PR - POWER ROCKER

NOMINAL PANEL CUT OUT SIZE: X₃ = A - 13.0x19.2

NUMBER OF POLES: X₄ = S - SINGLE

SWITCH FUNCTION: X₅X₆ = D1 - ON-ON WITH OPAQUE, SINGLE-COLOR ROCKER BUTTON
D2 - ON-(ON) WITH OPAQUE, SINGLE-COLOR ROCKER BUTTON
D3 - ON-OFF-ON WITH OPAQUE, SINGLE-COLOR ROCKER BUTTON
D4 - ON-OFF-(ON) WITH OPAQUE, SINGLE-COLOR ROCKER BUTTON
D5 - (ON)-OFF-(ON), WITH OPAQUE, SINGLE-COLOR ROCKER BUTTON

CURRENT RATING: X₇X₈ = 16 - 6

TERMINAL TYPE: X₉ = E - FASTON™ TAB
L - SOLDER LUG

FRAME COLOR: X₁₀ = B - BLACK
W - WHITE

ROCKER COLOR: X₁₁ = B - BLACK
G - GREEN
R - RED
W - WHITE

SECONDARY ROCKER COLOR: X₁₂ = Ø - NOT APPLICABLE
B - BLACK
G - GREEN
R - RED
W - WHITE

LEGEND TEXT PATTERN: X₁₃ =

Ø

D

E

F

G

K

-

=

I

||

-

o

=

I

o

||

◁

o

▷

LEGEND TEXT COLOR: X₁₄ = Ø - NOT APPLICABLE
G - GREEN
R - RED
B - BLACK
W - WHITE

1

MATERIALS:

ROCKER BUTTON & HOUSING FRAME: NYLON 66, UL 94 V-2.

TERMINAL, ACTIVE CONTACTOR: COPPER ALLOY PER ASTM B152/B152M

PLUNGER: COPPER ALLOY PER ASTM B036

PHENOLIC, UL94V1(SWITCH FUNCTION D5 ONLY)

SPRING: STEEL WIRE PER ASTM A228/A228M

CONTACT: SILVER-TIN OXIDE

2

FINISH:

TERMINAL, ACTIVE CONTACTOR: 1.0µm MIN SILVER

COPPER ALLOY PLUNGER: 3.0µm MIN NICKEL

3

ELECTRICAL SPECIFICATIONS:

CURRENT AND VOLTAGE: 6

CONTACT RESISTANCE (INITIAL): <100mΩ (5V, 1A DC)

DIELECTRIC STRENGTH (INITIAL): >1000 VAC, 1 MINUTE

INSULATION RESISTANCE (INITIAL): >100MΩ MIN (500VDC BETWEEN OPEN CONTACTS)

INRUSH CURRENT: 50A / 3msec (CAPACITIVE LOAD)

ELECTRICAL LIFE ENDURANCE: >6000 OPERATIONS, VOLTAGE DROP: <100mV

TEMPERATURE RISE AT TERMINALS: <30°C, 6000 OPERATIONS (AMBIENT CONDITIONS: 25±2°C AND 65±5%R.H)

4

MECHANICAL SPECIFICATIONS:

ACTUATING FORCE: 150g MIN, 650g MAX

OPERATING LIFE ENDURANCE: >100,000 OPERATIONS

TERMINAL RETENTION STRENGTH: >2.5kg- SOLDER LUG
>6.8kg- FASTON TAB

5

ENVIRONMENTAL SPECIFICATIONS:

AMBIENT TEMPERATURE: -20°C TO +85°C

HUMIDITY: MAX 85%

SALT SPRAY: NO REMAKABLE RUST IN METAL PARTS. (5%SALT / 35°C 24HRS)

SHOCK: NO MECHANICAL DEFECT OR DAMAGE. (100g / 10MSEC/ X,Y,Z 3 TIMES)

VIBRATION: NO MECHANICAL DEFECT OR DAMAGE. (10-55Hz /1.5mm/ X,Y,Z 2HRS)

6

UL: 16A@125VAC 1⁄3HP / 10A@250VAC 1⁄2HP

ENEC: 10A 125V~, 6(3)A 250V~, µ25T85

7

ELECTRICAL RATINGS, APPROVED AGENCY LOGOS, TERMINAL IDENTIFICATION NUMBERS,MOLDED APPROXIMATELY AS SHOWN ON THE SIDE AND/OR BOTTOM SURFACE(S) OF THE SWITCH HOUSING.

8

COMPONENT RECOGNIZED TO US & CANADIAN STANDARDS, UL FILE NO. E46765.

9

COMPONENT RECOGNIZED TO EUROPEAN STANDARDS (ENEC, PENDING VDE). MARKS LICENSE No. 40006757

10

TE CONNECTIVITY LOGO LOCATED APPROXIMATELY AS SHOWN PER TEC 202-36

16.5	23.5	2	PRASD5-16F-BB0KW	1-1571079-6
16.5	23.5	2	PRASD4-16F-BB0GW	1-1571079-5
16.5	23.5	2	PRASD4-16F-BB0FW	1-1571079-4
16.5	23.5	2	PRASD4-16F-BB000	1-1571079-3
13.8	20.9	1	PRASD2-16F-BB0EW	1-1571079-2
13.8	20.9	1	PRASD2-16F-BB0DW	1-1571079-1
13.8	20.9	1	PRASD2-16F-BB000	1-1571079-0
16.5	23.5	2	PRASD3-16F-BB0GW	1571079-9
16.5	23.5	2	PRASD3-16F-BB0FW	1571079-8
16.5	23.5	2	PRASD3-16F-BB000	1571079-7
13.8	20.9	1	PRASD1-16F-BB0EW	1571079-6
13.8	20.9	1	PRASD1-16F-BB0DW	1571079-5
13.8	20.9	1	PRASD1-16F-BB000	1571079-4
B	A	SHEET REF.	ALCOSWITCH PART NUMBER	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm

0 PLC ± -

1 PLC ± 0.30

2 PLC ± 0.05

3 PLC ± -

4 PLC ± -

ANGLES ± -

FINISH

TOLERANCES UNLESS OTHERWISE SPECIFIED:

DWN M.BINNER

CHK J.MOSIER

APVD -

PRODUCT SPEC NOT APPLICABLE

APPLICATION SPEC NOT APPLICABLE

WEIGHT -

CUSTOMER DRAWING

25FEB2002

TE Connectivity

POWER ROCKER SWITCH, 13.0mm X 19.2mm

PANEL CUT-OUT SIZE, SINGLE POLE, DOUBLE-THROW, THREE TERMINALS, NON-ILLUMINATED

SIZE A2

CAGE CODE 00779

DRAWING NO C=1571079

RESTRICTED TO -

SCALE 3:1

SHEET 3 OF 3

REV L1

1471-9 (3/11)

1571079