

PRODUCT-DETAILS

E 91/20

E 91/20 Fuse switch disconnecter



General Information

Extended Product Type	E 91/20
Product ID	2CSM200983R1801
EAN	8012542009832
Catalog Description	E 91/20 Fuse switch disconnecter
Long Description	E 91/20 is a fuseholder for overcurrent and short circuit protection. No blown fuse indicator.

Technical

Standards	IEC 60947-3
Rated Voltage (U_r)	acc. To IEC 400 V
Rated Operational Voltage	AC-20B 690 V AC-22B 400 V
Rated Insulation Voltage (U_i)	1 kV
Rated Frequency (f)	50/60 Hz
Power Loss	at Rated Operating Conditions per Pole 2.5 W
Number of Poles	1
Number of Protected Poles	1
Tightening Torque	2...2.5 N·m
Utilization Category	Connecting and disconnecting under no-load conditions - occasional actuation (AC-20B) Switching of mixed resistive and inductive loads, including moderate

overloads - occasional actuation (AC-22B)

Lock Type	Padlockable when open
Mounting Type	DIN-Rail
Sealing Type	Sealing Wire
Material of Conductor	Copper
Options Provided	No
Recommended Screw Driver	Pozidriv 2
Shock and Vibration Withstand acc. to IEC 61373	Category 1, Class B
Connecting Capacity	Rigid 1.5-25 mm ² Stranded 1.5-16 mm ²
Fuse Size	8.5x31.5 mm max. 90% with temp. +20 °C 50% with max. temp. +40 °C
Rated Operational Current AC (I _e)	20 A

Environmental

Ambient Air Temperature	Operation -5...+40 °C Storage -25...+70 °C
Degree of Protection	IP20
Maximum Operating Altitude Permissible	2000 m
Resistance to Vibrations acc. to IEC 60068-2-6	2 to 13 Hz x= 1 mm peak 13 to 100 Hz y= 0.7 g peak
Resistance to Shock acc. to IEC 60068-2-27	15g 18 shocks 13 ms
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Information	9AKK106713A5623
REACH Declaration	9AKK108467A9482
Environmental Information	See RoHS Information
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Technical UL/CSA

Connecting Capacity UL/CSA	Rigid 16-10 AWG Stranded 16-3 AWG
----------------------------	--------------------------------------

Dimensions

Width in Number of Modular Spacings	1
Product Net Width	0.018 m
Product Net Height	0.085 m
Product Net Depth / Length	0.064 m
Product Net Weight	0.061 kg
Built-In Depth (t ₂)	64 mm

Ordering

Minimum Order Quantity	1 piece
Package Level 1 Units	box 6 piece
Package Level 1 Gross Weight	0.369 kg

Certificates and Declarations

BV Certificate	9AKK108467A0330
CCC Certificate	9AKK108467A0340
Certification Agency	IMQ, BV, Korean register, CCC, EAC
Declaration of Conformity - CE	9AKK106713A5623
EAC Certificate	9AKK107992A1034
IMQ Certificate	9AKK108467A0323
KRS Certificate	9AKK108467A0337
LR Certificate	9AKK107991A7313

Installation

Instructions and Manuals	No document needed
--------------------------	--------------------

Popular Downloads

Data Sheet, Technical Information	2CSC444002B0204
-----------------------------------	-----------------

Classifications

ETIM 8	EC002705 - Holder for cylindrical fuse
ETIM 9	EC002705 - Holder for cylindrical fuse
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85361050
eClass	V11.0 : 27142121
Object Classification Code	F

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CSM257573R1801	E 9F8 GG1 Fuse link	E 9F8 GG1	1	piece
2CSM256393R1801	E 9F8 GG2 Fuse link	E 9F8 GG2	1	piece
2CSM258663R1801	E 9F8 GG4 Fuse link	E 9F8 GG4	1	piece
2CSM257483R1801	E 9F8 GG6 Fuse link	E 9F8 GG6	1	piece
2CSM256303R1801	E 9F8 GG8 Fuse link	E 9F8 GG8	1	piece
2CSM277573R1801	E 9F8 GG10 Fuse link	E 9F8 GG10	1	piece
2CSM277353R1801	E 9F8 GG12 Fuse link	E 9F8 GG12	1	piece
2CSM277133R1801	E 9F8 GG16 Fuse link	E 9F8 GG16	1	piece
2CSM277503R1801	E 9F8 GG20 Fuse link	E 9F8 GG20	1	piece
2CSM277283R1801	E 9F8 AM1 Fuse link	E 9F8 AM1	1	piece
2CSM277063R1801	E 9F8 AM2 Fuse link	E 9F8 AM2	1	piece
2CSM258743R1801	E 9F8 AM4 Fuse link	E 9F8 AM4	1	piece
2CSM257563R1801	E 9F8 AM6 Fuse link	E 9F8 AM6	1	piece
2CSM256383R1801	E 9F8 AM8 Fuse link	E 9F8 AM8	1	piece
2CSM258653R1801	E 9F8 AM10 Fuse link	E 9F8 AM10	1	piece

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Cylindrical Fuse Holders and Fuse Switch Disconnectors



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [ABB manufacturer:](#)

Other Similar products are found below :

[F202AC-63/0.03](#) [F204AC-40/0.1](#) [GJL1211501R8000](#) [AF140-30-00-13](#) [AF460-30-11-68](#) [MS116-0.4](#) [B14-14](#) [EF45-30](#) [B6S-30-01-1.7](#)
[1SAM350000R1015](#) [1SAZ711201R1045](#) [1SAZ721201R1008](#) [1SDA057197R1](#) [1SFA611143R1101](#) [1SFA611143R1103](#) [1SFA611143R1108](#)
[1SFA611205R1103](#) [1SFA611212R1103](#) [1SFA611215R1001](#) [1SFA611217R1007](#) [1SFA611302R1006](#) [1SFA611605R1110](#) [OHB95L10](#)
[OVR1N160277PS](#) [KT3LD](#) [S201-B16](#) [2CCA703155R0001](#) [2CDD281101R0063](#) [2CDD283101R0063](#) [1SAM350000R1001](#)
[1SAM350000R1004](#) [1SAZ711201R1033](#) [1SFA611213R1103](#) [1SLM004102A1104](#) [1SLM004102A1108](#) [1SVR730885R3300](#) [CEPY1-1001](#)
[2CCA703250R0001](#) [2CSF202001R3630](#) [2CSF202001R4630](#) [RB14-38](#) [M2SS5-10B](#) [TA110DU90](#) [TF42-2.3](#) [MCBH-00](#) [TV10-8F](#) [3304M](#)
[KC6-31Z-01](#) [L-10-50R-9-C](#) [DF3416FRAB0](#)