

AANI-AP-0200

Request Samples



Check Inventory



18 x 18 x 6.6 mm
RoHS Compliant
MSL Level = N/A


Features

- Full-Constellation Active GNSS Antenna
- Low Profile with Size 18 x 18 x 6.6 mm
- LNA Gain: 15 ± 3 dB
- Pre-Filtering for Enhanced Anti-Jamming Performance
- Low Current Consumption: 5 ± 3 mA
- Custom Cable & Connector Options Available


Applications

- Asset Tracking
- Fleet Management
- Micro-Mobility Solutions
- UAVs, Robotics & Autonomous Vehicles
- Precision GNSS Positioning
- Mission-Critical GNSS Timing
- Geofencing

Product Image



Full-Constellation Internal Active GNSS L1 Patch Antenna



AANI-AP-0200

Request Samples




Check Inventory



18 x 18 x 6.6 mm
RoHS Compliant
MSL Level = N/A

GNSS Frequency Bands Covered

	L1 1575.42MHz	L2 1227.6MHz	L5 1176.45MHz	
GPS	■	□	□	
GLONASS	■	□	□	
Galileo	■	□	□	□
BeiDou	□	□	□	
QZSS	■	□	□	□
IRNSS/NAVIC			□	
SBAS	■		□	




Frequency allocation: GNSS systems, upper L bands and lower L bands



12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
 Cave, TX 78738
 Phone: 512-371-6159 | Fax: 512-351-8858
 For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 09-02-25

ABRACON IS
 ISO9001-2015
 CERTIFIED



AANI-AP-0200

Request Samples



Check Inventory




18 x 18 x 6.6 mm
RoHS Compliant
MSL Level = N/A

Electrical Specification

Parameters		Min.	Typ.	Max.	Units	Note
Antenna						
Frequency		GPS: L1 GLONASS: G1 GALILEO: E1 QZSS: L1 SBAS: L1				
VSWR		≤ 2			-	
Polarization		RHCP			-	(Right Hand Circular Polarization)
Nominal Impedance		50			Ω	
Peak Gain (RHCP)		0.16	0.8	2.1	dBic	On 70 × 70 mm ground plane
Efficiency		58.3	58.9	78.1	%	
LNA						
VSWR		≤ 2.0			-	
DC Input		1.8		5.0	V	
Gain		15 ± 3			dB	
Noise Figure		≤ 2.6			dB	
Out of Band Attenuation	10-840 MHz	> 50			dB	
	840-1500 MHz	> 60				
	1700-2000 MHz	> 50				
	2000-3000 MHz	> 50				
Current Consumption		5 ± 3			mA	

Please note: All measurement data is based on the standard configuration (conducted in free space unless otherwise specified).

**AANI-AP-0200**

Request Samples



Check Inventory

**18 x 18 x 6.6 mm**
RoHS Compliant
MSL Level = N/A

Mechanical Specification


Parameter	Specification
Antenna Dimension	18 x 18 x 6.6 mm
Mounting Type	Adhesive Mount
RF Connector ⁽¹⁾	u.FL/IPEX-1/MHF1
Cable Length ⁽¹⁾	Ø 1.13mm x 100 mm

(1): Fully customizable RF Cable & Connector

Environmental Specification

Parameter	Specification
Operating Temperature	-40°C to +85°C
Storage Temperature	-40°C to +85°C
RoHS Compliance	Yes
ESD Sensitive	No
Relative Humidity	Up to 95%

Full-Constellation Internal Active GNSS L1 Patch Antenna



AANI-AP-0200

Request Samples



Check Inventory



18 x 18 x 6.6 mm
RoHS Compliant
MSL Level = N/A

Ordering Information

Part Number	Description	Connector Option
AANI-AP-0200-1	Full-Constellation Internal Active GNSS L1 Patch Antenna with 100 mm cable & MHF1connector	u.FL/IPEX-1/MHF1
AANI-AP-0200-2	Full-Constellation Internal Active GNSS L1 Patch Antenna with 150 mm cable & MHF1connector	u.FL/IPEX-1/MHF1
AANI-AP-0200-3	Full-Constellation Internal Active GNSS L1 Patch Antenna with 60 mm cable & MHF1connector	u.FL/IPEX-1/MHF1

Note: Different cable and connector configurations that are not listed may be available upon request via [Abracon online support](#)




12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
Cave, TX 78738
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 09-02-25

ABRACON IS
ISO9001-2015
CERTIFIED

Full-Constellation Internal Active GNSS L1 Patch Antenna



AANI-AP-0200

Request Samples




Check Inventory




18 x 18 x 6.6 mm
RoHS Compliant
MSL Level = N/A

Product Dimension



PART NUMBER	CABLE LENGTH (L)	CONNECTOR
AANI-AP-0200-1	100	U.FL/IPEX-1/MHF1
AANI-AP-0200-2	150	U.FL/IPEX-1/MHF1
AANI-AP-0200-3	60	U.FL/IPEX-1/MHF1

Unit: mm



AANI-AP-0200

Request Samples




Check Inventory





18 x 18 x 6.6 mm
RoHS Compliant
MSL Level = N/A

Measurement Setup



GNSS Block Diagram





AANI-AP-0200

Request Samples






Check Inventory



18 x 18 x 6.6 mm
RoHS Compliant
MSL Level = N/A

Reflection Characteristics – Return Loss & VSWR





AANI-AP-0200

Request Samples





Check Inventory



18 x 18 x 6.6 mm
RoHS Compliant
MSL Level = N/A

Radiation Characteristics –Passive Peak Gain





AANI-AP-0200

Request Samples





Check Inventory



18 x 18 x 6.6 mm
RoHS Compliant
MSL Level = N/A

Radiation Characteristics –Passive Efficiency





AANI-AP-0200

Request Samples





Check Inventory



18 x 18 x 6.6 mm
RoHS Compliant
MSL Level = N/A

LNA Characteristics –LNA Gain





AANI-AP-0200

Request Samples






Check Inventory




18 x 18 x 6.6 mm
RoHS Compliant
MSL Level = N/A

Radiation Characteristics – 3D & 2D Pattern


1561MHz




XY plane




XZ plane



YZ plane



Full-Constellation Internal Active GNSS L1 Patch Antenna



AANI-AP-0200

Request Samples





Check Inventory




18 x 18 x 6.6 mm
RoHS Compliant
MSL Level = N/A


1575MHz




XY plane



XZ plane



YZ plane




12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
Cave, TX 78738
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 09-02-25

ABRACON IS
ISO9001-2015
CERTIFIED

Full-Constellation Internal Active GNSS L1 Patch Antenna



AANI-AP-0200

Request Samples






Check Inventory




18 x 18 x 6.6 mm
RoHS Compliant
MSL Level = N/A


1602MHz




XY plane



XZ plane



YZ plane



12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
Cave, TX 78738
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 09-02-25

ABRACON IS
ISO9001-2015
CERTIFIED

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Antennas](#) category:

Click to view products by [Abracon](#) manufacturer:

Other Similar products are found below :

[930-033-R](#) [A09-F8NF-M](#) [108-00016-050](#) [W1049B090](#) [WTL2449CQ1-FRSMM](#) [0600-00060](#) [GD53-25](#) [S9025PLSMF](#) [GPSCPMM00](#) [ANT-WP868SMA-Y](#) [CBNC58](#) [MD10-004](#) [ABFT](#) [LP800NMOW](#) [NMOQ88C](#) [NMOQB](#) [NMOQC](#) [ANT-GSMGPSPUKS](#) [60210](#) [60140](#) [ANT-8WPIG-UFL](#) [ANT-GPSPUKS](#) [A21H0](#) [29000863](#) [EXD450TN](#) [2.4GHz 2dBi-1.13-L=50mm](#) [3E0702BK-005](#) [22100003](#) [DL-T022-2.4G](#) [DL-T023-4G](#) [T1-915M](#) [DL-T021-2.4GW](#) [DL-T021-2.4G](#) [KH-IPEX-1.13](#) [BWGNSCNX16-6B1Y2L120](#) [BWGNSCNX15-15B1Y4L120](#) [DL-T023-4GW](#) [3N0401LG-021](#) [KHA\(RG1.13\)-TX90B-IPEX](#) [KHA\(RG1.13\)-TX80B-IPEX](#) [KH-137-TX90B-IPEX4](#) [KH-113-TX100B-IPEX4](#) [KH-113-TX60B-IPEX4](#) [KH-081-TX300-IPEX](#) [3K0001BK00-001](#) [3K0001BK00-002](#) [3N0401LG-038](#) [3N0401BK-049](#) [PRO-OB-440](#) [DL-F8-5G](#)