


Commercial Grade Ceramic Base SMD 2-pad Crystal

Description

The ABM10A series is an AT-Cut fundamental mode MHz quartz crystal offered in a 2.5mm x 2.0mm x 0.53mm two-pad SMD package. Tight frequency accuracy of $\pm 15\text{ppm}$ at room temperature ($+25^{\circ}\text{C}$) with frequency stability as low as $\pm 50\text{ppm}$ over operating temperature range of -40°C to $+125^{\circ}\text{C}$ is achieved in industry-standard carrier frequencies common for high-density, modem, communication, test equipment, PCMCIA, and wireless end applications.



Features

- 2.5 x 2.0 x 0.53mm package
- Suitable for RoHS compliant reflow
- Seam sealed ceramic package with metal lid assures high precision and reliability
- [REACH/RoHS II Compliant](#) | MSL Level = 1


Typical Applications

- High-density applications
- Modems, communication, and test equipment
- PCMCIA and wireless applications

Electrical Specifications





Parameters	Min.	Typ.	Max.	Units	Notes
Frequency Range	12.000		54.000	MHz	
Operation Mode	Fundamental (AT-cut)				
Operating Temperature	-40		+125	$^{\circ}\text{C}$	Option "blank"; See options
Storage Temperature	-55		+150	$^{\circ}\text{C}$	
Frequency Tolerance @ $+25^{\circ}\text{C}$	-50		+50	ppm	Option "blank"; See options
Frequency Stability over the Operating Temperature (ref. to $+25^{\circ}\text{C}$)	-100		+100	ppm	Option "blank"; See options
Equivalent series resistance (R1)			250	Ω	12.000-23.999MHz
			50		24.000-47.999MHz
			40		48.000-54.000MHz
Shunt capacitance (C0)			3.0	pF	
Load capacitance (CL)		8		pF	Option "blank"; See options
Drive Level		100	200	μW	
Aging	-3		+3	ppm	@ $25^{\circ}\text{C} \pm 3^{\circ}\text{C}$ First year
Spurious Ratio			-3	dB	F0 $\pm 500\text{kHz}$
Insulation Resistance	500			M Ω	@100Vdc $\pm 15\text{V}$

Part Identification (left blank if standard)



Mechanical Dimensions

RECOMMENDED LAND PATTERN



Dimensions: inches [mm]

Reflow Profile [JEDEC J-STD-020]




Table 1

SnPb Eutectic Process
Classification Temperatures (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2

Pb-Free Process
Classification Temperatures (T_c)


Package Thickness	Volume mm ³ <350	Volume mm ³ 350-2000	Volume mm ³ >2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 mm - 2.5 mm	260 °C	250 °C	245 °C
>2.5 mm	250 °C	245 °C	245 °C

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat / soak		
Temperature minimum (T_{smin})	100°C	150°C
Temperature maximum (T_{smax})	150°C	200°C
Time (T_{smin} to T_{smax}) (t_s)	60 - 120 sec.	60 - 120 sec.
Average ramp-up rate (T_{smax} to T_p)	3°C/sec. max	3°C/sec. max
Liquidous temperature (T_L)	183°C	217°C
Time at liquidous (t_L)	60 - 150 sec.	60 - 150 sec.
Peak package body temperature (T_p)*	see Table 1	see Table 2
Time (t_p)** within 5°C of the specified classification temperature (T_c)	20 sec.	30 sec.
Ramp-down rate (T_p to T_{smax})	6°C/sec. max	6°C/sec. max
Time 25°C to peak temperature	6 min. max	8 min. max
Reflow cycles	2 max	2 max

*Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

**Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.

Packaging



Tape Specifications (mm)							
Width	Ao	Bo	Do	D ₁ (Min)	E ₁	F	Ko
8mm	*	*	1.5+0.1/-0.0	1.0	1.75±0.1	3.5±0.05	*
Width	P ₁	P ₂	P ₀	T (Max)	T ₁ (Max)	T ₂ (Max)	W (Max)
8mm	4.0±0.1	2.0±0.05	4.0±0.1	0.6	0.1	2.5	8.3

***Note: Compliant to EIA-481**

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Crystals](#) category:

Click to view products by [Abracon](#) manufacturer:

Other Similar products are found below :

[AB-11.0592MHZ](#) [RT3215-32.768-12.5-TR](#) [LFXTAL066198Cutt](#) [LFXTAL065253Cutt](#) [LFXTAL066431Cutt](#) [XT9S20ANA14M7456](#)
[XT9SNLANA16M](#) [049LF-40-3](#) [6504-202-1501](#) [6526-202-1501](#) [ABM3B-24.000MHZ-R60-D1W-](#) [SG636PCE-20.000MC](#) [3404](#)
[CM315D32768EZFT](#) [C1E-19.200-12-1530-X-R](#) [C1E-16.000-12-1530-X-R](#) [425F35E027M0000](#) [FP0800018](#) [MS3V-T1R-32.768kHz-7pF-](#)
[20PPM-TA-QC-Au](#) [VXM7-1C1-16M000](#) [MS3V-T1R-32.768kHz-9pF-20PPM-TA-QC-Au](#) [17000](#) [17301](#) [12.87114](#) [C1E-48.000-10-1530-X-R](#)
[C3E-48.000-10-1530-X-R](#) [FC5BSHFEM25.0-T1](#) [FC5AQCCMF10.0-T1](#) [32.768K7PI/3215E](#) [FC-12M](#) [32.7680KD-A0](#) [HC-49/U-](#)
[S6144000BBKB](#) [FC3BSHHEF32.0-T3](#) [ABM3C-25.000MHZ-E4Y-T](#) [49SMLB12.0000-18HJE-E\(T\)](#) [ABM8G-12.000MHZ-D4Y-T](#) [ABM8G-](#)
[12.000MHZ-18-R80-D2Y-T](#) [FKT26EIHQ0.032768-BAG1K](#) [FC4STCBMF10.0](#) [FO3HSKDM33.333-T1](#) [MS1V-T1K-32.768kHz-9pF-20PPM-](#)
[TA-QC-Au](#) [NX8045GB-8MHZ-STD-CSF-4](#) [NX8045GB-12.000000MHZ-LN-CF-001](#) [CXA-014745-6X7X40](#) [K6A480002020](#)
[SX32Y025000FI1T](#) [SX25Y040000BF1T002](#) [SX32Y048000BA1T001](#) [3607S-32.768DT09LLL](#) [X1A000161000116](#) [049UT2-4.000F07DTJGL](#)