


460 MHz SMD SAW Filter



AFII-SW-0018

Request Samples



Check Inventory



3.8 x 3.8 x 1.5 mm
RoHS Compliant
MSL Level = 3



Features

- 3.8 x 3.8 x 1.5 mm in Size
- Low Insertion Loss: 2.0 dB
- Out-of-Band Rejection: > 25 dB
- 50 Ohms Single-Ended Input & Output
- Maximum Input Power: 20dBm
- Industrial Grade -40°C ~ +85°C

Applications

- RF Modules
- Front-End Filter for Wireless Receivers
- Public Safety & Emergency Services
- Land Mobile Radio (LMR)
- Metering (Electric, Water, and Gas)

Product Image



460 MHz SMD SAW Filter



AFII-SW-0018

Request Samples



Check Inventory



3.8 x 3.8 x 1.5 mm
RoHS Compliant
MSL Level = 3

Electrical Specification

Parameters	Minimum	Typical	Maximum	Units	Notes
Center Frequency (fc)	-	460.0	-	MHz	
VSWR	-	1.8	2.0	-	450– 470 MHz
Insertion Loss ⁽¹⁾	-	2.0	2.3	dB	450– 470 MHz
Amplitude Ripple ⁽¹⁾	-	0.5	1.0	dB _{p-p}	450– 470 MHz
Group Delay ⁽¹⁾	-	29	38	ns	450– 470 MHz
Group Delay Ripple ⁽¹⁾	-	0.8	2.6	ns	450– 470 MHz
Attenuation ⁽²⁾ (Reference level from 0 dB)	40	45	-	dB	DC ~ 390.0 MHz
	40	42	-		530.0 ~ 900.0 MHz
	30	32	-		900.0 ~ 1500.0 MHz
	20	25	-		1500.0 ~ 3000.0 MHz
Source Impedance (single ended) ⁽³⁾	-	50	-	Ω	
Load Impedance (single ended) ⁽³⁾	-	50	-	Ω	
RF Power Dissipation	-	-	20	dBm	

Notes: (1) Averaged values of linear S-Parameters at +25°C

(2) Averaged values of linear S-Parameters at +25°C

(3) A matching network is unnecessary (refer to the Measurement Circuits section).

Mechanical Specification

Parameters	Specifications
Dimension	3.8 x 3.8 x 1.5 mm
Mounting Type	Surface Mount

Environmental Specification

Parameters	Specifications
Operating Temperature Range	-40°C ~ +85°C
Storage Temperature Range	-45°C ~ +85°C
ESD (HBM)	>100 V
ESD (CDM)	>100 V
MSL level	3
RoHS Compliant	Yes




5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 03-13-25

ABRACON IS
ISO9001-2015
CERTIFIED

460 MHz SMD SAW Filter



AFII-SW-0018

Request Samples



Check Inventory



3.8 x 3.8 x 1.5 mm
RoHS Compliant
MSL Level = 3

Ordering Information

Part Number	Description
AFII-SW-0018	460 MHz SMD SAW Filter on Cut Tape
AFII-SW-0018-T	460 MHz SMD SAW Filter on Tape & Reel
AFII-SW-0018-EVB	460 MHz SMD SAW Filter Evaluation Board

Note: Other options not listed may be available upon request via [Abracon online support](#)

460 MHz SMD SAW Filter



AFII-SW-0018

Request Samples




Check Inventory




3.8 x 3.8 x 1.5 mm
RoHS Compliant
MSL Level = 3


Product Dimensions



TOP VIEW



FRONT VIEW




BOTTOM VIEW

Unit : mm

Pin No.	Description
2	Input
1,3,4,6	Ground
5	Output

460 MHz SMD SAW Filter



AFII-SW-0018

Request Samples




Check Inventory



3.8 x 3.8 x 1.5 mm
RoHS Compliant
MSL Level = 3


Recommended Land Pattern



Unit : mm

Please note: The line width should be designed to achieve a 50-ohm characteristic impedance, depending on the PCB material and thickness. For technical assistance, please contact [Abracon online support](#) through our online support platform.

460 MHz SMD SAW Filter



AFII-SW-0018

Request Samples




Check Inventory



3.8 x 3.8 x 1.5 mm
RoHS Compliant
MSL Level = 3

Measurement Circuit



Port	Matching Component
Input	R1:50Ω
Output	R2:50Ω

460 MHz SMD SAW Filter



AFII-SW-0018

Request Samples




Check Inventory




3.8 x 3.8 x 1.5 mm
RoHS Compliant
MSL Level = 3

Frequency Characteristics


S21 narrow band



S21



460 MHz SMD SAW Filter



AFII-SW-0018

Request Samples




Check Inventory




3.8 x 3.8 x 1.5 mm
RoHS Compliant
MSL Level = 3


S21 wide band



Group Delay



460 MHz SMD SAW Filter



AFII-SW-0018

Request Samples





Check Inventory




3.8 x 3.8 x 1.5 mm
RoHS Compliant
MSL Level = 3

VSWR (S11 & S22)



460 MHz SMD SAW Filter



AFII-SW-0018

Request Samples




Check Inventory




3.8 x 3.8 x 1.5 mm
RoHS Compliant
MSL Level = 3

Smith Chart (S11 & S22)

Smith chart S11 (450~470MHz)



Smith chart S22 (450~470MHz)



460 MHz SMD SAW Filter



AFII-SW-0018

Request Samples



Check Inventory



3.8 x 3.8 x 1.5 mm
RoHS Compliant
MSL Level = 3

Reflow Profile [JEDEC J-STD-020]

Solder Paste: Ag3.0/Cu0.5/Sn




Table 1

SnPb Eutectic Process Classification Temperatures (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥ 350
<2.5mm	235°C	220°C
≥ 2.5mm	220°C	220°C

Table 2

Pb-Free Process Classification Temperatures (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ 350-2000	Volume mm ³ >2000
<1.6mm	260°C	260°C	260°C
1.6mm - 2.5mm	260°C	250°C	245°C
>2.5mm	240°C	240°C	240°C

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat / soak		
Temperature minimum (T_{smin})	100°C	150°C
Temperature maximum (T_{smax})	150°C	200°C
Time (T_{smin} to T_{smax}) (t_s)	60 – 120 sec.	60 – 180 sec.
Average ramp-up rate (T_{smax} to T_p)	3°C/sec. max	3°C/sec. max
Liquidous temperature (T_L)	183°C	217°C
Time at Liquidous (T_L)	60 – 150 sec.	60 – 150 sec.
Peak package body temperature (T_p)*	See Table 1	See Table 2
Time (T_p)** within 5°C of the specified classification temperature (T_c)	20 sec.	5 sec.
Ramp-down rate (T_p to T_{smax})	6°C/sec. max	3°C/sec. max
Time 25°C to peak temperature	6 min. max	8 min. max
Reflow cycles	2 max	2 max

*Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

**Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Signal Conditioning](#) category:

Click to view products by [Abracon](#) manufacturer:

Other Similar products are found below :

[PD0409J5050S2HF](#) [AFS14A35-1591.50-T3](#) [AFS20A20-1227.60-T3](#) [JP510S](#) [LFB322G45SN1A504](#) [SF2159E](#) [MAPDCC0005](#)
[BD0810N50100AHF](#) [DC0710J5005AHF](#) [DC2327J5005AHF](#) [X3C19F1-20S](#) [XC3500P-20S](#) [CDBLB455KCAX39-B0](#) [PD0922J5050D2HF](#)
[1E1305-3](#) [1F1304-3S](#) [BD1222J50200AHF](#) [BD1722J50100AHF](#) [BD0810J50150AHF](#) [BD1722J50200AHF](#) [TP-101-PIN](#) [T-1000-N](#) [XC0900P-](#)
[10S](#) [XC0900B-30S](#) [11305-10](#) [5962-9091202MXA](#) [X3C06A4-03S](#) [DSS-333-PIN](#) [PD2425J5050S2HF](#) [B39242B4360P810](#)
[B39781B8005P810](#) [B39881B8013P810](#) [B39771B8035P810](#) [B39741B8012P810](#) [B39212B8033P810](#) [B39162B8636P810](#) [SF2225E](#) [SF2275E](#)
[SF2395E](#) [SF2188D](#) [LFB182G45BG7D948](#) [SF2201E](#) [DC1722J5005AHF](#) [B39272B8818P810](#) [SF2253E](#) [SF2202E](#) [SF2182D](#) [SF2211E](#)
[SF2240E](#) [SF2307D](#)