


SMD 1176.45 MHZ SAW Filter



AFII-SW-0074-Q

Request Samples



Check Inventory



1.4 x 1.1 x 0.6 mm
RoHS Compliant
MSL Level = 1


Features

- AEC-Q200 Qualified
- GNSS L5 Band Support
- 1.4 x 1.1 x 0.6 mm in Size
- Low Insertion Loss: 1.4 dB
- Out-of-Band Rejection: > 29 dB
- Maximum Input Power: +13 dBm
- RoHS Compliant


Applications

- RF Modules
- RTK Systems
- Automotive Transportation & Telematics
- Asset Tracking / Fleet Management
- UAVs, Robotics & Autonomous Vehicles
- Micro-Mobility Solutions

Product Image



SMD 1176.45 MHZ SAW Filter



AFII-SW-0074-Q

Request Samples



Check Inventory



1.4 x 1.1 x 0.6 mm
RoHS Compliant
MSL Level = 1

Electrical Specification

Parameters	Minimum	Typical	Maximum	Units	Notes
Center Frequency(fc)	-	1176.45	-	MHz	-
VSWR ⁽¹⁾	-	1.8	2.1	-	1166.23 ~ 1186.67MHz
Insertion Loss ⁽¹⁾	-	1.4	2.2	dB	1166.23 ~ 1186.67MHz
Amplitude Ripple ⁽¹⁾	-	0.4	1.4		1166.23 ~ 1186.67MHz
Attenuation ⁽¹⁾ (Reference level from 0 dB)	30	45	-	dB	100 ~1080 MHz
	20	29	-		1080 ~1130 MHz
	30	34	-		1230 ~2000 MHz
	25	32	-		2000 ~3000 MHz
Group Delay ⁽¹⁾ (+25 °C)	-	17	18	ns	1166.23 ~ 1186.67MHz
Group Delay Ripple ⁽¹⁾ (+25 °C)	-	4	8	ns	1166.23 ~ 1186.67MHz
Source Impedance ⁽²⁾ (single ended)	-	50	-	Ω	-
Load Impedance ⁽²⁾ (single ended)	-	50	-	Ω	-
Input Power Level	-	-	13	dBm	-
DC Voltage (V)	-	-	3	V	-
Temperature Coefficient of Frequency	-	-36	-	ppm/°C	-

Notes: (1) Averaged values of linear S-Parameters at +25°C

(2) A matching network is unnecessary (refer to the Measurement Circuits section).

Mechanical Specification

Parameters	Specifications
Filter Dimension	1.4 x 1.1 x 0.6 mm
Mounting Type	Surface Mount

Environmental Specification

Parameters	Specifications
Operating Temperature Range	-40°C ~ +105°C
Storage Temperature Range	-40°C ~ +125°C
MSL level	1
ESD	50 V (MM) 100 V (HBM)




5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 07-01-25

ABRACON IS
ISO9001-2015
CERTIFIED

SMD 1176.45 MHZ SAW Filter



AFII-SW-0074-Q

Request Samples



Check Inventory




1.4 x 1.1 x 0.6 mm
RoHS Compliant
MSL Level = 1

Ordering Information

Part Number	Description
AFII-SW-0074-Q	SMD 1176.45 MHZ SAW Filter on Cut Tape
AFII-SW-0074-Q-T	SMD 1176.45 MHZ SAW Filter on Tape & Reel
AFII-SW-0074-Q-EVB	SMD 1176.45 MHZ SAW Filter Evaluation Board

Note: Other options not listed may be available upon request via [Abracon online support](#)

SMD 1176.45 MHZ SAW Filter



AFII-SW-0074-Q

Request Samples




Check Inventory




1.4 x 1.1 x 0.6 mm
RoHS Compliant
MSL Level = 1


Product Dimensions



TOP VIEW




FRONT VIEW




BOTTOM VIEW

PIN #	SYMBOL	FUNCTION
1	IN	INPUT
2	GND	GROUND
3	GND	GROUND
4	OUT	OUTPUT
5	GND	GROUND



Unit : mm

SMD 1176.45 MHZ SAW Filter



AFII-SW-0074-Q

Request Samples




Check Inventory



1.4 x 1.1 x 0.6 mm
RoHS Compliant
MSL Level = 1

Recommended Land Pattern




 : Land Pattern

Unit : mm

Please note: The line width should be designed to achieve a 50-ohm characteristic impedance, depending on the PCB material and thickness. For technical assistance, please contact [Abracon online support](#) through our online support platform

SMD 1176.45 MHZ SAW Filter



AFII-SW-0074-Q

Request Samples




Check Inventory




1.4 x 1.1 x 0.6 mm
RoHS Compliant
MSL Level = 1

Measurement Circuit



Port	Matching Component
Input (Pin 1)	R1: 50 Ω
Output (Pin 4)	R2: 50 Ω

SMD 1176.45 MHz SAW Filter



AFII-SW-0074-Q

Request Samples





Check Inventory




1.4 x 1.1 x 0.6 mm
RoHS Compliant
MSL Level = 1

Frequency Characteristics

S21 narrow band



SMD 1176.45 MHz SAW Filter



AFII-SW-0074-Q

Request Samples




Check Inventory




1.4 x 1.1 x 0.6 mm
RoHS Compliant
MSL Level = 1


S21 Wide Band



Group Delay



SMD 1176.45 MHz SAW Filter



AFII-SW-0074-Q

Request Samples





Check Inventory




1.4 x 1.1 x 0.6 mm
RoHS Compliant
MSL Level = 1

VSWR (S11 & S22)



SMD 1176.45 MHZ SAW Filter



AFII-SW-0074-Q

Request Samples




Check Inventory




1.4 x 1.1 x 0.6 mm
RoHS Compliant
MSL Level = 1

Smith Chart (S11 & S22)


Smith chart S11 (1166~1186MHz)



Smith chart S22 (1166~1186MHz)



SMD 1176.45 MHZ SAW Filter



AFII-SW-0074-Q

Request Samples



Check Inventory



1.4 x 1.1 x 0.6 mm
RoHS Compliant
MSL Level = 1

Reflow Profile [JEDEC J-STD-020]




Table 1

SnPb Eutectic Process Classification Temperatures (T_c)

Package Thickness	Volume mm^3 <350	Volume mm^3 ≥ 350
<2.5mm	235°C	220°C
$\geq 2.5\text{mm}$	220°C	220°C

Table 2

Pb-Free Process Classification Temperatures (T_c)

Package Thickness	Volume mm^3 <350	Volume mm^3 350-2000	Volume mm^3 >2000
<1.6mm	260°C	260°C	260°C
1.6mm - 2.5mm	260°C	250°C	245°C
>2.5mm	250°C	245°C	245°C

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat / soak		
Temperature minimum (T_{smmin})	100°C	150°C
Temperature maximum (T_{smmax})	150°C	180°C
Time (T_{smmin} to T_{smmax}) (t_s)	60 – 120 sec.	60 – 90 sec.
Average ramp-up rate (T_{smmax} to T_p)	3°C/sec. max	3°C/sec. max
Liquidous temperature (T_L)	183°C	220°C
Time at Liquidous (T_L)	60 – 150 sec.	50 – 80 sec.
Peak package body temperature (T_p)*	See Table 1	See Table 2
Time (T_p)** within 5°C of the specified classification temperature (T_c)	20 sec.	20 ~ 40 sec.
Ramp-down rate (T_p to T_{smmax})	6°C/sec. max	6°C/sec. max
Time 25°C to peak temperature	6 min. max	8 min. max
Reflow cycles	2 max	2 max

*Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

**Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Signal Conditioning](#) category:

Click to view products by [Abracon](#) manufacturer:

Other Similar products are found below :

[PD0409J5050S2HF](#) [AFS14A35-1591.50-T3](#) [AFS20A20-1227.60-T3](#) [JP510S](#) [LFB322G45SN1A504](#) [SF2159E](#) [MAPDCC0005](#)
[BD0810N50100AHF](#) [DC0710J5005AHF](#) [DC2327J5005AHF](#) [X3C19F1-20S](#) [XC3500P-20S](#) [CDBLB455KCAX39-B0](#) [PD0922J5050D2HF](#)
[1E1305-3](#) [1F1304-3S](#) [BD1222J50200AHF](#) [BD1722J50100AHF](#) [BD0810J50150AHF](#) [BD1722J50200AHF](#) [TP-101-PIN](#) [T-1000-N](#) [XC0900P-](#)
[10S](#) [XC0900B-30S](#) [11305-10](#) [5962-9091202MXA](#) [X3C06A4-03S](#) [DSS-333-PIN](#) [PD2425J5050S2HF](#) [B39242B4360P810](#)
[B39781B8005P810](#) [B39881B8013P810](#) [B39771B8035P810](#) [B39741B8012P810](#) [B39212B8033P810](#) [B39162B8636P810](#) [SF2225E](#) [SF2275E](#)
[SF2395E](#) [SF2188D](#) [LFB182G45BG7D948](#) [SF2201E](#) [DC1722J5005AHF](#) [B39272B8818P810](#) [SF2253E](#) [SF2202E](#) [SF2182D](#) [SF2211E](#)
[SF2240E](#) [SF2307D](#)