

915 MHz SMD SAW Filter



AFII-SW-0087

Request Samples





Check Inventory



3.0 x 3.0 x 1.4 mm
RoHS Compliant
MSL Level = 1

Description

Designed for long-range, low-power Sub-GHz communication, this robust bandpass filter is optimized for LoRa, Sigfox, and Wi-Fi HaLow protocols. With a precise 26 MHz bandwidth, it delivers excellent out-of-band rejection greater than 28 dB to minimize interference, while maintaining a low 2.2 dB insertion loss for optimal signal strength. Housed in a compact 3.0 x 3.0 x 1.4 mm package and rated for a +15 dBm input power, this MSL Level 1 compliant filter is an ideal and reliable solution for enhancing the performance and reliability of IoT RF modules in smart metering and smart lighting networks.



Features

- Bandwidth: 26 MHz
- 3.0 x 3.0 x 1.4 mm in Size
- Insertion Loss: 2.2 dB
- Out-of-Band Rejection: > 28 dB
- Maximum Input Power: +15 dBm
- [RoHS Compliant](#) | [MSL Level 1](#)

Applications

- RF Modules
- Sub-GHz LoRa / Sigfox / Wi-Fi HaLow
- Internet of Things (IoT)
- Smart Metering
- Smart Lighting

Ordering Information

Part Number	Description
AFII-SW-0087	915 MHz SMD SAW Filter on Cut Tape
AFII-SW-0087-T	915 MHz SMD SAW Filter on Tape & Reel
AFII-SW-0087-EVB	915 MHz SMD SAW Filter Evaluation Board

Note: Other options not listed may be available upon request via [Abracon online support](#)



12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
Cave, TX 78738
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 10-24-25

ABRACON IS
ISO9001-2015
CERTIFIED

915 MHz SMD SAW Filter



AFII-SW-0087

Request Samples



Check Inventory



3.0 x 3.0 x 1.4 mm
RoHS Compliant
MSL Level = 1

Electrical Specification

Parameters	Minimum	Typical	Maximum	Units	Notes
Center Frequency (fc)	-	915	-	MHz	
Insertion Loss	-	2.2	3.5	dB	902 - 928 MHz
Amplitude Ripple	-	0.6	2.0	dB _{p-p}	902 - 928 MHz
Group Delay	-	32.5	46.2	ns	902 - 928 MHz
Group Delay Ripple	-	2.8	13.7	ns	902 - 928 MHz
Attenuation	50	63	-	dB	D.C. - 800 MHz
	40	48	-		800 - 880 MHz
	32	39	-		960 - 1080 MHz
	45	65	-		1080 - 1500 MHz
	22	28	-		1500 - 3000 MHz
VSWR	-	1.6	2.3	-	902 - 928 MHz
DC Voltage	-	-	5	V	
Input Power	-	-	15	dBm	
Source Impedance (single ended) ⁽¹⁾	-	50	-	Ω	
Load Impedance (single ended) ⁽¹⁾	-	50	-	Ω	
Temperature Coefficient of Frequency	-	-36	-	ppm/°C	

Notes: (1) A matching network is unnecessary (refer to the Measurement Circuits section).

Mechanical Specification

Parameters	Specifications
Dimension	3.0 x 3.0 x 1.4 mm
Mounting Type	Surface Mount

Environmental Specification

Parameters	Specifications
Operating Temperature Range	-40°C ~ +85°C
Storage Temperature Range	-40°C ~ +85°C
MSL level	1
ESD	N/A



12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
Cave, TX 78738
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 10-24-25

ABRACON IS
ISO9001-2015
CERTIFIED

915 MHz SMD SAW Filter



AFII-SW-0087

Request Samples





Check Inventory



3.0 x 3.0 x 1.4 mm
RoHS Compliant
MSL Level = 1

Product Dimensions



Unit : mm

Pin No.	Description
A, C, D, F	Ground
B	Input
E	Output

915 MHz SMD SAW Filter



AFII-SW-0087

Request Samples




Check Inventory



3.0 x 3.0 x 1.4 mm
RoHS Compliant
MSL Level = 1

Recommended Land Pattern



Unit: mm

Please note: The line width should be designed to achieve a 50-ohm characteristic impedance, depending on the PCB material and thickness. For technical assistance, please contact [Abracon online support](#) through our online support platform

915 MHz SMD SAW Filter



AFII-SW-0087

Request Samples




Check Inventory



3.0 x 3.0 x 1.4 mm
RoHS Compliant
MSL Level = 1

Measurement Circuit



Source & Load Impedance: 50 Ω

Pin No.	Description
B	Input Impedance: 50 Ω
E	Output Impedance: 50 Ω
A, C, D, F	Ground

915 MHz SMD SAW Filter



AFII-SW-0087

Request Samples





Check Inventory



3.0 x 3.0 x 1.4 mm
RoHS Compliant
MSL Level = 1

Frequency Characteristics

S21 narrow band



915 MHz SMD SAW Filter



AFII-SW-0087

Request Samples




Check Inventory




3.0 x 3.0 x 1.4 mm
RoHS Compliant
MSL Level = 1


S21 wide band



Group Delay



915 MHz SMD SAW Filter



AFII-SW-0087

Request Samples





Check Inventory



3.0 x 3.0 x 1.4 mm
RoHS Compliant
MSL Level = 1

VSWR (S11 & S22)



915 MHz SMD SAW Filter



AFII-SW-0087

Request Samples




Check Inventory




3.0 x 3.0 x 1.4 mm
RoHS Compliant
MSL Level = 1

Smith Chart (S11 & S22)

Smith chart S11 (902~928MHz)



Smith chart S22 (902~928MHz)



915 MHz SMD SAW Filter



AFII-SW-0087

Request Samples



Check Inventory



3.0 x 3.0 x 1.4 mm
RoHS Compliant
MSL Level = 1

Reflow Profile [JEDEC J-STD-020]

Solder paste: Sn/3.0Ag/0.5Cu




Table 1

SnPb Eutectic Process Classification Temperatures (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥ 350
<2.5mm	235°C	220°C
≥ 2.5mm	220°C	220°C

Table 2

Pb-Free Process Classification Temperatures (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ 350-2000	Volume mm ³ >2000
<1.6mm	260°C	260°C	260°C
1.6mm - 2.5mm	260°C	250°C	245°C
>2.5mm	250°C	245°C	245°C

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat / soak		
Temperature minimum (T_{smin})	100°C	150°C
Temperature maximum (T_{smax})	150°C	200°C
Time (T_{smin} to T_{smax}) (t_s)	60 – 120 sec.	60 – 90 sec.
Average ramp-up rate (T_{smax} to T_p)	3°C/sec. max	3°C/sec. max
Liquidous temperature (T_L)	183°C	217°C
Time at Liquidous (T_L)	60 – 150 sec.	60 – 150 sec.
Peak package body temperature (T_p)*	See Table 1	See Table 2
Time (T_p)** within 5°C of the specified classification temperature (T_c)	20 sec.	10 sec.
Ramp-down rate (T_p to T_{smax})	6°C/sec. max	6°C/sec. max
Time 25°C to peak temperature	6 min. max	8 min. max
Reflow cycles	2 max	2 max

*Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

**Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.



12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
Cave, TX 78738
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 10-24-25

ABRACON IS
ISO9001-2015
CERTIFIED

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Signal Conditioning](#) category:

Click to view products by [Abracon](#) manufacturer:

Other Similar products are found below :

[PD0409J5050S2HF](#) [AFS14A35-1591.50-T3](#) [AFS20A20-1227.60-T3](#) [JP510S](#) [LFB322G45SN1A504](#) [SF2159E](#) [MAPDCC0005](#)
[BD0810N50100AHF](#) [DC0710J5005AHF](#) [DC2327J5005AHF](#) [X3C19F1-20S](#) [XC3500P-20S](#) [CDBLB455KCAX39-B0](#) [PD0922J5050D2HF](#)
[1E1305-3](#) [1F1304-3S](#) [BD1222J50200AHF](#) [BD1722J50100AHF](#) [BD0810J50150AHF](#) [BD1722J50200AHF](#) [TP-101-PIN](#) [T-1000-N](#) [XC0900P-](#)
[10S](#) [XC0900B-30S](#) [11305-10](#) [5962-9091202MXA](#) [X3C06A4-03S](#) [DSS-333-PIN](#) [PD2425J5050S2HF](#) [B39242B4360P810](#)
[B39781B8005P810](#) [B39881B8013P810](#) [B39771B8035P810](#) [B39741B8012P810](#) [B39212B8033P810](#) [B39162B8636P810](#) [SF2225E](#) [SF2275E](#)
[SF2395E](#) [SF2188D](#) [LFB182G45BG7D948](#) [SF2201E](#) [DC1722J5005AHF](#) [B39272B8818P810](#) [SF2253E](#) [SF2202E](#) [SF2182D](#) [SF2211E](#)
[SF2240E](#) [SF2307D](#)