

AVR-1F070605S

Request Samples



Check Inventory



7.1 x 6.1 x 5.4 mm
RoHS/RoHS II Compliant
MSL Level = 1

Features

- Shielded construction
- Soft saturation
- High Power Density
- Low DCR, High Efficiency
- Perfect for multi-phased power circuitry

Applications

- Desktop/ Server applications
- High current point-of-load (POL) converters
- Lighting
- Solar inverters and power
- Industrial and robotics
- Medium and high-power switch mode power supplies.

Electrical Specifications

Part Number	Inductance	Tolerance	DC Resistance	Saturation Current (Typ)		Temperature Rise Current
	0.1MHz/1.0V			@25°C	@100°C	Typ.
Units	nH	%	mΩ ±30%	A		A
Symbol	L		DCR	Isat		Irms
AVR-1F070605S90NL	90	±15%	0.17	50	45	25

Test Conditions

Isat: DC current at which the inductance drops 30% from its value without current.

Irms: DC current that causes the temperature rise (ΔT , approximate 40 °C) from 20°C ambient


Operating Temperature: -45°C ~ +125°C (including self-temperature rise)


Storage Condition: -40°C ~ +125°C (with packaging) and R.H. <95% max

Operating Voltage: 40V (across inductor)

AVR-1F070605S Series is **RoHS Compliant and Pb free**

Part Identification





AVR-1F070605S

Request Samples




Check Inventory




7.1 x 6.1 x 5.4 mm
RoHS/RoHS II Compliant
MSL Level = 1

Mechanical Specifications




Dimensions: Inches [mm]

Recommended Land Pattern



Dimensions: Inches [mm]



AVR-1F070605S

Request Samples




Check Inventory



7.1 x 6.1 x 5.4 mm
RoHS/RoHS II Compliant
MSL Level = 1

Reflow Profile



Zone	Description	Temperature	Times
1	Preheat	$T_{SMIN} \sim T_{SMAX}$ 150°C ~ 200°C	60 ~ 120 sec.
2	Reflow	T_L 217°C	60 ~ 150 sec.
3	Peak heat	T_p 260°C	5 sec. MAX

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Power Inductors - SMD category](#):

Click to view products by [Abracon manufacturer](#):

Other Similar products are found below :

[LLQPB201214T1R0M](#) [LLXND3030QKT470MNG](#) [LLQPB160807T4R7M](#) [SSL1306T-101M-N](#) [CDRH8D43RT125NP-680MC](#)
[CDRH70D45BT150NP-101MC](#) [CDRH10D68RT125NP-102PC](#) [CD43NP-1R0MC](#) [CDRH60D45BT150NP-331MC](#) [CDRH104NP-221MC](#)
[CDRH5D28RBH125NP-100MC](#) [CDRH6D38T125NP-330PC](#) [CDRH60D45BT150NP-221MC](#) [CDRR126NP-331MC](#) [CDRH60D45BT150NP-4R7NC](#) [CDRH124NP-331MC](#) [DEP1016NP-330PB](#) [CDRH6D38T125NP-3R9NC](#) [CDRH127L125NP-680MC](#) [CD43T125NP-680KC](#)
[CDRR7D45T125NP-6R8MC](#) [CDRH60D45BT150NP-100MC](#) [0630CDMCDDS-R15MC](#) [CDRCH12D78BNP-220MC](#) [CD75T125NP-471KC](#)
[CD105T125NP-101KC](#) [CDRH80D65BT150NP-102MC](#) [CD75T125NP-101KC](#) [CDRH10D60BT150NP-101MC](#) [CDRH104RT125NP-6R8PC](#)
[CD105T125NP-331KC](#) [CDRH104RT125NP-221MC](#) [CDRH40D18ANP-220NC](#) [CDRH70D45BT150NP-100MC](#) [CDRH5D28RBH125NP-101MC](#) [CDRH80D65BT150NP-471MC](#) [CDRH127L125NP-102MC](#) [WLPH201610M1R0PS](#) [78438336068HT](#) [744045470](#)
[IHLP5050CEEK3R3MA1](#) [744045680](#) [744032470](#) [74437346150](#) [7687709472](#) [7687709682](#) [7687714470](#) [7687779470](#) [SRP2512CL-1R0M](#)
[AIML-0603HC-100M-T](#)