

Heat Sink for AMD Kria™ K26 SOM

ATS Part#: **ATS-KRA-3559-C1-R0**
Description: 54 x 68 x 20 mm high-performance heat sink
Component: AMD Kria™ K26 SOM
Heat Sink Type: Active straight fin heat sink
Heat Sink Attachment: Screws



Adaptive
Computing
Partner

SELECT



Images for illustration
purposes only.




Fig.2 - Measured dimensions
of fan assembly hole pattern

Product Details and Assembly

- » Designed to fit the AMD Kria™ K26 System-on-Module (SOM)
- » Included mounting hardware kit: ATS-HK544-R0
- » Heat sink mounts directly to the heat spreader plate that comes standard on the K26 SOM
- » Fan assembly hole pattern is 40.0 mm C-C (center to center) - see Fig. 2
- » Included fan attachment kit (10mm fan height): ATS-HK545-R0
- » Fan not included - ATS recommended fans listed below
- » Provided with pre-assembled Thermal Interface Material (TIM) on base

Heat Sink Part Number	L (mm)	W (mm)	H (mm)	Heat Sink Weight (g)	Thermal Interface Material
ATS-KRA-3559-C1-R0	54	68	20	63	Chomerics T766

Recommended Fans


Part Number	MFG	L (mm)	W (mm)	H (mm)	Voltage (VDC)	Air Flow (CFM)	Static Pressure (Pa)
MF50100V1-10000-A99	Sunon	50	50	10	5	13.8	37.4
MF50101V1-10000-A99	Sunon	50	50	10	12	13.8	37.4
EFB0505MA-F00	Delta	50	50	10	5	9.2	28.1
EFB0512LA	Delta	50	50	10	12	7.5	17.0

Product Details

SCHEMATIC IMAGE	Dimension A	Dimension B	Dimension C	Dimension D	Dimension E	Dimension F	Fan Assembly Hole Pattern	Material	Finish
	54 mm	68 mm	20 mm	61 mm	28.5 mm	3.4 mm	40.0 mm center-to-center	AL-6063	Black Anodized

NOTES:

- 1) Fan not included - Fan type is specific to individual customer requirements and needs to be independently sourced
- 2) Dimensions A and B refer to heat sink size
- 3) Dimension C is the heat sink height from the bottom of the base to the top of the fin field
- 4) Dimensions D and E refer to the mounting hole pattern C-C (center to center)
- 5) Dimension F refers to the mounting hole diameter
- 6) Thermal performance data are provided for reference only.
Actual performance may vary by application.
- 7) ATS reserves the right to update or change its products without notice to improve the design or performance.
- 8) ATS certifies that this heat sink assembly is RoHS-6 and REACH compliant.
- 9) Contact ATS to learn about custom options available.



*All Images are for illustration purposes only.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heat Sinks](#) category:

Click to view products by [Advanced Thermal Solutions](#) manufacturer:

Other Similar products are found below :

[630-35ABT3](#) [656-15ABPE](#) [657-20ABPNE](#) [73452PPBA](#) [231-69PAB-15V](#) [253-122ABE-22](#) [PSC22CB](#) [BDN183CBA01](#) [32438](#) [LAE66A3CB](#)
[73381PPBA](#) [73403PPBA](#) [7G0047C](#) [8191-E40](#) [D10650-40T5](#) [ATS-54310K-C2-R0](#) [657-20ABPESC](#) [2341BG](#) [679-25AG](#) [6801G](#) [680-5K](#)
[SK145 37 5STSTO220](#) [TS-11042-CY](#) [7717-133DAP](#) [7717-26DAP](#) [SK104 50 8STS](#) [SK129 25 4STS](#) [APF30-30-10CB/A01](#) [43808-04](#)
[BDN123CBA01](#) [512-9M](#) [BDN113CBA01](#) [ATS-PF1K-C1-R0](#) [40139](#) [392-180AG](#) [1963872-1](#) [MTN-264-27](#) [V7477Y](#) [143-L](#) [30270](#)
[1960052651N021](#) [FK 212 MI-CB](#) [FK 219 CB 3 MI](#) [FK 250 06 LF PAK](#) [FK 250 08 LF PAK](#) [FK 264 MI 220 O](#) [FK 265 MI 220 O](#) [FK 272 MI](#)
[247 V](#) [FK 278 MI 247 H](#) [FK 280 MI 247 H](#)