ADAM-6520 Series

5-port 10/100 Mbps Industrial Ethernet Switches



Features

- Supports full/half duplex flow control
- Supports MDI/MDI-X auto crossover
- Embedded with a switch controller, supports auto-negotiation
- Supports +10 ~ 30 V_{DC} voltage power input
- Provides surge (EFT) protection 3,000 V
- (ADAM-6520L not equipped)

 Supports 4,000 V_{DC} Ethernet ESD protection (ADAM-6520L not equipped)
- · Provides flexible mounting: DIN-rail, Wall, Stack
- Supports wide operating temperature range: -40 ~ 85° C (ADAM-65201)



Introduction

ADAM-6520 is a 5-port industrial-grade switch with Ethernet connectivity and from 10 to 100 Mbps transfer rates. (Auto-negotiation). Just like any other product in the ADAM family, ADAM-6520 can be mounted in three different ways: DIN rail, Wall and Stack. Solid industrial-grade design assures reliable operation in common application areas like: semi-conductor factories, inventory control environments, assembly lines, manufacturing and many more.

All modules support a wide voltage range of $+10 \sim 30 \text{ V}_{DC}$ over the terminal block, and $3{,}000 \text{ V}_{DC}$ surge (EFT) protection ensures that over-voltage is no concern. The wide operating temperature of ADAM-6520 goes from $-10 \sim 70^{\circ}$, while ADAM-65201 from $-40 \sim 85^{\circ}$. This permits them to be functional in harsh environments.

The six inclusive LED indicators make troubleshooting of the modules easier. Each port has a pair of LEDs that indicate link status and port activities. This easily informs users of any collisions, the link status, power failure and data receipts for immediate on-site diagnosis.

Specifications

Communications

Standard IEEE 802.3, 802.3u, 802.3x

LAN 10/100Base-TX
 Transmission Distance Up to 100 m
 Transmission Speed Up to 100Mbps

Interface

Connectors 5 x RJ-45

2-pin removable screw terminal (power)

• LED Indicators Power, Link/Speed

Power

Power Consumption ADAM-6520L: Max. 3W

ADAM-6520/6520I: Max. 2.4 W

■ Power Input 1 x Unregulated 10 ~ 30 V_{DC}

Mechanism

Dimensions (W x H x D) 70 x 102 x 27 mm

• **Enclosure** IP30, ABS+PC with solid mounting kits

Mounting DIN 35 rail, Wall, Stack

Protection

• ESD (Ethernet) $4,000 V_{DC}$ (ADAM-6520L not equipped) • Surge (EFT for power) $3,000 V_{DC}$ (ADAM-6520L not equipped)

Environment

• Operating Temperature

ADAM-6520: -10 ~ 70° C (14 ~ 158° F), Stack: -10 ~ 60° C (14 ~ 140° F) ADAM-6520L: 0 ~ 60° C (32 ~ 140° F), Stack: 0 ~ 50° C (32 ~ 122° F) ADAM-6520I: -40 ~ 85° C (-40 ~ 185° F), Stack: -40 ~ 75° C (-40 ~ 167° F)

Storage Temperature

ADAM-6520 : -20 ~ 80° C (-4 ~ 176° F) ADAM-6520L : -10 ~ 70° C (14 ~ 158° F) ADAM-6520I : -50 ~ 95° C (-58 ~ 203° F)

Operating Humidity
 Storing Humidity
 20 ~ 95 % (non-condensing)
 0 ~ 95 % (non-condensing)

■ MTBF 1.580.000 hrs

Certifications

Safety
 UL 60950-1, CAN/CSA-C22.2 No.60950

EMC
 U.S.A.: FCC Part 15 CISPR 22
 EU: EN55011, EN61000-6-4

EU: EN55011, EN61000-6-4 EN55022 Class A, EN61000-3-2/3 EN55024

IEC61000-4-2/3/4/5/6/8/11

EN61000-6-2

Ordering Information

ADAM-6520
 ADAM-6520L
 5-port 10/100 Mbps Industrial Ethernet Switch
 5-port 10/100 Mbps Industrial Unmanaged Ethernet

Switch

• **ADAM-6520I** 5-port 10/100 Mbps Industrial Ethernet Switch w/Wide

Operating Temperature

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Ethernet Modules category:

Click to view products by Advantech manufacturer:

Other Similar products are found below:

TDKEZW3 V23993-USB1029A 100-POE4 I210T1BLK X520QDA1 BCM84794A1KFSBG X520DA2OCP 808-38157 7506GX2 TC

EXTENDER 2001 ETH-2S 105FX-SC-MDR 110FX2-SC BCM54291B0IQLEG 7000-P3201-P050150 750-1415 750-494 750-495 750-612

750-613 750-627 750-643 750-940 753-440 753-540 753-650/003-000 852-1322 852-1328 852-1812 852-1813 852-1816 LANTICK PE
0-16 LANTICK PE-16-0 RBMTXLITE-L4X2.X.X.X.X. USR-TCP232-T2 2017008 EKI-7708E-4F-AE EKI-7708E-4FP-AE EKI-7708G
4FP-AE 2352903-2 753-620 EGU-0702-SFP-T SW-125 SW-525 SW-725 1005957 1006191 304TX-N WIZ107SR_TTL ES-320

TDKEZW5