Standard Cable Pull Switches - Latching with Reset




SID and SIN Latching with Reset Button






Pull Cable to change contact state, push button to reset

SID RAST



SIN RAST



Variant 1

Article No. Designation Max. span Type

611.2431.050 SID-UV1Z P-RAST 144.8 Ft. (35 Meters) Metal Body with Tension Monitor

601.3531.367 SIN-UV1Z P-RAST 196.8 Ft. (60 Meters) Metal Body with Tension Monitor

Variant 2

Article No. Designation Max. span Type

601.2441.907 SID-UV2Z P-RAST 59 Ft. (18 Meters) Metal Body with **Tension Monitor**

13 → 14 25 ★ 26 →

Variant 3

Article No. Designation Max. span Туре

Technical Information

Maximum Switching Voltage Maximum Switching Amperage B10d Mechanical Service Life Switching Frequency Operating Temperature **Protection Rating Utilization Category** Rate Insulation Voltage **Approvals**

240V 16A On Request 1 x 10⁶ ≤ 20/min -30 °C to +80 °C AC-15, U_e /I_e 240 V / 3 A 400VAC

240V 10A On Request 1 x 10⁶ ≤ 20/min -30 °C to +80 °C IP65 AC-15, U /I_e 240 V / 3 A 400VAC





X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Control Switches category:

Click to view products by Altech manufacturer:

Other Similar products are found below:

80887-99 80932-99 86855-00 88814-30 89721-12 89804-08 EX0011-1 SSN RL01801 50051857-17 50099156-001-05 51.155R-15200 50058920-26 KMK-PA RAL9005 M16 ACCU-SC/L-3000 PORTAPRO CFPS-73-48M WEL.PT-O6 WEL.PT-L8 WEL.PT-K7 WEL.PT-H7 WEL.PT-E9 WEL.PT-D7 WEL.PT-B7 WEL.PT-AA9 WEL.PT-AA8 WEL.PT-A8 WEL.LT-F WEL.LT-4 WEL.LT-1LX WEL.LT-1L WEL.ET-BB WEL.CT5B7 WEL.51361699 RGFRA1903041A1T PLC-60/75 PLC-30/40 PLC-24/30 PLC-40/55 LOC-MIKSER2 8522808 CC-100N V8Y-11Z-Y V8Y-11Z-R V8Y-11Z-O V8Y-11Z-24R V8Y-11Z-24O V8Y-11Z-230B V8Y-11-230W V8Y-11-230O