

FEATURES

- Current Monitoring 3-Phase
- 5A
- AC (16.6-400Hz)
- 2 x DPDT Outputs
- 22.5mm Wide Industrial Design

FUNCTIONS

- Overcurrent monitoring
- Overcurrent monitoring + latch
- Undercurrent monitoring
- Undercurrent monitoring + latch
- Window function
- Window function + latch



SPECIFICATIONS

Supply circuit

Terminals/Connections	A1-A2 (galvanically separated)
Supply Voltage	24-240V AC/ DC
Supply Voltage Tolerance	-15%...+10%
Rated Frequency	48 ... 400Hz (24-240VAC), 16-48Hz (48-240VAC)
Power Consumption	1.5 W (2 VA)
Duty Cycle	100%
Reset Time	100ms
Residual Ripple	-
Drop-out Voltage	>30% of Supply
Overvoltage Category	III (IEC 60661-1)
Rated Surge Voltage	4kV
Rated Insulation Voltage	400VAC

Time Delays

Start-up Suppression time	0-10s
Trip Delay	0.1-10s

Indicators

Green LED ON	Supply Voltage present
Green LED Flashes	Start-up Suppression Time
Yellow LED ON/OFF	Indicator Relay Output
Red LED ON/OFF	Failure of corresponding threshold
Red LED Flashes	Indicator tripping delay of corresponding threshold

Mechanical/ Environmental Specs

Housing Material	V2
Protection Degree	IP40 (Enclosure) IP20 (Terminals)
Mounting	DIN Rail
Mounting Position	any
Dimensions	22.5 x 90 x 108 mm
Stripping Length	7 mm
Terminal Torque	1.0 Nm (8.5 lb.in)
Wire size Terminals	20-14AWG
Ambient Temperature IEC	-25...+55°C (IEC 60068-1)
Ambient Temperature UL	-25...+40°C (UL 508)
Storage Temperature	-25...+70 °C
Transport Temperature	-25...+70 °C
Relative Humidity	15%...85% (IEC 60721-3-3 class 3K3)
Vibration Resistance	10..55 Hz 0.35 mm (IEC 60068-2-6)
Shock Resistance	15 g 11 ms (IEC 60068-2-27)
Pollution Degree	3 (IEC 60664-1)
Installation Altitude	Up to 2000 m above sea level

Output Circuit

Output Configuration	2 x DPDT (C/O)
Terminals Output 1	15-16-18
Terminals Output 2	25-26-28
Output Contact Rating	5A/ 250VAC
Mechanical Life	20 x 10 ⁶ Switching cycles
Electrical Life	2 x 10 ⁵ Switching cycles (1000 VA)
Utilization Category	AC 15
Switching Frequency	max. 60/min @ 100 VA resistive load max. 6/min @ 1000 VA resistive load (IEC 60947-5-1)
Rated Surge Voltage	4kV
Overvoltage Category	III (IEC 60664-1)

Measuring Circuit

Measurand	Current, 3-Phase, AC (16.6-400Hz)
Measuring Range	5A AC
Terminals	K-I1, K-I2, K-I3
Overload Capacity	6A AC permanent
Input Resistance	10 Ω
Switching Threshold Minimum	5% - 95% I _n
Switching Threshold Maximum	10% - 100% I _n
Rated Surge Voltage	4kV
Rated Insulation Voltage	440V AC
Overvoltage Category	III (IEC 60664-1)

Accuracy

Base Accuracy	≤3 % (from full scale)
Adjustment Accuracy	≤5 % (from full scale)
Repetition Accuracy	≤0.2 %
Voltage Influence	N/A
Temperature Influence	≤0.05 % / °C
Frequency Response	-10%...+5% (16.6..400 Hz)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Industrial Relays](#) category:

Click to view products by [Altech](#) manufacturer:

Other Similar products are found below :

[6-1617801-8](#) [CX-3958](#) [EV250-4A-02](#) [EV250-6A-01](#) [FCA-210-113](#) [FCA-325-159](#) [FCA-410-138](#) [1-1833005-4](#) [H-16/S1](#) [H-8C](#) [ACC530U20](#)
[AR7-41F11](#) [EB3L-S10SAN](#) [AVR907](#) [1618095-3](#) [1618104-9](#) [1618279-1](#) [BHR124Y](#) [N417](#) [2-1618398-1](#) [PBO-40A3040](#) [KA-3C-12A](#)
[SAH159](#) [SF5201F02](#) [301-17SX](#) [SL6H3-26.5VDC](#) [1618105-2](#) [1618276-6](#) [A837D](#) [A862B1](#) [ACC730-8025B](#) [SZ-RW4](#) [SZ-T13](#) [2-1616126-3](#)
[2-1618002-9](#) [2-1618100-8](#) [GCA800A100VACDC](#) [GM-4PDT-5D](#) [GQS-DPDT-6D](#) [CGE40-2P-20AN](#) [HFW12111S02](#) [M39016/9-013L](#)
[M39016/9-022L](#) [400-13PX](#) [401-45X](#) [4-1618248-5](#) [42RO-500S-SIL](#) [AVR869](#) [MDR-4088](#) [B466B](#)