



DIGITAL INDICATORS

DIVERSE APPLICATIONS

Frequency Indicators

- Covers a wide range from 10 Hz to 90 Hz for stable system performance.
- Works with 240V AC and 110V AC, ensuring compatibility across industries.
- Essential for industrial automation, electric vehicle chargers, marine & aviation, production lines, and testing labs to ensure operational stability.



Temperature Indicators

- Measures from -50°C to 80°C with high accuracy.
- Supports NTC/Molded sensors with a 1-meter standard wire length for flexible installation.
- Designed with IP65 front protection, ideal for harsh industrial environments.



Voltage Indicators

- Measures 65V AC - 280V AC, 80V AC - 150V AC, and 10V DC - 26V DC, suitable for diverse applications.
- $\pm 1\%$ accuracy ensures reliable voltage readings, preventing electrical failures.
- Used in renewable energy, medical equipment, data centers, construction, and railway systems for stable power monitoring.



Current Indicators

- Supports 0A to 100A (with CT) or 0A to 12A for various electrical applications.
- Helps detect abnormal current levels to prevent equipment damage.
- Used in industrial motors, pumps & compressors, HVAC systems, elevators, and manufacturing plants to optimize energy efficiency and safety.



Technical Specifications

Voltage Indicators

1	Rated Supply Voltage	240 V AC / 110 V AC / 24 V DC
2	Operating Supply Voltage	65 V AC - 280 V AC / 80 V AC - 150 V DC - 26 V DC
3	Input Current	< 50 mA
4	Input Wattage	0.6 - 0.9 W / <1 W
5	Frequency	50/60 Hz
6	Indicating Voltage	65 V AC - 280 V AC / 80 V AC - 150 V DC - 26 V DC
7	Tolerance / Accuracy	± 1%
8	Surge Test	2 KV AS PER IEC 61000-4-5
9	HV Rating	2 KV AS PER IEC 60243
10	EFT	2KV
11	Rated Insulation Voltage	500 V AC @ 1MΩ
12	Display Type	7 Segment 3 digit
13	Electrical Life	20K under normal operating condition
14	Dimensions	63 x 28 mm
15	Weight	25 g
16	Degree of Protection	Above Panel: IP65 For Terminals: IP20
17	Mounting Details	Mounting on Panel, 22.5 Dia Hole
18	Connectors	2 Pin - screw terminal (<0.75 to 1 sq.mm wire)
19	Screw Tightning Torque	0.8Nm
20	Housing Colour	Black
21	Illuminating lens colour	Red/Yellow/Blue/Green/Amber/White
22	Operating temperature	-20°C TO 60°C
23	Storage temperature	-30°C TO 65°C
24	Air humidity	10% - 95%
25	Compliance	RoHS, CE



Technical Specifications

Current Indicators

1	Rated Supply Voltage	240 V AC / 110 V AC / 24 V DC
2	Operating Supply Voltage	70 V AC - 270 V AC / 80 V AC - 150 V DC - 26 V DC
3	Input Current	< 50 mA
4	Input Wattage	0.6 - 0.9 W / <1 W
5	Frequency	50/60 Hz
6	Current Indication Range	0A to 100A with CT for single phase / 0A to 12A
7	Tolerance Scope	± 1A
8	Surge Test	2 KV AS PER IEC 61000-4-5
9	HV Rating	2 KV AS PER IEC 60243
10	EFT	2KV
11	Rated Insulation Voltage	500 V AC @ 1MΩ
12	Display Type	7 Segment 3 digit
13	Electrical Life	20K under normal operating condition
14	Dimensions	63 x 28 mm
15	Weight	25 g
16	Degree of Protection	Above Panel: IP65 For Terminals: IP20
17	Mounting Details	Mounting on Panel, 22.5 Dia Hole
18	Connectors	2 Pin - screw terminal (<0.75 to 1 sq.mm wire)
19	Screw Tightning Torque	0.8Nm
20	Housing Colour	Black
21	Illuminating lens colour	Red/Yellow/Blue/Green/Amber/White
22	Operating temperature	-20°C TO 60°C
23	Storage temperature	-30°C TO 65°C
24	Air humidity	10% - 95%
25	Compliance	RoHS, CE



Technical Specifications

Temperature Indicators

1	Rated Supply Voltage	240 V AC / 110 V AC / 24 V DC
2	Operating Supply Voltage	70 V AC - 270 V AC / 80 V AC - 150 V AC / 10 V DC - 26 V DC
3	Input Current	< 50 mA
4	Input Wattage	0.6 - 0.9 W / <1W
5	Frequency	50/60 Hz
6	Temperature Indication Range	-50°C TO 80°C
7	Tolerance Scope	$\pm$ ° 1
8	Sensor Type	NTC/ Molded
9	Sensor Wire Length	1 meter std
10	Surge Test	2 KV AS PER IEC 61000-4-5
11	HV Rating	2 KV AS PER IEC 60243
12	EFT	2KV
13	Rated Insulation Voltage	500 V AC @ 1M Ω
14	Display Type	7 Segment 3 digit
15	Electrical Life	20K under normal operating condition
16	Dimensions	63 x 28 mm
	Weight	25 g
17	Degree of Protection	Above Panel: IP65
18		For Terminals: IP20
19	Mounting Details	Mounting on Panel, 22.5 Dia Hole
20	Connectors	2 Pin - screw terminal (<0.75 to 1 sq.mm wire)
21	Screw Tightning Torque	0.8Nm
22	Housing Colour	Black
23	Illuminating lens colour	Red/Yellow/Blue/Green/Amber/White
24	Operating temperature	-20°C TO 60°C
25	Storage temperature	-30°C TO 65°C
26	Air humidity	10% - 95%
27	Compliance	RoHS, CE



Technical Specifications

Frequency indicators

1	Rated Supply Voltage	240 V AC / 110 V AC
2	Operating Supply Voltage	70 V AC - 270 V AC / 80 V AC - 150 V AC
3	Input Current	< 50 mA
4	Input Wattage	0.6 - 0.9 W / <1 W
5	Tolerance Scope	$\pm$ 1 Hz
6	Frequency Sensing Range	10 Hz to 90 Hz
7	Surge Test	2 KV AS PER IEC 61000-4-5
8	HV Rating	2 KV AS PER IEC 60243
9	Rated Insulation Voltage	500 V AC @ 1M Ω
10	Display Type	7 Segment 3 digit
11	Electrical Life	20K under normal operating condition
12	Dimensions	63 x 28 mm
13	Weight	25 g
14	Degree of Protection	Above Panel: IP65
15		For Terminals: IP20
16	Mounting Details	Mounting on Panel, 22.5 Dia Hole
	Connectors	2 Pin - screw terminal (<0.75 to 1 sq.mm wire)
17	Screw Tightning Torque	0.8Nm
18	Housing Colour	Black
19	Illuminating lens colour	Red/Yellow/Blue/Green/Amber/White
20	Operating temperature	-20°C TO 60°C
21	Storage temperature	-30°C TO 65°C
22	Air humidity	10% - 95%
23	Compliance	RoHS, CE



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [LED Panel Mount Indicators](#) category:

Click to view products by [Altech](#) manufacturer:

Other Similar products are found below :

[FL2870C8R](#) [FL2950WL8G](#) [FL589WL8R](#) [NL177WL3G](#) [PB22BM41K](#) [PB22SIM40Y](#) [PB22SKRS31KC](#) [LE177WL39007](#) [LE2821H5G](#)
[LE2950BWL39018](#) [LH1048BSWL3702](#) [LH1048BWL3702](#) [LH382A](#) [LH677G](#) [FL276WL7R](#) [FL2950BWL7R](#) [FL2950WL8R](#) [FL2951WL8G](#)
[FL67C7R](#) [FL67WL8G](#) [C430AABG2](#) [VL1CK0P600](#) [LE276C39017](#) [LE276WL39007](#) [LH10503700](#) [LH392A](#) [LH692R](#) [MS18235-1RT](#) [SSI-](#)
[LXH072GD12V150](#) [LH382G](#) [604-301-04](#) [679-1312-333F](#) [NL177WL2G](#) [NL276WL2G](#) [NL2870C3A](#) [NL2950BWL2A](#) [NL589WL2G](#)
[PB22BM60K](#) [LE276C39007](#) [2693.8321](#) [SSI-LXR1612ID16615](#) [682-3135-141F](#) [LH1048BWL3700](#) [249-7972-3732-801F](#) [814-0333-503](#)
[FL276WL7A](#) [1116-G12-CW](#) [QRM85BXXHR24E](#) [6773132321F](#) [6773332323F](#)