

# ATC 100 A Series Porcelain Superchip® Multilayer Capacitors

- Case A Size  
(.055" x .055")
- High Q
- Low ESR/ESL
- Low Noise
- Extended WVDC  
up to 250 VDC
- Capacitance Range  
0.1 pF to 100 pF
- Ultra-Stable Performance
- High Self-Resonance
- Established Reliability (QPL)

ATC, the industry leader, offers new improved ESR/ESL performance for the 100 A Series RF/Microwave Capacitors. This is ATC's most versatile high Q, high self resonant multilayer capacitor. High density porcelain construction provides a rugged, hermetic package.

Typical functional applications: Bypass, Coupling, Tuning, Feedback, Impedance Matching and DC Blocking.

Typical circuit applications: Microwave/RF/IF Amplifiers, Mixers, Oscillators, Low Noise Amplifiers, Filter Networks, Timing Circuits and Delay Lines.

## ENVIRONMENTAL TESTS

ATC 100 A Series Capacitors are designed and manufactured to meet and exceed the requirements of EIA-198, MIL-PRF-55681 and MIL-PRF-123.

### THERMAL SHOCK:

MIL-STD-202, Method 107, Condition A.

### MOISTURE RESISTANCE:


MIL-STD-202, Method 106.

### LOW VOLTAGE HUMIDITY:

MIL-STD-202, Method 103, Condition A, with 1.5 Volts DC applied while subjected to an environment of 85°C with 85% relative humidity for 240 hours min.

### LIFE TEST:

MIL-STD-202, Method 108, for 2000 hours, at 125°C. 200% WVDC applied.



## ELECTRICAL AND MECHANICAL SPECIFICATIONS

**QUALITY FACTOR (Q):** greater than 10,000 at 1 MHz.

**TEMPERATURE COEFFICIENT OF CAPACITANCE (TCC):**  
+90 ±20 PPM/°C (-55°C to +125°C)

### INSULATION RESISTANCE (IR):

0.1 pF to 100 pF:

10<sup>6</sup> Megohms min. @ +25°C at rated WVDC.

10<sup>5</sup> Megohms min. @ +125°C at rated WVDC.

### WORKING VOLTAGE (WVDC):

See Capacitance Values Table, page 2.

### DIELECTRIC WITHSTANDING VOLTAGE (DWV):

250% of rated WVDC for 5 secs.

**RETRACE:** Less than ±(0.02% or 0.02 pF), whichever is greater.

**AGING EFFECTS:** None

### PIEZOELECTRIC EFFECTS:

None

(No capacitance variation with voltage or pressure).

**CAPACITANCE DRIFT:** ±(0.02% or 0.02 pF), whichever is greater.

### OPERATING TEMPERATURE RANGE:

From -55°C to +125°C (No derating of working voltage).

**TERMINATION STYLES:** Available in various surface mount styles. See Mechanical Configurations, page 3.

**TERMINAL STRENGTH:** Terminations for chips and pellets withstand a pull of 5 lbs. min., 10 lbs. typical, for 5 seconds in direction perpendicular to the termination surface of the capacitor. Test per MIL-STD-202, method 211.



AMERICAN

ATC North America  
sales@atceramics.com

TECHNICAL

ATC Europe  
saleseur@atceramics.com

CERAMICS

ATC Asia  
sales@atceramics-asia.com



THE  
ENGINEERS'  
CHOICE®  
ISO 9001 REGISTERED  
COMPANY

THE ENGINEERS' CHOICE™

www.atceramics.com

ATC # 001-806 Rev. M 9/14

# ATC 100 A Capacitance Values

| CAP.<br>CODE | CAP.<br>(pF) | TOL.             | RATED WVDC |                     | CAP.<br>CODE | CAP.<br>(pF) | TOL.    | RATED WVDC |                     | CAP.<br>CODE | CAP.<br>(pF) | TOL.             | RATED WVDC |                     |
|--------------|--------------|------------------|------------|---------------------|--------------|--------------|---------|------------|---------------------|--------------|--------------|------------------|------------|---------------------|
|              |              |                  | STD.       | EXT.                |              |              |         | STD.       | EXT.                |              |              |                  | STD.       | EXT.                |
| 0R1          | 0.1          | B                | 150        | EXTENDED<br>VOLTAGE | 2R2          | 2.2          | B, C, D | 150        | EXTENDED<br>VOLTAGE | 160          | 16           | F, G, J,<br>K, M | 150        | EXTENDED<br>VOLTAGE |
| 0R2          | 0.2          |                  |            |                     | 2R4          | 2.4          |         |            |                     | 180          | 18           |                  |            |                     |
| 0R3          | 0.3          | B, C             |            |                     | 2R7          | 2.7          |         |            |                     | 200          | 20           |                  |            |                     |
| 0R4          | 0.4          |                  |            |                     | 3R0          | 3.0          |         |            |                     | 220          | 22           |                  |            |                     |
| 0R5          | 0.5          | B, C, D          |            |                     | 3R3          | 3.3          |         |            |                     | 240          | 24           |                  |            |                     |
| 0R6          | 0.6          |                  |            |                     | 3R6          | 3.6          |         |            |                     | 270          | 27           |                  |            |                     |
| 0R7          | 0.7          |                  |            |                     | 3R9          | 3.9          |         |            |                     | 300          | 30           |                  |            |                     |
| 0R8          | 0.8          |                  |            |                     | 4R3          | 4.3          |         |            |                     | 330          | 33           |                  |            |                     |
| 0R9          | 0.9          |                  |            |                     | 4R7          | 4.7          |         |            |                     | 360          | 36           |                  |            |                     |
| 1R0          | 1.0          |                  |            |                     | 5R1          | 5.1          |         |            |                     | 390          | 39           |                  |            |                     |
| 1R1          | 1.1          |                  |            | 5R6                 | 5.6          | 430          | 43      |            |                     |              |              |                  |            |                     |
| 1R2          | 1.2          |                  |            | 6R2                 | 6.2          | 470          | 47      |            |                     |              |              |                  |            |                     |
| 1R3          | 1.3          |                  |            | B, C, J,<br>K, M    | 6R8          | 6.8          | 510     |            | 51                  |              |              |                  |            |                     |
| 1R4          | 1.4          |                  |            |                     | 7R5          | 7.5          | 560     |            | 56                  |              |              |                  |            |                     |
| 1R5          | 1.5          | F, G, J,<br>K, M |            | 8R2                 | 8.2          | 620          | 62      |            |                     |              |              |                  |            |                     |
| 1R6          | 1.6          |                  |            | 9R1                 | 9.1          | 680          | 68      |            |                     |              |              |                  |            |                     |
| 1R7          | 1.7          | F, G, J,<br>K, M |            | 100                 | 10           | 750          | 75      |            |                     |              |              |                  |            |                     |
| 1R8          | 1.8          |                  |            | 110                 | 11           | 820          | 82      |            |                     |              |              |                  |            |                     |
| 1R9          | 1.9          |                  |            | 120                 | 12           | 910          | 91      |            |                     |              |              |                  |            |                     |
| 2R0          | 2.0          |                  |            | 130                 | 13           | 101          | 100     |            |                     |              |              |                  |            |                     |
| 2R1          | 2.1          |                  |            | 150                 | 15           |              |         |            |                     |              |              |                  |            |                     |

VRMS = 0.707 X WVDC


SPECIAL VALUES, TOLERANCES, HIGHER WVDC AND MATCHING AVAILABLE. PLEASE CONSULT FACTORY.

NOTE: EXTENDED WVDC DOES NOT APPLY TO CDR PRODUCTS.

## CAPACITANCE TOLERANCE

| Code | B       | C        | D       | F   | G   | J   | K    | M    |
|------|---------|----------|---------|-----|-----|-----|------|------|
| Tol. | ±0.1 pF | ±0.25 pF | ±0.5 pF | ±1% | ±2% | ±5% | ±10% | ±20% |

## ATC PART NUMBER CODE



The above part number refers to a 100 A Series (case size A) 10 pF capacitor, J tolerance (±5%), 150 WVDC, with W termination (Tin/Lead, Solder Plated over Nickel Barrier), laser marking and ATC Tape and Reel packaging.

ATC accepts orders for our parts using designations **with** or **without** the "ATC" prefix. Both methods of defining the part number are equivalent, i.e., part numbers referenced with the "ATC" prefix are interchangeable to parts referenced without the "ATC" prefix. Customers are free to use either in specifying or procuring parts from American Technical Ceramics.

For additional information and catalogs contact your ATC representative or call direct at (+1-631) 622-4700.

Consult factory for additional performance data.





A M E R I C A N T E C H N I C A L C E R A M I C S

ATC North America  
sales@atceramics.com

ATC Europe  
sales@atceramics.com

ATC Asia  
sales@atceramics-asia.com

# ATC 100 A Capacitors: Mechanical Configurations

| ATC SERIES & CASE SIZE | ATC TERM. CODE | MIL-PRF-55681 | CASE SIZE & TYPE                                                                                                    | OUTLINES<br><br>W/T IS A TERMINATION SURFACE                                      | BODY DIMENSIONS<br>INCHES (mm)                  |                            |                     | LEAD AND TERMINATION<br>DIMENSIONS AND MATERIALS |                                                                         |
|------------------------|----------------|---------------|---------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------|----------------------------|---------------------|--------------------------------------------------|-------------------------------------------------------------------------|
|                        |                |               |                                                                                                                     |                                                                                   | LENGTH<br>(L)                                   | WIDTH<br>(W)               | THICKNESS<br>(T)    | OVERLAP<br>(Y)                                   | MATERIALS                                                               |
| 100A                   | W              | CDR12BG       | A <br>Solder Plate                 |  | .055<br>+.015 -.010<br>(1.40<br>+0.38<br>-0.25) | .055 ±.015<br>(1.40 ±0.38) | .057 (1.45)<br>max. | .010<br>+.010 -.005<br>(0.25<br>+0.25 -0.13)     | Tin/Lead, Solder Plated<br>over<br>Nickel Barrier Termination           |
| 100A                   | P              | CDR12BG       | A <br>Pellet                       |  | .055<br>+.025 -.010<br>(1.40<br>+0.64<br>-0.25) | .055 ±.015<br>(1.40 ±0.38) | .057 (1.45)<br>max. | .010<br>+.010 -.005<br>(0.25<br>+0.25 -0.13)     | Heavy Tin/Lead Coated,<br>over<br>Nickel Barrier Termination            |
| 100A                   | T              | N/A           | A <br>Solderable<br>Nickel Barrier |  | .055<br>+.015 -.010<br>(1.40<br>+0.38<br>-0.25) | .055 ±.015<br>(1.40 ±0.38) | .057 (1.45)<br>max. | .010<br>+.010 -.005<br>(0.25<br>+0.25 -0.13)     | <b>RoHS Compliant</b><br>Tin Plated over<br>Nickel Barrier Termination  |
| 100A                   | CA             | CDR11BG       | A <br>Gold Chip                    |  | .055<br>+.015 -.010<br>(1.40<br>+0.38<br>-0.25) | .055 ±.015<br>(1.40 ±0.38) | .057 (1.45)<br>max. | .010<br>+.010 -.005<br>(0.25<br>+0.25 -0.13)     | <b>RoHS Compliant</b><br>Gold Plated over<br>Nickel Barrier Termination |

For a complete military catalog, request American Technical Ceramics document ATC 001-818.




A M E R I C A N   T E C H N I C A L   C E R A M I C S

ATC North America  
sales@atceramics.com

ATC Europe  
sales@atceramics.com


ATC Asia  
sales@atceramics-asia.com

# ATC 100 A Non-Magnetic Capacitors: Mechanical Configurations

| ATC SERIES & CASE SIZE | ATC TERM. CODE | MIL-PRF-55681      | CASE SIZE & TYPE                                                                                                  | OUTLINES<br>W/T IS A TERMINATION SURFACE                                          | BODY DIMENSIONS<br>INCHES (mm)                |                            |                     | LEAD AND TERMINATION<br>DIMENSIONS AND MATERIALS |                                                                           |
|------------------------|----------------|--------------------|-------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------|----------------------------|---------------------|--------------------------------------------------|---------------------------------------------------------------------------|
|                        |                |                    |                                                                                                                   |                                                                                   | LENGTH<br>(L)                                 | WIDTH<br>(W)               | THICKNESS<br>(T)    | OVERLAP<br>(Y)                                   | MATERIALS                                                                 |
| 100A                   | WN             | Meets Requirements | A <br>Non-Mag Solder Plate       |  | .055<br>+.025 -.010<br>(1.40<br>+.64<br>-.25) | .055 ±.015<br>(1.40 ±0.38) | .057 (1.45)<br>max. | .010<br>+.010 -.005<br>(0.25<br>+.025 -.013)     | Tin/Lead, Solder Plated over Non-Magnetic Barrier Termination             |
| 100A                   | PN             | Meets Requirements | A <br>Non-Mag Pellet             |  | .055<br>+.035 -.010<br>(1.40<br>+.89<br>-.25) | .055 ±.015<br>(1.40 ±0.38) | .057 (1.45)<br>max. | .010<br>+.010 -.005<br>(0.25<br>+.025 -.013)     | Heavy Tin/Lead Coated, over Non-Magnetic Barrier Termination              |
| 100A                   | TN             | Meets Requirements | A <br>Non-Mag Solderable Barrier |  | .055<br>+.025 -.010<br>(1.40<br>+.64<br>-.25) | .055 ±.015<br>(1.40 ±0.38) | .057 (1.45)<br>max. | .010<br>+.010 -.005<br>(0.25<br>+.025 -.013)     | <b>RoHS Compliant</b><br>Tin Plated over Non-Magnetic Barrier Termination |

All 100 A Capacitors are available laser marked with ATC's identification, capacitance code and tolerance.

## Suggested Mounting Pad Dimensions



Horizontal Electrode Orientation

Vertical Electrode Orientation

Case A

|                  | Pad Size     | A Min. | B Min. | C Min. | D Min. |
|------------------|--------------|--------|--------|--------|--------|
| Vertical Mount   | Normal       | .070   | .050   | .030   | .130   |
|                  | High Density | .050   | .030   | .030   | .090   |
| Horizontal Mount | Normal       | .080   | .050   | .030   | .130   |
|                  | High Density | .060   | .030   | .030   | .090   |

Dimensions are in inches.

A M E R I C A N   T E C H N I C A L   C E R A M I C S

ATC North America  
sales@atceramics.com


ATC Europe  
saleseur@atceramics.com

ATC Asia  
sales@atceramics-asia.com


www.atceramics.com

# ATC 100 A Performance Data


**ESR VS. CAPACITANCE**  
**ATC SERIES 100, CASE A**




**Q VS. CAPACITANCE**  
**ATC SERIES 100, CASE A**




**SERIES RESONANCE VS. CAPACITANCE**  
**ATC SERIES 100, CASE A**



**CURRENT RATING VS. CAPACITANCE**  
**ATC SERIES 100, CASE A**



**CAPACITANCE CHANGE VS. TEMPERATURE**  
**ATC SERIES 100, CASE A**



**A M E R I C A N   T E C H N I C A L   C E R A M I C S**


ATC North America  
sales@atceramics.com

ATC Europe  
sales@atceramics.com


ATC Asia  
sales@atceramics-asia.com

# ATC 100 A Performance Data

**CURRENT RATING VS. CAPACITANCE**  
**ATC SERIES 100, CASE A, EXTENDED VOLTAGE**



**CURRENT RATING VS. CAPACITANCE**  
**ATC SERIES 100, CASE A, EXTENDED VOLTAGE**



Sales of ATC products are subject to the terms and conditions contained in American Technical Ceramics Corp. Terms and Conditions of Sale (ATC document #001-992 Rev. B 12/05). Copies of these terms and conditions will be provided upon request. They may also be viewed on ATC's website at [www.atceramics.com/productfinder/default.asp](http://www.atceramics.com/productfinder/default.asp). Click on the link for Terms and Conditions of Sale.

ATC has made every effort to have this information as accurate as possible. However, no responsibility is assumed by ATC for its use, nor for any infringements of rights of third parties which may result from its use. ATC reserves the right to revise the content or modify its product without prior notice.

© 1996 American Technical Ceramics Corp. All Rights Reserved.

ATC # 001-806 Rev. M 9/14



**AMERICAN**

ATC North America  
[sales@atceramics.com](mailto:sales@atceramics.com)

**TECHNICAL**

ATC Europe  
[saleseur@atceramics.com](mailto:saleseur@atceramics.com)

**CERAMICS**

ATC Asia  
[sales@atceramics-asia.com](mailto:sales@atceramics-asia.com)



THE  
ENGINEERS'  
CHOICE®

ISO 9001 REGISTERED  
COMPANY

**THE ENGINEERS' CHOICE™**

**[www.atceramics.com](http://www.atceramics.com)**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for*** [Multilayer Ceramic Capacitors MLCC - SMD/SMT](#) ***category:***

***Click to view products by*** [American Technical Ceramics](#) ***manufacturer:***

Other Similar products are found below :

[M39014/01-1467](#) [M39014/02-1218V](#) [M39014/02-1225V](#) [M39014/02-1262V](#) [M39014/02-1301](#) [M39014/22-0631](#) [1210J5000102JCT](#)  
[1210J2K00102KXT](#) [1210J5000103KXT](#) [1210J5000223KXT](#) [D55342E07B379BR-TR](#) [D55342E07B523DR-T/R](#) [1812J1K00103KXT](#)  
[1812J1K00473KXT](#) [1812J2K00680JCT](#) [1812J4K00102MXT](#) [1812J5000102JCT](#) [1812J5000103JCT](#) [1812J5000682JCT](#) [NIN-FB391JTRF](#)  
[NIN-FC2R7JTRF](#) [NPIS27H102MTRF](#) [C1206C101J1GAC](#) [C1608C0G1E472JT000N](#) [C2012C0G2A472J](#) [2220J2K00101JCT](#)  
[KHC201E225M76N0T00](#) [LRC-LRF1206LF-01R025FTR1K](#) [1812J1K00222JCT](#) [1812J2K00102KXT](#) [1812J2K00222KXT](#)  
[1812J2K00472KXT](#) [2-1622820-7-CUT-TAPE](#) [2220J3K00102KXT](#) [2225J2500824KXT](#) [CCR07CG103KM](#) [CGA2B2C0G1H010C](#)  
[CGA2B2C0G1H040C](#) [CGA2B2C0G1H050C](#) [CGA2B2C0G1H060D](#) [CGA2B2C0G1H070D](#) [CGA2B2C0G1H151J](#) [CGA2B2C0G1H1R5C](#)  
[CGA2B2C0G1H2R2C](#) [CGA2B2C0G1H3R3C](#) [CGA2B2C0G1H680J](#) [CGA2B2C0G1H6R8D](#) [CGA2B2X8R1H221K](#) [CGA2B2X8R1H472K](#)  
[CGA3E1X7R1C474K](#)