

1. MATERIALS AND FINISHES:
BODY, REAR BODY, COUPLING NUT, CAP
& INNER FERRULE - BRASS, NICKEL PLATING
CONTACT - BeCu, GOLD PLATING
INSULATOR - PTFE, NATURAL
RETAINING RING - PHOSPHOR BRONZE, NICKEL PLATING
GASKET - SILICONE RUBBER, RED

2. ELECTRICAL:

- A. IMPEDANCE: 50 OHM
- B. FREQUENCY RANGE: DC - 7.1 GHz
- C. VSWR: 1.30 MAX. @ DC - 3 GHz
1.40 MAX. @ 3 - 6 GHz
- D. DIELECTRIC WITHSTANDING VOLTAGE: 500 VRMS. MIN.


3. MECHANICAL:
A. DURABILITY: 500 CYCLES MIN.
B. TEMPERATURE RANGE: -65°C TO +165°C

4. PACKAGING:
A. QUANTITY: SINGLE PACK
B. MARKING: PACKAGING TO BE MARKED
"AMPHENOL RF, 31-6981 AND DATE CODE"
C. CAP AND INNER FERRULE ARE PACKAGED LOOSE.


5. CABLE ASSEMBLY INSTRUCTIONS:

- A. TRIM CABLE AS SHOWN (TWO STAGE TRIM).
- B. INSERT CABLE THROUGH INNER FERRULE AND PEEL BRAID BACK, OVER INNER FERRULE
- C. INSERT CABLE INTO THE CONNECTOR.
- D. SOLDER CONTACT TO CABLE CENTER CONDUCTOR.
- E. CRIMP BODY OVER INNER FERRULE USING 0.105" HEX.
- F. PRESS CAP FLUSH.

INTERFACE PER
RP TNC PLUG




RECOMMENDED CABLE STRIPPING DIMENSIONS (TRIM 1)




RECOMMENDED CABLE STRIPPING DIMENSIONS (TRIM 2)

REVISIONS				
REV	DESCRIPTION	DATE	ECN	BY
A	RELEASE TO MFG.	24-SEP-24	17177	SH



SCALE 1.500



CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

NOTICE: These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE METRIC (INCHES) AND TOLERANCES ARE:

<0.5mm = ±0.05mm	[<0.020 = ±0.002]
>0.5 - 6mm = ±0.1mm	[>0.020 - 0.236 = ±0.004]
>6.00 - 30mm = ±0.2mm	[>0.236 - 1.181 = ±0.008]
>30.00 - 120mm = ±0.3mm	[>1.181 - 4.725 = ±0.012]

[illegible]

SEE NOTES

ENGR.2
JACK LIANG

DATE	22-FEB-21
------	-----------

TITLE

RP TNC RA PLUG
FOR 0.81 MM CABLE

SHEET NO. 2 OF 2

SCALE: 6.5:1.0

Amphenol RF

SIZE	DRAWING NO. 31-6981
------	---------------------

ITEM NO. 31-6981

PART NO. 31-6981

REV

A

THIRD ANGLE PROJ.



REFERENCE

EAR#
10195

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Connectors / Coaxial Connectors](#) ***category:***

Click to view products by [Amphenol](#) ***manufacturer:***

Other Similar products are found below :

[6002-7051-003](#) [6059674-1](#) [630059-000](#) [M55339/15-00491](#) [7002-1541-010](#) [7002-1572-002](#) [7003-1572-002](#) [7004-1512-000](#) [7009-1511-004](#)
[7105-1521-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7405-1521-005](#) [7405-1521-019](#) [7405-1521-802](#) [755-74-5](#) [7706-2](#) [873183](#)
[PL375-33](#) [95-850-148-3](#) [R107003010W](#) [R112186000](#) [R113082097](#) [R113236000](#) [R113240097](#) [R114083000](#) [R114670000W](#) [R121053000](#)
[R124072220W](#) [R124076450](#) [R124175123](#) [R125075001](#) [R125414001](#) [R125415030](#) [R125415271](#) [R141007161](#) [R141574161W](#)
[R142004000W](#) [R142076000W](#) [R142076161W](#) [R142184000W](#) [R142676700](#) [R143012000](#) [R143075000W](#) [R143089117](#) [R143235161W](#)
[R143292700](#) [R143557000](#) [R161008000](#)