




THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF AMPHENOL LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY AMPHENOL LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2020/01/20	Vicky	Initial Released
B	C220468	2022/03/25	Vicky	$\triangle B$ X2
C	C230130	2023/02/09	Ruru	$\triangle C$ X2



- Note:
- * RoHS Compliant
 - * ⌀ Important dimension
 - * C1
 - $\triangle C$ Waterproof rate: IP68, mated 1m/24h
 - Housing: Thermoplastic, Black
 - Pin: Copper alloy, Gold plated
 - O-Ring: Rubber, Dark gray
 - Nut: Thermoplastic, Black
 - Outer Mold: Thermoplastic, Black
 - * C2
 - $\triangle C$ Waterproof rate: IP68, mated 1m/24h
 - Housing: Thermoplastic, Black
 - Pin: Copper alloy, Gold plated
 - O-Ring: Rubber, Dark gray
 - Nut: Thermoplastic, Black
 - Outer Mold: Thermoplastic, Black
 - Cable: UL21388, PVC Jacket, Black
 - * Cable length tolerance:

0.5M < L \leq 1M	+60/-0 mm
1M < L \leq 3M	+120/-0 mm
3M < L \leq 5M	+160/-0 mm
5M < L \leq 10M	± 100 mm
10M < L \leq 20M	± 200 mm
20M < L \leq 30M	± 300 mm
30M < L \leq 99M	± 500 mm

UNIT: mm	⌀	⌒	TITLE
TOLERANCE			ACC, XLOK, B-10A, DB-ENDED FF
± 0.5 mm	SCALE	SIZE	SHEET
	1:2	A4	1 OF 2
	REV. C	WC-REV. A.5	⌀ : Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO.	DRAWN BY	DATE
	Vicky	2020-01-20
DWG NO.	CHECKED BY	DATE
AB-BBXXFR-BBBR-QDXXX	Rita	2020-01-20
CUSTOMER	APPROVED BY	DATE
ALTW	Max	2020-01-20

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

3P	PVC	6.5	16	AB-BB03FR-BBBR-QDXXX
2P		6.0		AB-BB02FR-BBBR-QDXXX
Contacts	Cable Jacket	Cable OD	AWG	Item No.

AB-BB XX FR-BBBR-QD XXX

△ XX: No. Of Pin

XXX: 0.5~99Meters
 A05: 0.5 Meter
 001: 01 Meter
 002: 02 Meters
 :
 099: 99 Meters

Pin Out	2	Red	紅	2	Brown	棕	3	Red	紅
	1	Black	黑	1	Black	黑	1	Black	黑
	Pin #	Wire		Pin #	Wire		Pin #	Wire	
C2									
	2P			3P					
C1									
	2P			3P					

Pin Assignments Front View

UNIT:mm			TITLE
TOLERANCE	±0.5mm		ACC, XLOK, B-10A, DB-ENDED FF
SCALE	1:2	SIZE	A4
REV.	C	SHEET	2 OF 2
		WC-REV.	A.5
		QC: Inspection item	

Amphenol LTW
 安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
DWG NO	CHECKED BY	DATE
CUSTOMER	APPROVED BY	DATE
ALTW	Vicky Rita Max	2020-01-20 2020-01-20 2020-01-20

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Sensor Cables / Actuator Cables](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[60963](#) [60964](#) [M83513/19-F01CP](#) [703000D02F2002](#) [703000D02F300](#) [703001D02F1201](#) [704000D02F120](#) [802027213811-1](#) [84914-0235](#)
[883030A09M050](#) [884031A09M005](#) [8R4006A18M010](#) [1200980008](#) [1200980031](#) [1211810021](#) [1400637](#) [1401201](#) [1401348](#) [1405278](#)
[1408644/94F/8](#) [1455311](#) [1513981](#) [1550119](#) [1554212](#) [1R3006A20A120G](#) [1R4004A17A120](#) [1R4006A20A1202](#) [1R4006A39M005](#) [2289297-6](#)
[8R3006A16A1203](#) [8R5E36E03M020](#) [2R7004A20F060](#) [301000A01F200](#) [301002A01F120](#) [2289297-1](#) [2289297-8](#) [2289297-9](#)
[302000A01F120](#) [CONM6A-S2](#) [332021A01F200](#) [3R1006A20F030](#) [3R9006A20A1201](#) [403001A10M040](#) [4030P1A10M040](#) [41-01023](#)
[MBCC-412](#) [1R3G06A20A120](#) [543031A10M010](#) [884030A09M100](#) [883033A09M020](#)