

NOTES: UNLESS OTHERWISE SPECIFIED

1. PLUG MATERIAL:

SHELL: ZINC ALLOY, NICKEL PLATED COUPLING RING: ALLUMINUM ALLOY, NICKEL PLATED INSERT AND RETAINING RING: THERMOPLASTIC SEAL: SILICONE RUBBER

2. BACKSHELL MATERIAL:


SHELL: ALUMINIUM ALLOY, NICKEL PLATED; LATCH SEGMENT: ALUMINIUM ALLOY, NICKEL PLATED; SCREW AND LOCK WASHER: STAINLESS STEEL; BUSHING: EPDM.

3. SPECIFICATIONS:


- 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
- 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
- 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25℃.
- 3.4 MOISTURE RESISTANCE: IP67 & IP69K (MATED CONDITION).
- 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT

4. APPLY TO CABLE OD SIZE: Ø11.20-Ø24.08 . CAN BE USED:

- 4.1. WITH LARGE AND SMALL BUSHINGS IN PLACE.
- 4.2. WITH ONLY LARGE BUSHING IN PLACE.
- 4.3. WITH BOTH BUSHINGS REMOVED.
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 6. SEE SPECIFIC PLUG DRAWING FOR:
 - 6.1 CONTACT SIZE AND WIRE RANGE.
 - 6.2 RETAINING RING COLOR.
 - 6.3 MATING PART(S).
 - 6.4 CONTACT LAYOUT AND ALL OTHER SPECIFICATIONS.







	AHDM06-2	HD36-24-23PN-059							
	PART N	DESCRIPTION				ITEM			
QUANTITY	MATERIA				ALS LI	ST			
	UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 3) Fractions ±1/64 Angles ±1* 3) Note reference = X		ES DA	TE	Amphenol				
2) Tolerances are a			16MAF	R2020					
2 PL DEC ±0.15					Sine Systems - www.amphenol-sine.com				
3) Note reference			44724 Morley Drive Clinton Township, MI 48036			036			
MATERIAL SPECIFICA	MATERIAL SPECIFICATIONS: PROCESS SPECIFICATIONS:				-	ΓΕ AHDM PLUG, S	,	HD,	
PROCESS SPECIFICA			SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO MORMAL		KIT W/ CABLE CLAMP BACKSHELL				
PROCESS SPECIFICA					в С-	AHDM06-24-2		A1	
NEXT ASSY:		MANUFACTURING VARIATIONS.		SCALE: NONE		SHEET 1 OF	1		

DWG NO: AHDM06-24-23PN-059 REV: A

KIT,PLUG AND BACKSHELL,SZ 24

REV: A1 SH: 1

AT Series™ - Contact Size 16 Options

Machined Contacts, Sockets & Pins				
Part Number	Description		AWG	Туре
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined
AT60-215-16141 Male Contact - Pin, Nickel-plated		16	14	Machined
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined
AT62-201-16141-22	Female Contact - Socket, Nickel-plated	16	22-24	Machined

Tooling - Machined Contacts			
Part	Part Number	Description	
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)	
3	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)	

Contact Removal Tools				
Part	Part Number Description			
3	ATRT-100	Used for removal of contacts for A Series™ products		
	AT11-310-1605	Contact Removal Tool, Plastic, Size 16		
	A114017	Sealing Plug, Size 16, White		

Stamped & Formed Contacts, Sockets & Pins				
Part Number	Description		AWG	Туре
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed

Tooling - Stamped & Formed Contacts			
Part	Part Number	Description	
	MFX-3950	Crimp Die - Size 16, 18-20AWG (S&F contacts only)	
	MFX-3953	Crimp Die - Size 16, 16-18AWG (S&F contacts only)	
	MFX-3975	Crimp Die - Size 16, 14-16AWG (S&F contacts only)	
	MFX-3990	Crimp Die - Size 16, 20-22AWG (S&F contacts only)	
	ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG (S&F contacts only)	
	ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG (S&F contacts only)	
	ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG (S&F contacts only)	

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Standard Circular Connector category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

5M2530B10P 600259N006 600273N007 6134-336-13149 6134-337-11149 6134-337-2390 6134-341-17149 6280-4SG-516 6280-7SG-3DC 6290 6291A 66200A-10 680-SMG 681-PMG CXS3102A14S2P CXS3102A181S 7251-6SG-300 7271-6SG-300 7282-3PG-300-CH3 75-474014-05S 75-474618-01S 75-474618-04P 75-474618-04S 799539-000 MI8-SE 805-005-07NF11-19PC 805-005-07NF15-7PA 8280-4PG-516 8280-7PG-519 8282-5PG-519 836783-1 MP-4102-25P-C 862256-1 864019-2 866857-1 867865-1 PT01SP-14-18P PT08P-14-5S PTSF06SE-14-12S 120-1833-000 QCM019PC2DC012B 1-2069279-1 121583-0217 121667-0020 129591AU 1000B BULK RD10A16-19-P6CS051/1 RD10A20-31-P8CS051/1 RD16A14-12-S6CS051/2 1301240290 1301240347