

SNS1PBNC Drop Connectors - Snap-N-Seal One-Piece BNC Compression Connector



For more Information
please call

1-800-Belden1



General Description:

Snap-N-Seal One-Piece BNC Compression Connectors, Compression BNC

Usage (Overall)

Suitable Applications: Broadcast, CATV

Physical Characteristics (Connectivity)

Product Family:

Part Number	Cable Type	Center Conductor (mm)	Cable O.D. (mm)	Post I.D. (mm)	Inner Pack	Sleeve I.D. (mm)	Sleeve Color	Outer Pack	Tool
SNS1P59BNC	RG59, 1505A, 9167, 9275, 8241	0.559	0.914	3.912	10	6.426	Orange	50	SNSUTL, CST596711, CST596
SNS1P59QSBNC	RG59 Quad Shield	0.559	1.067	3.912	10	6.985	Green	50	SNSUTL, CST596711, CST596
SNS1P6BNC	RG6	0.813	1.016	4.851	10	7.366	Blue	50	SSNSUTL, CST596711, CST596
SNS1P6QSBNC	RG6 Quad Shield	0.813	1.016	4.851	10	8.001	Violet	50	SNSUTL, CST596711, CST596
SNS1P6UBNC	RG6, RG6 Quad Shield	0.813	1.016	4.851	10	7.442	Red	50	SNSUTL, CST596711, CST596
SNS1P59HECBNC	F59 HEC-2, S59HEC, 02240V, 02241V	0.559	0.914	3.912	10	7.366	White	50	SNSUTL, CST596711, CST59

Connector Type:	BNC Compression
Nut:	Zinc Alloy with Nickel Plate
Body Components:	Brass
Body Finish:	Nickel
Terminal/Contact:	Beryllium Copper with Silver Plate
Insulators:	TPX
O-Rings:	Ethylene Propylene

Mechanical Characteristics (Connectivity)

Cable Insertion Force (Max./lbs.):	<20
Cable Retention Force:	40 lbs. min. per SCTE IPS-SP-404
Temperature Rating:	-40°F To +140°F

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	11/27/2008

Electrical Characteristics (Overall)

Frequency Range:	5 MHz TO 1 GHz
Nominal Impedance:	75 Ohms
Return Loss (typical):	-30 dB up to 1 GHz
Insertion Loss:	<=-0.20 dB up to 1 GHz
RFI Shielding (typical):	-65 dB

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

METRIC MEASUREMENT VERSION

SNS1PBNC Drop Connectors - Snap-N-Seal One-Piece BNC Compression Connector

Revision Number: 0 Revision Date: 08-26-2011

© 2017 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Connectors / Coaxial Connectors](#) category:

Click to view products by [Belden](#) manufacturer:

Other Similar products are found below :

[R125315120](#) [8915-1511-000](#) [89674-0827](#) [5916-1103-603](#) [0106-001-000](#) [6-0001-3](#) [6001-7071-019](#) [6002-7051-003](#) [6002-7551-202](#) [6059674-1](#) [619550-1](#) [630059-000](#) [M39012/25-0021](#) [M39012/79-3008](#) [M39030/3-01N](#) [M39030/3-03N](#) [M3933/25-36N](#) [6500-7071-046](#) [6501-1071-002](#) [M83723/72W2457N](#) [6769](#) [CX050L2AQ](#) [7002-1541-010](#) [7002-1572-002](#) [7003-1572-002](#) [7004-1512-000](#) [7009-1511-004](#) [7010-1511-000](#) [7029-1511-060](#) [7101-1541-010](#) [7101-1571-002](#) [7105-1521-002](#) [7145-1521-002](#) [7209-1511-011](#) [7210-1511-012](#) [7210-1511-015](#) [7210-1511-019](#) [7225-1512-050](#) [7242-1511-000](#) [73137-5015](#) [73251-0111](#) [73251-0672](#) [7325-1512-000](#) [73276-1501](#) [73366-0013](#) [73404-2300](#) [73413-6080](#) [73415-5721](#) [7405-1521-005](#) [7405-1521-802](#)