






		1	2	3	4				
A						产品编号			
						HAY420A			
						产品名称			
						5557-nA/nAW			
B	5557-NA								
									
C	5557-NAW								
									
E	Dimensional & Ordering Information								
	poles		2-24 poles						
	Pitch between ploes		4.20mm						
	Rated Voltage		300V AC,DC						
	Rated current		9.0A						
	Withstand Voltage		1500V.AC/minute						
	Insulation Resistance		≥1000MΩ						
	Temperaure Range		-25℃~+85℃						
	Applicable Wire		AWG#28~#20						
	F	ECN NO.		UNIT	TOLERANCE	PROJECTION	DRAWING		CHECK
NEW DRAWING		mm	. *** ±0.08 . ** ±0.15 . * ±0.25		张建斌		程海洋	周顺招	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) *category:*

Click to view products by [Boom](#) *manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)